

# CREATING ACTIVITIES

Source : Guidewire Educational Platform

## Creating Activities



# Lesson objectives

**By the end of this lesson, you will be able to:**


- Create and configure activity patterns
- Create and configure activities



## Activity overview


# Activity

- An **activity** represents a task that someone must attend to or an issue that someone should be aware of
- Used to:
  - Let automatic processes assign work to user
  - Let a user assign work to another user
  - Alert user to certain event, such as an underwriting issue





# Activity parent objects

- Every activity is associated with an account
- Can also be associated with a job (and its subtypes) or a policy, which implicitly links it to their account, which implicitly links it to their account



# When are activities created?

- Automatically during policy job
  - Typically created when work must be done by a user to move the job forward
- Automatically by
  - Business rule
  - Gosu code
  - Workflow
- Manually by end user
  - Typically done to request work to be done by another user





**Activity pattern**



# Activity patterns

- Activity patterns are templates that standardize how activities are generated
- Both the user interface and Gosu code create activities based on these patterns

## Activity pattern



**Subject = Rate Policy**  
**Priority = medium**  
**Due Days = 5**  
**Escalation Days = 10**

## Activity



**Subject: Rate Policy**  
**Priority: medium**  
**Due Date: May 12**  
**Escalation Date: May 17**

# Managing activity patterns

- Activity patterns are typically created and modified by administrators
- Administration tab > Business Settings > Activity Patterns
- To create a new activity pattern, click the New Activity Pattern button
  - Code field is a unique internal name for the pattern and is used to reference an activity pattern in Gosu
- To edit an existing activity pattern, click the name of the activity pattern in the list
  - Changes to an activity pattern affect only activities from that point forward



## Creating activities in Gosu



# Using activity patterns in Gosu

- There are two operations that you can perform in Gosu involving activity patterns
  - One is to test which activity pattern an existing activity uses
    - `Entity.ActivityPattern.Code == "pattern_code"`
  - The other is to retrieve an activity pattern for use in creating a new activity
    - `ActivityPattern.finder.getActivityPatternByCode( "pattern_code" )`
    - Returns an ActivityPattern object
- Use the activity pattern code to refer to an activity pattern in Gosu code
  - Do not use a pattern ID or PublicID value

# Create activity related to an account

- Gosu code

*activityPattern.createAccountActivity(bundle, activityPattern, Account, subject, description, approvalIssue, priority, mandatory, targetDate, escalationDate)*

or

*account.newActivity(activityPattern)*

- Example

```
var anAccount : Account
var anActivityPattern : ActivityPattern
anActivityPattern = ActivityPattern.finder.getActivityPatternByCode("notification")
anAccount.newActivity(anActivityPattern)
```

# Create activity related to a policy

- Gosu code

*activityPattern.createPolicyActivity(bundle, policy, subject, description, approvalIssue, priority, mandatory, targetDate, escalationDate)*

- Example

```
if(policy != null) {  
    var a : Activity  
    var pattern = ActivityPattern.finder.getActivityPatternByCode("coverage")  
    a = pattern.createPolicyActivity(  
        policy.Bundle,  
        policy,  
        "Verify coverage",  
        "Call customer to verify coverage",  
        null,  
        typekey.Priority.TC_NORMAL,  
        false,  
        null,  
        null)  
}
```

- By default, an activity is always related to an account

# Create activity related to a job

- Gosu code

*activityPattern.createJobActivity(bundle, job, subject, description, approvalIssue, priority, mandatory, targetDate, escalationDate)*

- Example

```
if(policyPeriod != null) {  
    var a : Activity  
    var pattern = ActivityPattern.finder.getActivityPatternByCode("coverage")  
    a = pattern.createJobActivity(policyPeriod.Job.Bundle, policyPeriod.Job, null, null, null, null, null, null, null)  
}
```

- By default, an activity is always related to an account



**Review**



# Lesson objectives review

**You are now able to:**

- Create and configure activity patterns
- Create and configure activities



This presentation contains information that may be privileged or confidential and is the property of the Capgemini Group.

Copyright © 2022 Capgemini. All rights reserved.

