JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class StringReader

java.lang.Object
    java.io.Reader
        java.io.StringReader

All Implemented Interfaces:

Closeable, AutoCloseable, Readable

```
public class StringReader
extends Reader
```

A character stream whose source is a string.

API Note:

`Reader.of(CharSequence)` provides a method to read from any `CharSequence` that may be more efficient than `StringReader`.

Since:

1.1

Field Summary

Fields declared in class Reader
lock

Constructor Summary

Constructors

Constructor	Description
`StringReader(String s)`	Creates a new string reader.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
void	close()	Closes the stream and releases any system resources associated with it.
void		

	mark(int readAheadLimit)	Marks the present position in the stream.
boolean	**markSupported**()	Tells whether this stream supports the mark() operation, which it does.
int	**read**()	Reads a single character.
int	**read**(char[] cbuf, int off, int len)	Reads characters into a portion of an array.
boolean	**ready**()	Tells whether this stream is ready to be read.
void	**reset**()	Resets the stream to the most recent mark, or to the beginning of the string if it has never been marked.
long	**skip**(long n)	Skips characters.

Methods declared in class Reader

nullReader, of, read, read, readAllAsString, readAllLines, transferTo

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

StringReader

```
public StringReader(String s)
```

Creates a new string reader.

Parameters:

s - String providing the character stream.

Method Details

read

```
public int read()
         throws IOException
```

Reads a single character.

Overrides:

read in class Reader

Returns:

The character read, or -1 if the end of the stream has been reached

Throws:

IOException - If an I/O error occurs

read

```
public int read(char[] cbuf,
                int off,
                int len)
         throws IOException
```

Reads characters into a portion of an array.

If `len` is zero, then no characters are read and `0` is returned; otherwise, there is an attempt to read at least one character. If no character is available because the stream is at its end, the value `-1` is returned; otherwise, at least one character is read and stored into `cbuf`.

Specified by:

read in class Reader

Parameters:

`cbuf` - Destination buffer

`off` - Offset at which to start storing characters

`len` - Maximum number of characters to read

Returns:

The number of characters read, or -1 if the end of the stream has been reached

Throws:

IndexOutOfBoundsException - If `off` is negative, or `len` is negative, or `len` is greater than `cbuf.length - off`

IOException - If an I/O error occurs

skip

```
public long skip(long n)
          throws IOException
```

Skips characters. If the stream is already at its end before this method is invoked, then no characters are skipped and zero is returned.

The `n` parameter may be negative, even though the `skip` method of the `Reader` superclass throws an exception in this case. Negative values of `n` cause the stream to skip backwards. Negative return values indicate a skip backwards. It is not possible to skip backwards past the beginning of the string.

If the entire string has been read or skipped, then this method has no effect and always returns `0`.

Overrides:

`skip` in class `Reader`

Parameters:

`n` - The number of characters to skip

Returns:

The number of characters actually skipped

Throws:

`IOException` - If an I/O error occurs

ready

```
public boolean ready()
              throws IOException
```

Tells whether this stream is ready to be read.

Overrides:

`ready` in class `Reader`

Returns:

True if the next read() is guaranteed not to block for input

Throws:

`IOException` - If the stream is closed

markSupported

```
public boolean markSupported()
```

Tells whether this stream supports the mark() operation, which it does.

Overrides:

markSupported in class Reader

Returns:

true if and only if this stream supports the mark operation.

mark

```
public void mark(int readAheadLimit)
          throws IOException
```

Marks the present position in the stream. Subsequent calls to reset() will reposition the stream to this point.

Overrides:

mark in class Reader

Parameters:

`readAheadLimit` - Limit on the number of characters that may be read while still preserving the mark. Because the stream's input comes from a string, there is no actual limit, so this argument must not be negative, but is otherwise ignored.

Throws:

`IllegalArgumentException` - If `readAheadLimit < 0`

`IOException` - If an I/O error occurs

reset

```
public void reset()
           throws IOException
```

Resets the stream to the most recent mark, or to the beginning of the string if it has never been marked.

Overrides:

reset in class Reader

Throws:

`IOException` - If an I/O error occurs

close

```
public void close()
```

Closes the stream and releases any system resources associated with it. Once the stream has been closed, further read(), ready(), mark(), or reset() invocations will throw an IOException. Closing a previously closed stream has no effect. This method will block while there is another thread blocking on the reader.

Specified by:

`close` in interface `AutoCloseable`

Specified by:

`close` in interface `Closeable`

Specified by:

`close` in class `Reader`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.