JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class StringWriter

java.lang.Object
    java.io.Writer
        java.io.StringWriter

All Implemented Interfaces:

Closeable, Flushable, Appendable, AutoCloseable

```
public class StringWriter
extends Writer
```

A character stream that collects its output in a string buffer, which can then be used to construct a string.

Closing a `StringWriter` has no effect. The methods in this class can be called after the stream has been closed without generating an `IOException`.

Since:

1.1

Field Summary

Fields declared in class Writer
lock

Constructor Summary

Constructors

Constructor	Description
`StringWriter()`	Create a new string writer using the default initial string-buffer size.
`StringWriter(int initialSize)`	Create a new string writer using the specified initial string-buffer size.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
StringWriter	`append(char c)`	Appends the specified character to this writer.

StringWriter	**append**(CharSequence csq)	Appends the specified character sequence to this writer.
StringWriter	**append**(CharSequence csq, int start, int end)	Appends a subsequence of the specified character sequence to this writer.
void	**close**()	Closing a StringWriter has no effect.
void	**flush**()	Flush the stream.
StringBuffer	**getBuffer**()	Return the string buffer itself.
String	**toString**()	Return the buffer's current value as a string.
void	**write**(char[] cbuf, int off, int len)	Write a portion of an array of characters.
void	**write**(int c)	Write a single character.
void	**write**(String str)	Write a string.
void	**write**(String str, int off, int len)	Write a portion of a string.

Methods declared in class Writer

nullWriter, write

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

StringWriter

```
public StringWriter()
```

Create a new string writer using the default initial string-buffer size.

StringWriter

```
public StringWriter(int initialSize)
```

Create a new string writer using the specified initial string-buffer size.

Parameters:

`initialSize` - The number of `char` values that will fit into this buffer before it is automatically expanded

Throws:

`IllegalArgumentException` - If `initialSize` is negative

Method Details

write

```
public void write(int c)
```

Write a single character.

Overrides:

`write` in class `Writer`

Parameters:

`c` - int specifying a character to be written

write

```
public void write(char[] cbuf,
                  int off,
                  int len)
```

Write a portion of an array of characters.

Specified by:

`write` in class `Writer`

Parameters:

`cbuf` - Array of characters

`off` - Offset from which to start writing characters

`len` - Number of characters to write

Throws:

`IndexOutOfBoundsException` - If `off` is negative, or `len` is negative, or `off + len` is negative or greater than the length of the given array

write

```
public void write(String str)
```

Write a string.

Overrides:

write in class Writer

Parameters:

str - String to be written

write

```
public void write(String str,
                  int off,
                  int len)
```

Write a portion of a string.

Overrides:

write in class Writer

Parameters:

str - String to be written

off - Offset from which to start writing characters

len - Number of characters to write

Throws:

IndexOutOfBoundsException - If off is negative, or len is negative, or off + len is negative or greater than the length of the given string

append

```
public StringWriter append(CharSequence csq)
```

Appends the specified character sequence to this writer.

An invocation of this method of the form out.append(csq) when csq is not null, behaves in exactly the same way as the invocation

```
    out.write(csq.toString())
```

Depending on the specification of toString for the character sequence csq, the entire sequence may not be appended. For instance, invoking the toString method of a character buffer will return a subsequence whose content depends upon the buffer's position and limit.

Specified by:

`append` in interface `Appendable`

Overrides:

`append` in class `Writer`

Parameters:

`csq` - The character sequence to append. If `csq` is `null`, then the four characters `"null"` are appended to this writer.

Returns:

This writer

Since:

1.5

append

```
public StringWriter append(CharSequence csq,
                           int start,
                           int end)
```

Appends a subsequence of the specified character sequence to this writer.

An invocation of this method of the form `out.append(csq, start, end)` when `csq` is not `null`, behaves in exactly the same way as the invocation

```
    out.write(csq.subSequence(start, end).toString())
```

Specified by:

`append` in interface `Appendable`

Overrides:

`append` in class `Writer`

Parameters:

`csq` - The character sequence from which a subsequence will be appended. If `csq` is `null`, then characters will be appended as if `csq` contained the four characters `"null"`.

`start` - The index of the first character in the subsequence

`end` - The index of the character following the last character in the subsequence

Returns:

This writer

Throws:

`IndexOutOfBoundsException` - If `start` or `end` are negative, `start` is greater than `end`, or `end` is greater than `csq.length()`

Since:

1.5

append

```
public StringWriter append(char c)
```

Appends the specified character to this writer.

An invocation of this method of the form `out.append(c)` behaves in exactly the same way as the invocation

```
    out.write(c)
```

Specified by:

`append` in interface `Appendable`

Overrides:

`append` in class `Writer`

Parameters:

`c` - The 16-bit character to append

Returns:

This writer

Since:

1.5

toString

```
public String toString()
```

Return the buffer's current value as a string.

Overrides:

`toString` in class `Object`

Returns:

a string representation of the object

getBuffer

```
public StringBuffer getBuffer()
```

Return the string buffer itself.

Returns:

StringBuffer holding the current buffer value.

flush

```
public void flush()
```

Flush the stream.

The `flush` method of `StringWriter` does nothing.

Specified by:

`flush` in interface `Flushable`

Specified by:

`flush` in class `Writer`

close

```
public void close()
           throws IOException
```

Closing a `StringWriter` has no effect. The methods in this class can be called after the stream has been closed without generating an `IOException`.

Specified by:

`close` in interface `AutoCloseable`

Specified by:

`close` in interface `Closeable`

Specified by:

`close` in class `Writer`

Throws:

`IOException` - If an I/O error occurs

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.