JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class StrictMath

java.lang.Object
    java.lang.StrictMath

```
public final class StrictMath
extends Object
```

The class `StrictMath` contains methods for performing basic numeric operations such as the elementary exponential, logarithm, square root, and trigonometric functions.

To help ensure portability of Java programs, the definitions of some of the numeric functions in this package require that they produce the same results as certain published algorithms. These algorithms are available from the well-known network library `netlib` as the package "Freely Distributable Math Library," `fdlibm`. These algorithms, which are written in the C programming language, are then to be understood to be transliterated into Java and executed with all floating-point and integer operations following the rules of Java arithmetic. The following transformations are used in the transliteration:

- Extraction and setting of the high and low halves of a 64-bit `double` in C is expressed using Java platform methods that perform bit-wise conversions from `double` to `long` and `long` to `double`.
- Unsigned `int` values in C are mapped to signed `int` values in Java with updates to operations to replicate unsigned semantics where the results on the same textual operation would differ. For example, >> shifts on unsigned C values are replaced with >>> shifts on signed Java values. Sized comparisons on unsigned C values (<, <=, >, >=) are replaced with semantically equivalent calls to `compareUnsigned`.

The Java math library is defined with respect to `fdlibm` version 5.3 with a fix to `pow` so that its error bounds conform to the quality of implementation criteria for `pow`. Where `fdlibm` provides more than one definition for a function (such as `acos`), use the "IEEE 754 core function" version (residing in a file whose name begins with the letter `e`). The methods which require `fdlibm` semantics are `sin`, `cos`, `tan`, `asin`, `acos`, `atan`, `exp`, `log`, `log10`, `cbrt`, `atan2`, `pow`, `sinh`, `cosh`, `tanh`, `asinh`, `acosh`,`atanh`, `hypot`, `expm1`, and `log1p`.

The platform uses signed two's complement integer arithmetic with int and long primitive types. The developer should choose the primitive type to ensure that arithmetic operations consistently produce correct results, which in some cases means the operations will not overflow the range of values of the computation. The best practice is to choose the primitive type and algorithm to avoid overflow. In cases where the size is `int` or `long` and overflow errors need to be detected, the methods whose names end with `Exact` throw an `ArithmeticException` when the results overflow.

IEEE 754 Recommended Operations

The `Math` class discusses how the shared quality of implementation criteria for selected `Math` and `StrictMath` methods relate to the IEEE 754 recommended operations.

Since:

1.3

External Specifications

IEEE Standard for Floating-Point Arithmetic

Field Summary

Fields

Modifier and Type	Field	Description
`static final double`	`E`	The `double` value that is closer than any other to *e*, the base of the natural logarithms.
`static final double`	`PI`	The `double` value that is closer than any other to *pi* (π), the ratio of the circumference of a circle to its diameter.
`static final double`	`TAU`	The `double` value that is closer than any other to *tau* (τ), the ratio of the circumference of a circle to its radius.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
`static double`	`abs(double a)`	Returns the absolute value of a `double` value.
`static float`	`abs(float a)`	Returns the absolute value of a `float` value.

`static int`	**`abs`**`(int a)`	Returns the absolute value of an `int` value.
`static long`	**`abs`**`(long a)`	Returns the absolute value of a `long` value.
`static int`	**`absExact`**`(int a)`	Returns the mathematical absolute value of an `int` value if it is exactly representable as an `int`, throwing `ArithmeticException` if the result overflows the positive `int` range.
`static long`	**`absExact`**`(long a)`	Returns the mathematical absolute value of an `long` value if it is exactly representable as an `long`, throwing `ArithmeticException` if the result overflows the positive `long` range.
`static double`	**`acos`**`(double a)`	Returns the arc cosine of a value; the returned angle is in the range 0.0 through *pi*.
`static double`	**`acosh`**`(double x)`	Returns the inverse hyperbolic cosine of a `double` value.
`static int`	**`addExact`**`(int x, int y)`	Returns the sum of its arguments, throwing an exception if the result overflows an `int`.
`static long`	**`addExact`**`(long x, long y)`	Returns the sum of its arguments, throwing an exception if the result overflows a `long`.
`static double`	**`asin`**`(double a)`	Returns the arc sine of a value; the returned

		angle is in the range −*pi*/2 through *pi*/2.
`static double`	**`asinh`**`(double x)`	Returns the inverse hyperbolic sine of a `double` value.
`static double`	**`atan`**`(double a)`	Returns the arc tangent of a value; the returned angle is in the range −*pi*/2 through *pi*/2.
`static double`	**`atan2`**`(double y, double x)`	Returns the angle *theta* from the conversion of rectangular coordinates (x, y) to polar coordinates (r, *theta*).
`static double`	**`atanh`**`(double x)`	Returns the inverse hyperbolic tangent of a `double` value.
`static double`	**`cbrt`**`(double a)`	Returns the cube root of a `double` value.
`static double`	**`ceil`**`(double a)`	Returns the smallest (closest to negative infinity) `double` value that is greater than or equal to the argument and is equal to a mathematical integer.
`static int`	**`ceilDiv`**`(int x, int y)`	Returns the smallest (closest to negative infinity) `int` value that is greater than or equal to the algebraic quotient.
`static long`	**`ceilDiv`**`(long x, int y)`	Returns the smallest (closest to negative infinity) `long` value that is greater than or equal

		to the algebraic quotient.
static long	**ceilDiv**(long x, long y)	Returns the smallest (closest to negative infinity) long value that is greater than or equal to the algebraic quotient.
static int	**ceilDivExact**(int x, int y)	Returns the smallest (closest to negative infinity) int value that is greater than or equal to the algebraic quotient.
static long	**ceilDivExact**(long x, long y)	Returns the smallest (closest to negative infinity) long value that is greater than or equal to the algebraic quotient.
static int	**ceilMod**(int x, int y)	Returns the ceiling modulus of the int arguments.
static int	**ceilMod**(long x, int y)	Returns the ceiling modulus of the long and int arguments.
static long	**ceilMod**(long x, long y)	Returns the ceiling modulus of the long arguments.
static double	**clamp**(double value, double min, double max)	Clamps the value to fit between min and max.
static float	**clamp**(float value, float min, float max)	Clamps the value to fit between min and max.
static int		

	`clamp(long value, int min, int max)`	Clamps the value to fit between min and max.
`static long`	`clamp(long value, long min, long max)`	Clamps the value to fit between min and max.
`static double`	`copySign (double magnitude, double sign)`	Returns the first floating-point argument with the sign of the second floating-point argument.
`static float`	`copySign (float magnitude, float sign)`	Returns the first floating-point argument with the sign of the second floating-point argument.
`static double`	`cos(double a)`	Returns the trigonometric cosine of an angle.
`static double`	`cosh(double x)`	Returns the hyperbolic cosine of a `double` value.
`static int`	`decrementExact(int a)`	Returns the argument decremented by one, throwing an exception if the result overflows an `int`.
`static long`	`decrementExact(long a)`	Returns the argument decremented by one, throwing an exception if the result overflows a `long`.
`static int`	`divideExact(int x, int y)`	Returns the quotient of the arguments, throwing an exception if the result overflows an `int`.
`static long`	`divideExact(long x, long y)`	Returns the quotient of the arguments, throwing an exception if the result overflows a `long`.

`static double`	**`exp`**`(double a)`	Returns Euler's number *e* raised to the power of a `double` value.
`static double`	**`expm1`**`(double x)`	Returns $e^x - 1$.
`static double`	**`floor`**`(double a)`	Returns the largest (closest to positive infinity) `double` value that is less than or equal to the argument and is equal to a mathematical integer.
`static int`	**`floorDiv`**`(int x, int y)`	Returns the largest (closest to positive infinity) `int` value that is less than or equal to the algebraic quotient.
`static long`	**`floorDiv`**`(long x, int y)`	Returns the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient.
`static long`	**`floorDiv`**`(long x, long y)`	Returns the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient.
`static int`	**`floorDivExact`**`(int x, int y)`	Returns the largest (closest to positive infinity) `int` value that is less than or equal to the algebraic quotient.
`static long`	**`floorDivExact`**`(long x, long y)`	Returns the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient.
`static int`	**`floorMod`**`(int x, int y)`	

		Returns the floor modulus of the `int` arguments.
`static int`	**`floorMod`**`(long x, int y)`	Returns the floor modulus of the `long` and `int` arguments.
`static long`	**`floorMod`**`(long x, long y)`	Returns the floor modulus of the `long` arguments.
`static double`	**`fma`**`(double a, double b, double c)`	Returns the fused multiply add of the three arguments; that is, returns the exact product of the first two arguments summed with the third argument and then rounded once to the nearest `double`.
`static float`	**`fma`**`(float a, float b, float c)`	Returns the fused multiply add of the three arguments; that is, returns the exact product of the first two arguments summed with the third argument and then rounded once to the nearest `float`.
`static int`	**`getExponent`**`(double d)`	Returns the unbiased exponent used in the representation of a `double`.
`static int`	**`getExponent`**`(float f)`	Returns the unbiased exponent used in the representation of a `float`.
`static double`	**`hypot`**`(double x, double y)`	Returns sqrt(x^2 +y^2) without intermediate overflow or underflow.

static double	**IEEEremainder**(double f1, double f2)	Computes the remainder operation on two arguments as prescribed by the IEEE 754 standard.
static int	**incrementExact**(int a)	Returns the argument incremented by one, throwing an exception if the result overflows an int.
static long	**incrementExact**(long a)	Returns the argument incremented by one, throwing an exception if the result overflows a long.
static double	**log**(double a)	Returns the natural logarithm (base *e*) of a double value.
static double	**log10**(double a)	Returns the base 10 logarithm of a double value.
static double	**log1p**(double x)	Returns the natural logarithm of the sum of the argument and 1.
static double	**max**(double a, double b)	Returns the greater of two double values.
static float	**max**(float a, float b)	Returns the greater of two float values.
static int	**max**(int a, int b)	Returns the greater of two int values.
static long	**max**(long a, long b)	Returns the greater of two long values.
static double	**min**(double a, double b)	Returns the smaller of two double values.
static float	**min**(float a, float b)	Returns the smaller of two float values.

static int	**min**(int a, int b)	Returns the smaller of two int values.
static long	**min**(long a, long b)	Returns the smaller of two long values.
static int	**multiplyExact**(int x, int y)	Returns the product of the arguments, throwing an exception if the result overflows an int.
static long	**multiplyExact**(long x, int y)	Returns the product of the arguments, throwing an exception if the result overflows a long.
static long	**multiplyExact**(long x, long y)	Returns the product of the arguments, throwing an exception if the result overflows a long.
static long	**multiplyFull**(int x, int y)	Returns the exact mathematical product of the arguments.
static long	**multiplyHigh**(long x, long y)	Returns as a long the most significant 64 bits of the 128-bit product of two 64-bit factors.
static int	**negateExact**(int a)	Returns the negation of the argument, throwing an exception if the result overflows an int.
static long	**negateExact**(long a)	Returns the negation of the argument, throwing an exception if the result overflows a long.
static double	**nextAfter**(double start, double direction)	Returns the floating-point number adjacent to the first argument in the direction of the second argument.
static float		

	`nextAfter(float start, double direction)`	Returns the floating-point number adjacent to the first argument in the direction of the second argument.
`static double`	`nextDown(double d)`	Returns the floating-point value adjacent to `d` in the direction of negative infinity.
`static float`	`nextDown(float f)`	Returns the floating-point value adjacent to `f` in the direction of negative infinity.
`static double`	`nextUp(double d)`	Returns the floating-point value adjacent to `d` in the direction of positive infinity.
`static float`	`nextUp(float f)`	Returns the floating-point value adjacent to `f` in the direction of positive infinity.
`static double`	`pow(double a, double b)`	Returns the value of the first argument raised to the power of the second argument.
`static int`	`powExact(int x, int n)`	Returns `x` raised to the power of `n`, throwing an exception if the result overflows an `int`.
`static long`	`powExact(long x, int n)`	Returns `x` raised to the power of `n`, throwing an exception if the result overflows a `long`.
`static double`	`random()`	Returns a `double` value with a positive sign, greater than or equal to `0.0` and less than `1.0`.

`static double`	**`rint`**`(double a)`	Returns the `double` value that is closest in value to the argument and is equal to a mathematical integer.
`static long`	**`round`**`(double a)`	Returns the closest `long` to the argument, with ties rounding to positive infinity.
`static int`	**`round`**`(float a)`	Returns the closest `int` to the argument, with ties rounding to positive infinity.
`static double`	**`scalb`**`(double d, int scaleFactor)`	Returns `d` × $2^{\texttt{scaleFactor}}$ rounded as if performed by a single correctly rounded floating-point multiply.
`static float`	**`scalb`**`(float f, int scaleFactor)`	Returns `f` × $2^{\texttt{scaleFactor}}$ rounded as if performed by a single correctly rounded floating-point multiply.
`static double`	**`signum`**`(double d)`	Returns the signum function of the argument; zero if the argument is zero, 1.0 if the argument is greater than zero, -1.0 if the argument is less than zero.
`static float`	**`signum`**`(float f)`	Returns the signum function of the argument; zero if the argument is zero, 1.0f if the argument is greater than zero, -1.0f if the argument is less than zero.

static double	**sin**(double a)	Returns the trigonometric sine of an angle.
static double	**sinh**(double x)	Returns the hyperbolic sine of a double value.
static double	**sqrt**(double a)	Returns the correctly rounded positive square root of a double value.
static int	**subtractExact**(int x, int y)	Returns the difference of the arguments, throwing an exception if the result overflows an int.
static long	**subtractExact**(long x, long y)	Returns the difference of the arguments, throwing an exception if the result overflows a long.
static double	**tan**(double a)	Returns the trigonometric tangent of an angle.
static double	**tanh**(double x)	Returns the hyperbolic tangent of a double value.
static double	**toDegrees**(double angrad)	Converts an angle measured in radians to an approximately equivalent angle measured in degrees.
static int	**toIntExact**(long value)	Returns the value of the long argument, throwing an exception if the value overflows an int.
static double	**toRadians**(double angdeg)	Converts an angle measured in degrees to an approximately equivalent angle measured in radians.
static double	**ulp**(double d)	

		Returns the size of an ulp of the argument.
static float	**ulp**(float f)	Returns the size of an ulp of the argument.
static int	**unsignedMultiplyExact**(int x, int y)	Returns the product of the unsigned arguments, throwing an exception if the result overflows an unsigned int.
static long	**unsignedMultiplyExact**(long x, int y)	Returns the product of the unsigned arguments, throwing an exception if the result overflows an unsigned long.
static long	**unsignedMultiplyExact**(long x, long y)	Returns the product of the unsigned arguments, throwing an exception if the result overflows an unsigned long.
static long	**unsignedMultiplyHigh**(long x, long y)	Returns as a long the most significant 64 bits of the unsigned 128-bit product of two unsigned 64-bit factors.
static int	**unsignedPowExact**(int x, int n)	Returns unsigned x raised to the power of n, throwing an exception if the result overflows an unsigned int.
static long	**unsignedPowExact**(long x, int n)	Returns unsigned x raised to the power of n, throwing an exception if the result overflows an unsigned long.

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Field Details

E

`public static final double E`

The `double` value that is closer than any other to *e*, the base of the natural logarithms.

See Also:

Constant Field Values

PI

`public static final double PI`

The `double` value that is closer than any other to *pi* (π), the ratio of the circumference of a circle to its diameter.

See Also:

Constant Field Values

TAU

`public static final double TAU`

The `double` value that is closer than any other to *tau* (τ), the ratio of the circumference of a circle to its radius.

API Note:

The value of *pi* is one half that of *tau*; in other words, *tau* is double *pi* .

Since:

19

See Also:

Constant Field Values

Method Details

sin

`public static double sin(double a)`

Returns the trigonometric sine of an angle. Special cases:

- If the argument is NaN or an infinity, then the result is NaN.
- If the argument is zero, then the result is a zero with the same sign as the argument.

Parameters:

`a` - an angle, in radians.

Returns:

the sine of the argument.

cos

```
public static double cos(double a)
```

Returns the trigonometric cosine of an angle. Special cases:

- If the argument is NaN or an infinity, then the result is NaN.
- If the argument is zero, then the result is `1.0`.

Parameters:

`a` - an angle, in radians.

Returns:

the cosine of the argument.

tan

```
public static double tan(double a)
```

Returns the trigonometric tangent of an angle. Special cases:

- If the argument is NaN or an infinity, then the result is NaN.
- If the argument is zero, then the result is a zero with the same sign as the argument.

Parameters:

`a` - an angle, in radians.

Returns:

the tangent of the argument.

asin

```
public static double asin(double a)
```

Returns the arc sine of a value; the returned angle is in the range −*pi*/2 through *pi*/2. Special cases:

- If the argument is NaN or its absolute value is greater than 1, then the result is NaN.
- If the argument is zero, then the result is a zero with the same sign as the argument.

Parameters:

a - the value whose arc sine is to be returned.

Returns:

the arc sine of the argument.

acos

```
public static double acos(double a)
```

Returns the arc cosine of a value; the returned angle is in the range 0.0 through *pi*. Special case:

- If the argument is NaN or its absolute value is greater than 1, then the result is NaN.
- If the argument is `1.0`, the result is positive zero.

Parameters:

a - the value whose arc cosine is to be returned.

Returns:

the arc cosine of the argument.

atan

```
public static double atan(double a)
```

Returns the arc tangent of a value; the returned angle is in the range −*pi*/2 through *pi*/2. Special cases:

- If the argument is NaN, then the result is NaN.
- If the argument is zero, then the result is a zero with the same sign as the argument.
- If the argument is infinite, then the result is the closest value to *pi*/2 with the same sign as the input.

Parameters:

a - the value whose arc tangent is to be returned.

Returns:

the arc tangent of the argument.

toRadians

```
public static double toRadians(double angdeg)
```

Converts an angle measured in degrees to an approximately equivalent angle measured in radians. The conversion from degrees to radians is generally inexact.

Parameters:

`angdeg` - an angle, in degrees

Returns:

the measurement of the angle `angdeg` in radians.

toDegrees

```
public static double toDegrees(double angrad)
```

Converts an angle measured in radians to an approximately equivalent angle measured in degrees. The conversion from radians to degrees is generally inexact; users should *not* expect `cos(toRadians(90.0))` to exactly equal `0.0`.

Parameters:

`angrad` - an angle, in radians

Returns:

the measurement of the angle `angrad` in degrees.

exp

```
public static double exp(double a)
```

Returns Euler's number *e* raised to the power of a `double` value. Special cases:

- If the argument is NaN, the result is NaN.
- If the argument is positive infinity, then the result is positive infinity.
- If the argument is negative infinity, then the result is positive zero.
- If the argument is zero, then the result is `1.0`.

Parameters:

`a` - the exponent to raise *e* to.

Returns:

the value e^{a}, where *e* is the base of the natural logarithms.

log

```
public static double log(double a)
```

Returns the natural logarithm (base e) of a `double` value. Special cases:

- If the argument is NaN or less than zero, then the result is NaN.
- If the argument is positive infinity, then the result is positive infinity.
- If the argument is positive zero or negative zero, then the result is negative infinity.
- If the argument is `1.0`, then the result is positive zero.

Parameters:

`a` - a value

Returns:

the value ln `a`, the natural logarithm of `a`.

log10

```
public static double log10(double a)
```

Returns the base 10 logarithm of a `double` value. Special cases:

- If the argument is NaN or less than zero, then the result is NaN.
- If the argument is positive infinity, then the result is positive infinity.
- If the argument is positive zero or negative zero, then the result is negative infinity.
- If the argument is equal to 10^n for integer n, then the result is n. In particular, if the argument is `1.0` (10^0), then the result is positive zero.

Parameters:

`a` - a value

Returns:

the base 10 logarithm of `a`.

Since:

1.5

sqrt

```
public static double sqrt(double a)
```

Returns the correctly rounded positive square root of a `double` value. Special cases:

- If the argument is NaN or less than zero, then the result is NaN.
- If the argument is positive infinity, then the result is positive infinity.
- If the argument is positive zero or negative zero, then the result is the same as the argument.

Otherwise, the result is the `double` value closest to the true mathematical square root of the argument value.

Parameters:

`a` - a value.

Returns:

the positive square root of `a`.

cbrt

```
public static double cbrt(double a)
```

Returns the cube root of a `double` value. For positive finite `x`, `cbrt(-x) == -cbrt(x)`; that is, the cube root of a negative value is the negative of the cube root of that value's magnitude. Special cases:

- If the argument is NaN, then the result is NaN.
- If the argument is infinite, then the result is an infinity with the same sign as the argument.
- If the argument is zero, then the result is a zero with the same sign as the argument.

Parameters:

`a` - a value.

Returns:

the cube root of `a`.

Since:

1.5

IEEEremainder

```
public static double IEEEremainder(double f1,
                                   double f2)
```

Computes the remainder operation on two arguments as prescribed by the IEEE 754 standard. The remainder value is mathematically equal to $f1 - f2 \times n$, where n is the mathematical integer closest to the exact mathematical value of the quotient `f1/f2`, and if two mathematical integers are equally close to `f1/f2`, then n is the integer that is even. If the remainder is zero, its sign is the same as the sign of the first argument. Special cases:

- If either argument is NaN, or the first argument is infinite, or the second argument is positive zero or negative zero, then the result is NaN.
- If the first argument is finite and the second argument is infinite, then the result is the same as the first argument.

Parameters:

`f1` - the dividend.

`f2` - the divisor.

Returns:

the remainder when `f1` is divided by `f2`.

ceil

```
public static double ceil(double a)
```

Returns the smallest (closest to negative infinity) `double` value that is greater than or equal to the argument and is equal to a mathematical integer. Special cases:

- If the argument value is already equal to a mathematical integer, then the result is the same as the argument.
- If the argument is NaN or an infinity or positive zero or negative zero, then the result is the same as the argument.
- If the argument value is less than zero but greater than -1.0, then the result is negative zero.

Note that the value of `StrictMath.ceil(x)` is exactly the value of `-StrictMath.floor(-x)`.

Parameters:

`a` - a value.

Returns:

the smallest (closest to negative infinity) floating-point value that is greater than or equal to the argument and is equal to a mathematical integer.

floor

```
public static double floor(double a)
```

Returns the largest (closest to positive infinity) `double` value that is less than or equal to the argument and is equal to a mathematical integer. Special cases:

- If the argument value is already equal to a mathematical integer, then the result is the same as the argument.
- If the argument is NaN or an infinity or positive zero or negative zero, then the result is the same as the argument.

Parameters:

`a` - a value.

Returns:

the largest (closest to positive infinity) floating-point value that less than or equal to the argument and is equal to a mathematical integer.

rint

```
public static double rint(double a)
```

Returns the `double` value that is closest in value to the argument and is equal to a mathematical integer. If two `double` values that are mathematical integers are equally close to the value of the argument, the result is the integer value that is even. Special cases:

- If the argument value is already equal to a mathematical integer, then the result is the same as the argument.
- If the argument is NaN or an infinity or positive zero or negative zero, then the result is the same as the argument.

Parameters:

`a` - a value.

Returns:

the closest floating-point value to `a` that is equal to a mathematical integer.

atan2

```
public static double atan2(double y,
                           double x)
```

Returns the angle *theta* from the conversion of rectangular coordinates (`x`, `y`) to polar coordinates (r, *theta*). This method computes the phase *theta* by computing an arc tangent of `y/x` in the range of −*pi* to *pi*. Special cases:

- If either argument is NaN, then the result is NaN.
- If the first argument is positive zero and the second argument is positive, or the first argument is positive and finite and the second argument is positive infinity, then the result is positive zero.
- If the first argument is negative zero and the second argument is positive, or the first argument is negative and finite and the second argument is positive infinity, then the result is negative zero.
- If the first argument is positive zero and the second argument is negative, or the first argument is positive and finite and the second argument is negative infinity, then the result is the `double` value closest to *pi*.
- If the first argument is negative zero and the second argument is negative, or the first argument is negative and finite and the second argument is negative infinity, then the result is the `double` value closest to -*pi*.

- If the first argument is positive and the second argument is positive zero or negative zero, or the first argument is positive infinity and the second argument is finite, then the result is the `double` value closest to *pi*/2.
- If the first argument is negative and the second argument is positive zero or negative zero, or the first argument is negative infinity and the second argument is finite, then the result is the `double` value closest to -*pi*/2.
- If both arguments are positive infinity, then the result is the `double` value closest to *pi*/4.
- If the first argument is positive infinity and the second argument is negative infinity, then the result is the `double` value closest to 3*pi*/4.
- If the first argument is negative infinity and the second argument is positive infinity, then the result is the `double` value closest to -*pi*/4.
- If both arguments are negative infinity, then the result is the `double` value closest to -3*pi*/4.

API Note:

For *y* with a positive sign and finite nonzero *x*, the exact mathematical value of `atan2` is equal to:

- If *x* > 0, atan(abs(*y*/*x*))
- If *x* < 0, π - atan(abs(*y*/*x*))

Parameters:

y - the ordinate coordinate

x - the abscissa coordinate

Returns:

the *theta* component of the point (*r*, *theta*) in polar coordinates that corresponds to the point (*x*, *y*) in Cartesian coordinates.

pow

```
public static double pow(double a,
                         double b)
```

Returns the value of the first argument raised to the power of the second argument. Special cases:

- If the second argument is positive or negative zero, then the result is 1.0.
- If the second argument is 1.0, then the result is the same as the first argument.
- If the second argument is NaN, then the result is NaN.
- If the first argument is NaN and the second argument is nonzero, then the result is NaN.

- If
    - the absolute value of the first argument is greater than 1 and the second argument is positive infinity, or
    - the absolute value of the first argument is less than 1 and the second argument is negative infinity,

  then the result is positive infinity.
- If
    - the absolute value of the first argument is greater than 1 and the second argument is negative infinity, or
    - the absolute value of the first argument is less than 1 and the second argument is positive infinity,

  then the result is positive zero.
- If the absolute value of the first argument equals 1 and the second argument is infinite, then the result is NaN.
- If
    - the first argument is positive zero and the second argument is greater than zero, or
    - the first argument is positive infinity and the second argument is less than zero,

  then the result is positive zero.
- If
    - the first argument is positive zero and the second argument is less than zero, or
    - the first argument is positive infinity and the second argument is greater than zero,

  then the result is positive infinity.
- If
    - the first argument is negative zero and the second argument is greater than zero but not a finite odd integer, or
    - the first argument is negative infinity and the second argument is less than zero but not a finite odd integer,

  then the result is positive zero.
- If
    - the first argument is negative zero and the second argument is a positive finite odd integer, or
    - the first argument is negative infinity and the second argument is a negative finite odd integer,

  then the result is negative zero.
- If
    - the first argument is negative zero and the second argument is less than zero but not a finite odd integer, or
    - the first argument is negative infinity and the second argument is greater than zero but not a finite odd integer,

  then the result is positive infinity.

- If
  - the first argument is negative zero and the second argument is a negative finite odd integer, or
  - the first argument is negative infinity and the second argument is a positive finite odd integer,

  then the result is negative infinity.
- If the first argument is finite and less than zero
  - if the second argument is a finite even integer, the result is equal to the result of raising the absolute value of the first argument to the power of the second argument
  - if the second argument is a finite odd integer, the result is equal to the negative of the result of raising the absolute value of the first argument to the power of the second argument
  - if the second argument is finite and not an integer, then the result is NaN.
- If both arguments are integers, then the result is exactly equal to the mathematical result of raising the first argument to the power of the second argument if that result can in fact be represented exactly as a `double` value.

(In the foregoing descriptions, a floating-point value is considered to be an integer if and only if it is finite and a fixed point of the method `ceil` or, equivalently, a fixed point of the method `floor`. A value is a fixed point of a one-argument method if and only if the result of applying the method to the value is equal to the value.)

API Note:

The special cases definitions of this method differ from the special case definitions of the IEEE 754 recommended `pow` operation for `±1.0` raised to an infinite power. This method treats such cases as indeterminate and specifies a NaN is returned. The IEEE 754 specification treats the infinite power as a large integer (large-magnitude floating-point numbers are numerically integers, specifically even integers) and therefore specifies `1.0` be returned.

Parameters:

`a` - base.

`b` - the exponent.

Returns:

the value a^b.

round

```
public static int round(float a)
```

Returns the closest `int` to the argument, with ties rounding to positive infinity.

Special cases:

- If the argument is NaN, the result is 0.
- If the argument is negative infinity or any value less than or equal to the value of `Integer.MIN_VALUE`, the result is equal to the value of `Integer.MIN_VALUE`.
- If the argument is positive infinity or any value greater than or equal to the value of `Integer.MAX_VALUE`, the result is equal to the value of `Integer.MAX_VALUE`.

Parameters:

`a` - a floating-point value to be rounded to an integer.

Returns:

the value of the argument rounded to the nearest `int` value.

See Also:

`Integer.MAX_VALUE`, `Integer.MIN_VALUE`

round

```
public static long round(double a)
```

Returns the closest `long` to the argument, with ties rounding to positive infinity.

Special cases:

- If the argument is NaN, the result is 0.
- If the argument is negative infinity or any value less than or equal to the value of `Long.MIN_VALUE`, the result is equal to the value of `Long.MIN_VALUE`.
- If the argument is positive infinity or any value greater than or equal to the value of `Long.MAX_VALUE`, the result is equal to the value of `Long.MAX_VALUE`.

Parameters:

`a` - a floating-point value to be rounded to a `long`.

Returns:

the value of the argument rounded to the nearest `long` value.

See Also:

`Long.MAX_VALUE`, `Long.MIN_VALUE`

random

```
public static double random()
```

Returns a `double` value with a positive sign, greater than or equal to `0.0` and less than `1.0`. Returned values are chosen pseudorandomly with (approximately) uniform distribution from that range.

When this method is first called, it creates a single new pseudorandom-number generator, exactly as if by the expression

```
new java.util.Random()
```

This new pseudorandom-number generator is used thereafter for all calls to this method and is used nowhere else.

This method is properly synchronized to allow correct use by more than one thread. However, if many threads need to generate pseudorandom numbers at a great rate, it may reduce contention for each thread to have its own pseudorandom-number generator.

Returns:

a pseudorandom `double` greater than or equal to `0.0` and less than `1.0`.

See Also:

`Random.nextDouble()`

addExact

```
public static int addExact(int x,
                           int y)
```

Returns the sum of its arguments, throwing an exception if the result overflows an `int`.

Parameters:

x - the first value

y - the second value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an int

Since:

1.8

See Also:

`Math.addExact(int,int)`

addExact

```
public static long addExact(long x,
                            long y)
```

Returns the sum of its arguments, throwing an exception if the result overflows a `long`.

Parameters:

x - the first value

y - the second value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows a long

Since:

1.8

See Also:

`Math.addExact(long,long)`

subtractExact

```
public static int subtractExact(int x,
                                int y)
```

Returns the difference of the arguments, throwing an exception if the result overflows an `int`.

Parameters:

x - the first value

y - the second value to subtract from the first

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an int

Since:

1.8

See Also:

`Math.subtractExact(int,int)`

subtractExact

```
public static long subtractExact(long x,
                                 long y)
```

Returns the difference of the arguments, throwing an exception if the result overflows a `long`.

Parameters:

x - the first value

y - the second value to subtract from the first

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows a long

Since:

1.8

See Also:

`Math.subtractExact(long,long)`

multiplyExact

```
public static int multiplyExact(int x,
                                int y)
```

Returns the product of the arguments, throwing an exception if the result overflows an `int`.

Parameters:

x - the first value

y - the second value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an int

Since:

1.8

See Also:

`Math.multiplyExact(int,int)`

multiplyExact

```
public static long multiplyExact(long x,
                                 int y)
```

Returns the product of the arguments, throwing an exception if the result overflows a `long`.

Parameters:

x - the first value

y - the second value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows a long

Since:

9

See Also:

`Math.multiplyExact(long,int)`

multiplyExact

```
public static long multiplyExact(long x,
                                 long y)
```

Returns the product of the arguments, throwing an exception if the result overflows a `long`.

Parameters:

x - the first value

y - the second value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows a long

Since:

1.8

See Also:

`Math.multiplyExact(long,long)`

divideExact

```
public static int divideExact(int x,
                              int y)
```

Returns the quotient of the arguments, throwing an exception if the result overflows an `int`. Such overflow occurs in this method if `x` is `Integer.MIN_VALUE` and `y` is `-1`. In contrast, if `Integer.MIN_VALUE / -1` were evaluated directly, the result would be `Integer.MIN_VALUE` and no exception would be thrown.

If `y` is zero, an `ArithmeticException` is thrown (JLS §15.17.2).

The built-in remainder operator "`%`" is a suitable counterpart both for this method and for the built-in division operator "`/`".

Parameters:

`x` - the dividend

`y` - the divisor

Returns:

the quotient `x / y`

Throws:

`ArithmeticException` - if `y` is zero or the quotient overflows an int

See *Java Language Specification*:

15.17.2 Division Operator /

Since:

18

See Also:

`Math.divideExact(int,int)`

divideExact

```
public static long divideExact(long x,
                               long y)
```

Returns the quotient of the arguments, throwing an exception if the result overflows a `long`. Such overflow occurs in this method if `x` is `Long.MIN_VALUE` and `y` is `-1`. In contrast, if `Long.MIN_VALUE / -1` were evaluated directly, the result would be `Long.MIN_VALUE` and no exception would be thrown.

If `y` is zero, an `ArithmeticException` is thrown (JLS §15.17.2).

The built-in remainder operator "`%`" is a suitable counterpart both for this method and for the built-in division operator "`/`".

Parameters:

x - the dividend

y - the divisor

Returns:

the quotient `x / y`

Throws:

`ArithmeticException` - if y is zero or the quotient overflows a long

See *Java Language Specification*:

15.17.2 Division Operator /

Since:

18

See Also:

`Math.divideExact(long,long)`

floorDivExact

```
public static int floorDivExact(int x,
                                int y)
```

Returns the largest (closest to positive infinity) `int` value that is less than or equal to the algebraic quotient. This method is identical to `floorDiv(int,int)` except that it throws an `ArithmeticException` when the dividend is Integer.MIN_VALUE and the divisor is `-1` instead of ignoring the integer overflow and returning `Integer.MIN_VALUE`.

The floor modulus method `floorMod(int,int)` is a suitable counterpart both for this method and for the `floorDiv(int,int)` method.

See `Math.floorDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the largest (closest to positive infinity) `int` value that is less than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor y is zero, or the dividend x is `Integer.MIN_VALUE` and the divisor y is `-1`.

Since:

18

See Also:

`Math.floorDiv(int, int)`

floorDivExact

```
public static long floorDivExact(long x,
                                 long y)
```

Returns the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient. This method is identical to `floorDiv(long,long)` except that it throws an `ArithmeticException` when the dividend is Long.MIN_VALUE and the divisor is `-1` instead of ignoring the integer overflow and returning `Long.MIN_VALUE`.

The floor modulus method `floorMod(long,long)` is a suitable counterpart both for this method and for the `floorDiv(long,long)` method.

For examples, see `Math.floorDiv`.

Parameters:

x - the dividend

y - the divisor

Returns:

the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor `y` is zero, or the dividend `x` is `Long.MIN_VALUE` and the divisor `y` is `-1`.

Since:

18

See Also:

`Math.floorDiv(int, int)`,
`Math.floorDiv(long,long)`

ceilDivExact

```
public static int ceilDivExact(int x,
                               int y)
```

Returns the smallest (closest to negative infinity) `int` value that is greater than or equal to the algebraic quotient. This method is identical to `ceilDiv(int,int)` except that it throws an `ArithmeticException` when the

dividend is Integer.MIN_VALUE and the divisor is `-1` instead of ignoring the integer overflow and returning `Integer.MIN_VALUE`.

The ceil modulus method `ceilMod(int,int)` is a suitable counterpart both for this method and for the `ceilDiv(int,int)` method.

See `Math.ceilDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the smallest (closest to negative infinity) `int` value that is greater than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor `y` is zero, or the dividend `x` is `Integer.MIN_VALUE` and the divisor `y` is `-1`.

Since:

18

See Also:

`Math.ceilDiv(int, int)`

ceilDivExact

```
public static long ceilDivExact(long x,
                                 long y)
```

Returns the smallest (closest to negative infinity) `long` value that is greater than or equal to the algebraic quotient. This method is identical to `ceilDiv(long,long)` except that it throws an `ArithmeticException` when the dividend is Long.MIN_VALUE and the divisor is `-1` instead of ignoring the integer overflow and returning `Long.MIN_VALUE`.

The ceil modulus method `ceilMod(long,long)` is a suitable counterpart both for this method and for the `ceilDiv(long,long)` method.

For examples, see `Math.ceilDiv`.

Parameters:

x - the dividend

y - the divisor

Returns:

the smallest (closest to negative infinity) `long` value that is greater than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor `y` is zero, or the dividend `x` is `Long.MIN_VALUE` and the divisor `y` is `-1`.

Since:

18

See Also:

`Math.ceilDiv(int, int)`,
`Math.ceilDiv(long,long)`

incrementExact

```
public static int incrementExact(int a)
```

Returns the argument incremented by one, throwing an exception if the result overflows an `int`. The overflow only occurs for the maximum value.

Parameters:

`a` - the value to increment

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an int

Since:

14

See Also:

`Math.incrementExact(int)`

incrementExact

```
public static long incrementExact(long a)
```

Returns the argument incremented by one, throwing an exception if the result overflows a `long`. The overflow only occurs for the maximum value.

Parameters:

`a` - the value to increment

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows a long

Since:

14

See Also:

`Math.incrementExact(long)`

decrementExact

```
public static int decrementExact(int a)
```

Returns the argument decremented by one, throwing an exception if the result overflows an `int`. The overflow only occurs for the minimum value.

Parameters:

`a` - the value to decrement

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an int

Since:

14

See Also:

`Math.decrementExact(int)`

decrementExact

```
public static long decrementExact(long a)
```

Returns the argument decremented by one, throwing an exception if the result overflows a `long`. The overflow only occurs for the minimum value.

Parameters:

`a` - the value to decrement

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows a long

Since:

14

See Also:

`Math.decrementExact(long)`

negateExact

```
public static int negateExact(int a)
```

Returns the negation of the argument, throwing an exception if the result overflows an `int`. The overflow only occurs for the minimum value.

Parameters:

a - the value to negate

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an int

Since:

14

See Also:

`Math.negateExact(int)`

negateExact

```
public static long negateExact(long a)
```

Returns the negation of the argument, throwing an exception if the result overflows a `long`. The overflow only occurs for the minimum value.

Parameters:

a - the value to negate

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows a long

Since:

14

See Also:

`Math.negateExact(long)`

toIntExact

```
public static int toIntExact(long value)
```

Returns the value of the `long` argument, throwing an exception if the value overflows an `int`.

Parameters:

value - the long value

Returns:

the argument as an int

Throws:

ArithmeticException - if the argument overflows an int

Since:

1.8

See Also:

Math.toIntExact(long)

multiplyFull

```
public static long multiplyFull(int x,
                                int y)
```

Returns the exact mathematical product of the arguments.

Parameters:

x - the first value

y - the second value

Returns:

the result

Since:

9

See Also:

Math.multiplyFull(int,int)

multiplyHigh

```
public static long multiplyHigh(long x,
                                long y)
```

Returns as a long the most significant 64 bits of the 128-bit product of two 64-bit factors.

Parameters:

x - the first value

y - the second value

Returns:

the result

Since:

9

See Also:

`unsignedMultiplyHigh(long, long)`,
`Math.multiplyHigh(long,long)`

unsignedMultiplyHigh

```
public static long unsignedMultiplyHigh(long x,
                                        long y)
```

Returns as a `long` the most significant 64 bits of the unsigned 128-bit product of two unsigned 64-bit factors.

Parameters:

x - the first value

y - the second value

Returns:

the result

Since:

18

See Also:

`multiplyHigh(long, long)`,
`Math.unsignedMultiplyHigh(long,long)`

floorDiv

```
public static int floorDiv(int x,
                           int y)
```

Returns the largest (closest to positive infinity) `int` value that is less than or equal to the algebraic quotient. There is one special case: if the dividend is Integer.MIN_VALUE and the divisor is `-1`, then integer overflow occurs and the result is equal to `Integer.MIN_VALUE`.

See `Math.floorDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the largest (closest to positive infinity) `int` value that is less than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor y is zero

Since:

1.8

See Also:

`Math.floorDiv(int, int)`,
`Math.floor(double)`

floorDiv

```
public static long floorDiv(long x,
                            int y)
```

Returns the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient. There is one special case: if the dividend is Long.MIN_VALUE and the divisor is `-1`, then integer overflow occurs and the result is equal to `Long.MIN_VALUE`.

See `Math.floorDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor y is zero

Since:

9

See Also:

`Math.floorDiv(long, int)`,
`Math.floor(double)`

floorDiv

```
public static long floorDiv(long x,
                            long y)
```

Returns the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient. There is one special case: if the dividend is

Long.MIN_VALUE and the divisor is `-1`, then integer overflow occurs and the result is equal to `Long.MIN_VALUE`.

See `Math.floorDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the largest (closest to positive infinity) `long` value that is less than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

1.8

See Also:

`Math.floorDiv(long, long)`,
`Math.floor(double)`

floorMod

```
public static int floorMod(int x,
                           int y)
```

Returns the floor modulus of the `int` arguments.

The floor modulus is `r = x - (floorDiv(x, y) * y)`, has the same sign as the divisor `y` or is zero, and is in the range of `-abs(y) < r < +abs(y)`.

The relationship between `floorDiv` and `floorMod` is such that:

- `floorDiv(x, y) * y + floorMod(x, y) == x`

See `Math.floorMod` for examples and a comparison to the `%` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the floor modulus `x - (floorDiv(x, y) * y)`

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

1.8

See Also:

`Math.floorMod(int, int)`,
`floorDiv(int, int)`

floorMod

```
public static int floorMod(long x,
                           int y)
```

Returns the floor modulus of the `long` and `int` arguments.

The floor modulus is `r = x - (floorDiv(x, y) * y)`, has the same sign as the divisor `y` or is zero, and is in the range of `-abs(y) < r < +abs(y)`.

The relationship between `floorDiv` and `floorMod` is such that:

- `floorDiv(x, y) * y + floorMod(x, y) == x`

See `Math.floorMod` for examples and a comparison to the `%` operator.

Parameters:

`x` - the dividend

`y` - the divisor

Returns:

the floor modulus `x - (floorDiv(x, y) * y)`

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

9

See Also:

`Math.floorMod(long, int)`,
`floorDiv(long, int)`

floorMod

```
public static long floorMod(long x,
                            long y)
```

Returns the floor modulus of the `long` arguments.

The floor modulus is `r = x - (floorDiv(x, y) * y)`, has the same sign as the divisor `y` or is zero, and is in the range of `-abs(y) < r < +abs(y)`.

The relationship between `floorDiv` and `floorMod` is such that:

- `floorDiv(x, y) * y + floorMod(x, y) == x`

See `Math.floorMod` for examples and a comparison to the `%` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the floor modulus `x - (floorDiv(x, y) * y)`

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

1.8

See Also:

`Math.floorMod(long, long)`,
`floorDiv(long, long)`

ceilDiv

```
public static int ceilDiv(int x,
                          int y)
```

Returns the smallest (closest to negative infinity) `int` value that is greater than or equal to the algebraic quotient. There is one special case: if the dividend is Integer.MIN_VALUE and the divisor is `-1`, then integer overflow occurs and the result is equal to `Integer.MIN_VALUE`.

See `Math.ceilDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the smallest (closest to negative infinity) `int` value that is greater than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

18

See Also:

`Math.ceilDiv(int, int)`,
`Math.ceil(double)`

ceilDiv

```
public static long ceilDiv(long x,
                           int y)
```

Returns the smallest (closest to negative infinity) `long` value that is greater than or equal to the algebraic quotient. There is one special case: if the dividend is Long.MIN_VALUE and the divisor is `-1`, then integer overflow occurs and the result is equal to `Long.MIN_VALUE`.

See `Math.ceilDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the smallest (closest to negative infinity) `long` value that is greater than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor y is zero

Since:

18

See Also:

`Math.ceilDiv(long, int)`,
`Math.ceil(double)`

ceilDiv

```
public static long ceilDiv(long x,
                           long y)
```

Returns the smallest (closest to negative infinity) `long` value that is greater than or equal to the algebraic quotient. There is one special case: if the dividend is Long.MIN_VALUE and the divisor is `-1`, then integer overflow occurs and the result is equal to `Long.MIN_VALUE`.

See `Math.ceilDiv` for examples and a comparison to the integer division `/` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the smallest (closest to negative infinity) `long` value that is greater than or equal to the algebraic quotient.

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

18

See Also:

`Math.ceilDiv(long, long)`,
`Math.ceil(double)`

ceilMod

```
public static int ceilMod(int x,
                          int y)
```

Returns the ceiling modulus of the `int` arguments.

The ceiling modulus is `r = x - (ceilDiv(x, y) * y)`, has the opposite sign as the divisor `y` or is zero, and is in the range of `-abs(y) < r < +abs(y)`.

The relationship between `ceilDiv` and `ceilMod` is such that:

- `ceilDiv(x, y) * y + ceilMod(x, y) == x`

See `Math.ceilMod` for examples and a comparison to the `%` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the ceiling modulus `x - (ceilDiv(x, y) * y)`

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

18

See Also:

`Math.ceilMod(int, int)`,
`ceilDiv(int, int)`

ceilMod

```
public static int ceilMod(long x,
                          int y)
```

Returns the ceiling modulus of the `long` and `int` arguments.

The ceiling modulus is `r = x - (ceilDiv(x, y) * y)`, has the opposite sign as the divisor `y` or is zero, and is in the range of `-abs(y) < r < +abs(y)`.

The relationship between `ceilDiv` and `ceilMod` is such that:

- `ceilDiv(x, y) * y + ceilMod(x, y) == x`

See `Math.ceilMod` for examples and a comparison to the `%` operator.

Parameters:

`x` - the dividend

`y` - the divisor

Returns:

the ceiling modulus `x - (ceilDiv(x, y) * y)`

Throws:

`ArithmeticException` - if the divisor `y` is zero

Since:

18

See Also:

`Math.ceilMod(long, int)`,
`ceilDiv(long, int)`

ceilMod

```
public static long ceilMod(long x,
                           long y)
```

Returns the ceiling modulus of the `long` arguments.

The ceiling modulus is `r = x - (ceilDiv(x, y) * y)`, has the opposite sign as the divisor `y` or is zero, and is in the range of `-abs(y) < r < +abs(y)`.

The relationship between `ceilDiv` and `ceilMod` is such that:

- `ceilDiv(x, y) * y + ceilMod(x, y) == x`

See `Math.ceilMod` for examples and a comparison to the `%` operator.

Parameters:

x - the dividend

y - the divisor

Returns:

the ceiling modulus `x - (ceilDiv(x, y) * y)`

Throws:

`ArithmeticException` - if the divisor y is zero

Since:

18

See Also:

`Math.ceilMod(long, long)`,
`ceilDiv(long, long)`

abs

```
public static int abs(int a)
```

Returns the absolute value of an `int` value. If the argument is not negative, the argument is returned. If the argument is negative, the negation of the argument is returned.

Note that if the argument is equal to the value of `Integer.MIN_VALUE`, the most negative representable `int` value, the result is that same value, which is negative. In contrast, the `absExact(int)` method throws an `ArithmeticException` for this value.

Parameters:

a - the argument whose absolute value is to be determined.

Returns:

the absolute value of the argument.

See Also:

`Math.absExact(int)`

absExact

```
public static int absExact(int a)
```

Returns the mathematical absolute value of an `int` value if it is exactly representable as an `int`, throwing `ArithmeticException` if the result overflows the positive `int` range.

Since the range of two's complement integers is asymmetric with one additional negative value (JLS §4.2.1), the mathematical absolute value of

`Integer.MIN_VALUE` overflows the positive `int` range, so an exception is thrown for that argument.

Parameters:

a - the argument whose absolute value is to be determined

Returns:

the absolute value of the argument, unless overflow occurs

Throws:

`ArithmeticException` - if the argument is `Integer.MIN_VALUE`

Since:

15

See Also:

`Math.abs(int)`, `Math.absExact(int)`

abs

```
public static long abs(long a)
```

Returns the absolute value of a `long` value. If the argument is not negative, the argument is returned. If the argument is negative, the negation of the argument is returned.

Note that if the argument is equal to the value of `Long.MIN_VALUE`, the most negative representable `long` value, the result is that same value, which is negative. In contrast, the `absExact(long)` method throws an `ArithmeticException` for this value.

Parameters:

a - the argument whose absolute value is to be determined.

Returns:

the absolute value of the argument.

See Also:

`Math.absExact(long)`

absExact

```
public static long absExact(long a)
```

Returns the mathematical absolute value of an `long` value if it is exactly representable as an `long`, throwing `ArithmeticException` if the result overflows the positive `long` range.

Since the range of two's complement integers is asymmetric with one additional negative value (JLS §4.2.1), the mathematical absolute value of

`Long.MIN_VALUE` overflows the positive `long` range, so an exception is thrown for that argument.

Parameters:

a - the argument whose absolute value is to be determined

Returns:

the absolute value of the argument, unless overflow occurs

Throws:

`ArithmeticException` - if the argument is `Long.MIN_VALUE`

Since:

15

See Also:

`Math.abs(long)`, `Math.absExact(long)`

abs

```
public static float abs(float a)
```

Returns the absolute value of a `float` value. If the argument is not negative, the argument is returned. If the argument is negative, the negation of the argument is returned. Special cases:

- If the argument is positive zero or negative zero, the result is positive zero.
- If the argument is infinite, the result is positive infinity.
- If the argument is NaN, the result is NaN.

API Note:

As implied by the above, one valid implementation of this method is given by the expression below which computes a `float` with the same exponent and significand as the argument but with a guaranteed zero sign bit indicating a positive value:
`Float.intBitsToFloat(0x7fffffff & Float.floatToRawIntBits(a))`

Parameters:

a - the argument whose absolute value is to be determined

Returns:

the absolute value of the argument.

abs

```
public static double abs(double a)
```

Returns the absolute value of a `double` value. If the argument is not negative, the argument is returned. If the argument is negative, the negation of the argument is returned. Special cases:

- If the argument is positive zero or negative zero, the result is positive zero.
- If the argument is infinite, the result is positive infinity.
- If the argument is NaN, the result is NaN.

API Note:

As implied by the above, one valid implementation of this method is given by the expression below which computes a `double` with the same exponent and significand as the argument but with a guaranteed zero sign bit indicating a positive value:
`Double.longBitsToDouble((Double.doubleToRawLongBits(a)<<1)>>>1)`

Parameters:

`a` - the argument whose absolute value is to be determined

Returns:

the absolute value of the argument.

max

```
public static int max(int a,
                      int b)
```

Returns the greater of two `int` values. That is, the result is the argument closer to the value of `Integer.MAX_VALUE`. If the arguments have the same value, the result is that same value.

Parameters:

`a` - an argument.

`b` - another argument.

Returns:

the larger of `a` and `b`.

max

```
public static long max(long a,
                       long b)
```

Returns the greater of two `long` values. That is, the result is the argument closer to the value of `Long.MAX_VALUE`. If the arguments have the same value, the result is that same value.

Parameters:

`a` - an argument.

b - another argument.

Returns:

the larger of a and b.

max

```
public static float max(float a,
                        float b)
```

Returns the greater of two float values. That is, the result is the argument closer to positive infinity. If the arguments have the same value, the result is that same value. If either value is NaN, then the result is NaN. Unlike the numerical comparison operators, this method considers negative zero to be strictly smaller than positive zero. If one argument is positive zero and the other negative zero, the result is positive zero.

Parameters:

a - an argument.

b - another argument.

Returns:

the larger of a and b.

max

```
public static double max(double a,
                         double b)
```

Returns the greater of two double values. That is, the result is the argument closer to positive infinity. If the arguments have the same value, the result is that same value. If either value is NaN, then the result is NaN. Unlike the numerical comparison operators, this method considers negative zero to be strictly smaller than positive zero. If one argument is positive zero and the other negative zero, the result is positive zero.

Parameters:

a - an argument.

b - another argument.

Returns:

the larger of a and b.

min

```
public static int min(int a,
                      int b)
```

Returns the smaller of two `int` values. That is, the result the argument closer to the value of `Integer.MIN_VALUE`. If the arguments have the same value, the result is that same value.

Parameters:

`a` - an argument.

`b` - another argument.

Returns:

the smaller of `a` and `b`.

min

```
public static long min(long a,
                       long b)
```

Returns the smaller of two `long` values. That is, the result is the argument closer to the value of `Long.MIN_VALUE`. If the arguments have the same value, the result is that same value.

Parameters:

`a` - an argument.

`b` - another argument.

Returns:

the smaller of `a` and `b`.

min

```
public static float min(float a,
                        float b)
```

Returns the smaller of two `float` values. That is, the result is the value closer to negative infinity. If the arguments have the same value, the result is that same value. If either value is NaN, then the result is NaN. Unlike the numerical comparison operators, this method considers negative zero to be strictly smaller than positive zero. If one argument is positive zero and the other is negative zero, the result is negative zero.

Parameters:

`a` - an argument.

`b` - another argument.

Returns:

the smaller of `a` and `b`.

min

```
public static double min(double a,
                         double b)
```

Returns the smaller of two `double` values. That is, the result is the value closer to negative infinity. If the arguments have the same value, the result is that same value. If either value is NaN, then the result is NaN. Unlike the numerical comparison operators, this method considers negative zero to be strictly smaller than positive zero. If one argument is positive zero and the other is negative zero, the result is negative zero.

Parameters:

`a` - an argument.

`b` - another argument.

Returns:

the smaller of `a` and `b`.

clamp

```
public static int clamp(long value,
                        int min,
                        int max)
```

Clamps the value to fit between min and max. If the value is less than `min`, then `min` is returned. If the value is greater than `max`, then `max` is returned. Otherwise, the original value is returned.

While the original value of type long may not fit into the int type, the bounds have the int type, so the result always fits the int type. This allows to use method to safely cast long value to int with saturation.

Parameters:

`value` - value to clamp

`min` - minimal allowed value

`max` - maximal allowed value

Returns:

a clamped value that fits into `min..max` interval

Throws:

`IllegalArgumentException` - if `min > max`

Since:

21

clamp

```
public static long clamp(long value,
                         long min,
                         long max)
```

Clamps the value to fit between min and max. If the value is less than `min`, then `min` is returned. If the value is greater than `max`, then `max` is returned. Otherwise, the original value is returned.

Parameters:

`value` - value to clamp

`min` - minimal allowed value

`max` - maximal allowed value

Returns:

a clamped value that fits into `min..max` interval

Throws:

`IllegalArgumentException` - if `min > max`

Since:

21

clamp

```
public static double clamp(double value,
                           double min,
                           double max)
```

Clamps the value to fit between min and max. If the value is less than `min`, then `min` is returned. If the value is greater than `max`, then `max` is returned. Otherwise, the original value is returned. If value is NaN, the result is also NaN.

Unlike the numerical comparison operators, this method considers negative zero to be strictly smaller than positive zero. E.g., `clamp(-0.0, 0.0, 1.0)` returns 0.0.

Parameters:

`value` - value to clamp

`min` - minimal allowed value

`max` - maximal allowed value

Returns:

a clamped value that fits into `min..max` interval

Throws:

IllegalArgumentException - if either of min and max arguments is NaN, or min > max, or min is +0.0, and max is -0.0.

Since:

21

clamp

```
public static float clamp(float value,
                          float min,
                          float max)
```

Clamps the value to fit between min and max. If the value is less than min, then min is returned. If the value is greater than max, then max is returned. Otherwise, the original value is returned. If value is NaN, the result is also NaN.

Unlike the numerical comparison operators, this method considers negative zero to be strictly smaller than positive zero. E.g., clamp(-0.0f, 0.0f, 1.0f) returns 0.0f.

Parameters:

value - value to clamp

min - minimal allowed value

max - maximal allowed value

Returns:

a clamped value that fits into min..max interval

Throws:

IllegalArgumentException - if either of min and max arguments is NaN, or min > max, or min is +0.0f, and max is -0.0f.

Since:

21

fma

```
public static double fma(double a,
                         double b,
                         double c)
```

Returns the fused multiply add of the three arguments; that is, returns the exact product of the first two arguments summed with the third argument and then rounded once to the nearest double. The rounding is done using the round to nearest even rounding mode. In contrast, if a * b + c is evaluated as a regular floating-point expression, two rounding errors are involved, the first for the multiply operation, the second for the addition operation.

Special cases:

- If any argument is NaN, the result is NaN.
- If one of the first two arguments is infinite and the other is zero, the result is NaN.
- If the exact product of the first two arguments is infinite (in other words, at least one of the arguments is infinite and the other is neither zero nor NaN) and the third argument is an infinity of the opposite sign, the result is NaN.

Note that `fusedMac(a, 1.0, c)` returns the same result as `(a + c)`. However, `fusedMac(a, b, +0.0)` does *not* always return the same result as `(a * b)` since `fusedMac(-0.0, +0.0, +0.0)` is `+0.0` while `(-0.0 * +0.0)` is `-0.0`; `fusedMac(a, b, -0.0)` is equivalent to `(a * b)` however.

API Note:

This method corresponds to the fusedMultiplyAdd operation defined in IEEE 754-2008.

Parameters:

`a` - a value

`b` - a value

`c` - a value

Returns:

($a \times b + c$) computed, as if with unlimited range and precision, and rounded once to the nearest `double` value

Since:

9

fma

```
public static float fma(float a,
                        float b,
                        float c)
```

Returns the fused multiply add of the three arguments; that is, returns the exact product of the first two arguments summed with the third argument and then rounded once to the nearest `float`. The rounding is done using the round to nearest even rounding mode. In contrast, if `a * b + c` is evaluated as a regular floating-point expression, two rounding errors are involved, the first for the multiply operation, the second for the addition operation.

Special cases:

- If any argument is NaN, the result is NaN.

- If one of the first two arguments is infinite and the other is zero, the result is NaN.
- If the exact product of the first two arguments is infinite (in other words, at least one of the arguments is infinite and the other is neither zero nor NaN) and the third argument is an infinity of the opposite sign, the result is NaN.

Note that `fma(a, 1.0f, c)` returns the same result as `(a + c)`. However, `fma(a, b, +0.0f)` does *not* always return the same result as `(a * b)` since `fma(-0.0f, +0.0f, +0.0f)` is `+0.0f` while `(-0.0f * +0.0f)` is `-0.0f`; `fma(a, b, -0.0f)` is equivalent to `(a * b)` however.

API Note:

This method corresponds to the fusedMultiplyAdd operation defined in IEEE 754-2008.

Parameters:

`a` - a value

`b` - a value

`c` - a value

Returns:

($a \times b + c$) computed, as if with unlimited range and precision, and rounded once to the nearest `float` value

Since:

9

ulp

```
public static double ulp(double d)
```

Returns the size of an ulp of the argument. An ulp, unit in the last place, of a `double` value is the positive distance between this floating-point value and the `double` value next larger in magnitude. Note that for non-NaN x, `ulp(-`x`) == ulp(`x`)`.

Special Cases:

- If the argument is NaN, then the result is NaN.
- If the argument is positive or negative infinity, then the result is positive infinity.
- If the argument is positive or negative zero, then the result is `Double.MIN_VALUE`.
- If the argument is ±`Double.MAX_VALUE`, then the result is equal to 2^{971}.

Parameters:

`d` - the floating-point value whose ulp is to be returned

Returns:

the size of an ulp of the argument

Since:

1.5

ulp

```
public static float ulp(float f)
```

Returns the size of an ulp of the argument. An ulp, unit in the last place, of a `float` value is the positive distance between this floating-point value and the `float` value next larger in magnitude. Note that for non-NaN x, `ulp(-`x`) == ulp(`x`)`.

Special Cases:

- If the argument is NaN, then the result is NaN.
- If the argument is positive or negative infinity, then the result is positive infinity.
- If the argument is positive or negative zero, then the result is `Float.MIN_VALUE`.
- If the argument is ±`Float.MAX_VALUE`, then the result is equal to 2^{104}.

Parameters:

`f` - the floating-point value whose ulp is to be returned

Returns:

the size of an ulp of the argument

Since:

1.5

signum

```
public static double signum(double d)
```

Returns the signum function of the argument; zero if the argument is zero, 1.0
if the argument is greater than zero, -1.0 if the argument is less than zero.

Special Cases:

- If the argument is NaN, then the result is NaN.
- If the argument is positive zero or negative zero, then the result is the same as the argument.

Parameters:

`d` - the floating-point value whose signum is to be returned

Returns:

the signum function of the argument

Since:

1.5

signum

```
public static float signum(float f)
```

Returns the signum function of the argument; zero if the argument is zero, 1.0f if the argument is greater than zero, -1.0f if the argument is less than zero.

Special Cases:

- If the argument is NaN, then the result is NaN.
- If the argument is positive zero or negative zero, then the result is the same as the argument.

Parameters:

`f` - the floating-point value whose signum is to be returned

Returns:

the signum function of the argument

Since:

1.5

sinh

```
public static double sinh(double x)
```

Returns the hyperbolic sine of a `double` value. The hyperbolic sine of x is defined to be $(e^x - e^{-x})/2$ where e is Euler's number.

Special cases:

- If the argument is NaN, then the result is NaN.
- If the argument is infinite, then the result is an infinity with the same sign as the argument.
- If the argument is zero, then the result is a zero with the same sign as the argument.

Parameters:

`x` - The number whose hyperbolic sine is to be returned.

Returns:

The hyperbolic sine of x.

Since:

1.5

cosh

```
public static double cosh(double x)
```

Returns the hyperbolic cosine of a `double` value. The hyperbolic cosine of x is defined to be $(e^x + e^{-x})/2$ where e is Euler's number.

Special cases:

- If the argument is NaN, then the result is NaN.
- If the argument is infinite, then the result is positive infinity.
- If the argument is zero, then the result is `1.0`.

Parameters:

x - The number whose hyperbolic cosine is to be returned.

Returns:

The hyperbolic cosine of x.

Since:

1.5

tanh

```
public static double tanh(double x)
```

Returns the hyperbolic tangent of a `double` value. The hyperbolic tangent of x is defined to be $(e^x - e^{-x})/(e^x + e^{-x})$, in other words, sinh(x)/cosh(x). Note that the absolute value of the exact tanh is always less than 1.

Special cases:

- If the argument is NaN, then the result is NaN.
- If the argument is zero, then the result is a zero with the same sign as the argument.
- If the argument is positive infinity, then the result is `+1.0`.
- If the argument is negative infinity, then the result is `-1.0`.

Parameters:

x - The number whose hyperbolic tangent is to be returned.

Returns:

The hyperbolic tangent of x.

Since:

1.5

asinh

```
public static double asinh(double x)
```

Returns the inverse hyperbolic sine of a `double` value. The inverse hyperbolic sine of *x* is defined to be the function such that asinh(sinh(*x*)) = *x* for any *x*. Note that both domain and range of the exact asinh are unrestricted.

Special cases:

- If the argument is zero, then the result is a zero with the same sign as the argument.
- If the argument is infinity, then the result is infinity with the same sign as the argument.
- If the argument is NaN, then the result is NaN.

Parameters:

x - The number whose inverse hyperbolic sine is to be returned.

Returns:

The inverse hyperbolic sine of `x`.

Since:

27

acosh

```
public static double acosh(double x)
```

Returns the inverse hyperbolic cosine of a `double` value. The inverse hyperbolic cosine of *x* is defined to be the function such that acosh(cosh(*x*)) = *x* for any *x* >= 0. Note that range of the exact acosh(x) is >= 0.

Special cases:

- If the argument is positive infinity, then the result is positive infinity
- If the argument less than `1.0`, then the result is NaN.
- If the argument is NaN, then the result is NaN.
- If the argument is `1.0`, then the result is positive zero.

Parameters:

x - The number whose inverse hyperbolic cosine is to be returned.

Returns:

The inverse hyperbolic cosine of `x`.

Since:

27

atanh

```
public static double atanh(double x)
```

Returns the inverse hyperbolic tangent of a `double` value. The inverse hyperbolic tangent of *x* is defined to be the function such that atanh(tanh(*x*)) = *x* for any *x*. Note that the domain of the exact atanh is (-1; 1), the range is unrestricted.

Special cases:

- If the argument is NaN, then the result is NaN.
- If the argument is zero, then the result is a zero with the same sign as the argument.
- If the argument is `+1.0`, then the result is positive infinity.
- If the argument is `-1.0`, then the result is negative infinity.
- If the argument is greater than `1.0` in magnitude, then the result is NaN.

Parameters:

x - The number whose inverse hyperbolic tangent is to be returned.

Returns:

The inverse hyperbolic tangent of x.

Since:

27

hypot

```
public static double hypot(double x,
                           double y)
```

Returns sqrt(x^2 +y^2) without intermediate overflow or underflow.

Special cases:

- If either argument is infinite, then the result is positive infinity.
- If either argument is NaN and neither argument is infinite, then the result is NaN.
- If both arguments are zero, the result is positive zero.

Parameters:

x - a value

y - a value

Returns:

sqrt(x^2 +y^2) without intermediate overflow or underflow

Since:

1.5

expm1

```
public static double expm1(double x)
```

Returns $e^x - 1$. Note that for values of x near 0, the exact sum of `expm1(x) + 1` is much closer to the true result of e^x than `exp(x)`.

Special cases:

- If the argument is NaN, the result is NaN.
- If the argument is positive infinity, then the result is positive infinity.
- If the argument is negative infinity, then the result is -1.0.
- If the argument is zero, then the result is a zero with the same sign as the argument.

Parameters:

x - the exponent to raise e to in the computation of $e^x - 1$.

Returns:

the value e^x - 1.

Since:

1.5

log1p

```
public static double log1p(double x)
```

Returns the natural logarithm of the sum of the argument and 1. Note that for small values `x`, the result of `log1p(x)` is much closer to the true result of ln(1 + `x`) than the floating-point evaluation of `log(1.0+x)`.

Special cases:

- If the argument is NaN or less than -1, then the result is NaN.
- If the argument is positive infinity, then the result is positive infinity.
- If the argument is negative one, then the result is negative infinity.
- If the argument is zero, then the result is a zero with the same sign as the argument.

Parameters:

x - a value

Returns:

the value ln(x + 1), the natural log of x + 1

Since:

1.5

copySign

```
public static double copySign(double magnitude,
                              double sign)
```

Returns the first floating-point argument with the sign of the second floating-point argument. For this method, a NaN `sign` argument is always treated as if it were positive.

Parameters:

`magnitude` - the parameter providing the magnitude of the result

`sign` - the parameter providing the sign of the result

Returns:

a value with the magnitude of `magnitude` and the sign of `sign`.

Since:

1.6

copySign

```
public static float copySign(float magnitude,
                             float sign)
```

Returns the first floating-point argument with the sign of the second floating-point argument. For this method, a NaN `sign` argument is always treated as if it were positive.

Parameters:

`magnitude` - the parameter providing the magnitude of the result

`sign` - the parameter providing the sign of the result

Returns:

a value with the magnitude of `magnitude` and the sign of `sign`.

Since:

1.6

getExponent

```
public static int getExponent(float f)
```

Returns the unbiased exponent used in the representation of a `float`. Special cases:

- If the argument is NaN or infinite, then the result is `Float.MAX_EXPONENT` + 1.

- If the argument is zero or subnormal, then the result is `Float.MIN_EXPONENT` -1.

Parameters:

`f` - a `float` value

Returns:

the unbiased exponent of the argument

Since:

1.6

getExponent

```
public static int getExponent(double d)
```

Returns the unbiased exponent used in the representation of a `double`. Special cases:

- If the argument is NaN or infinite, then the result is `Double.MAX_EXPONENT` + 1.
- If the argument is zero or subnormal, then the result is `Double.MIN_EXPONENT` -1.

Parameters:

`d` - a `double` value

Returns:

the unbiased exponent of the argument

Since:

1.6

nextAfter

```
public static double nextAfter(double start,
                               double direction)
```

Returns the floating-point number adjacent to the first argument in the direction of the second argument. If both arguments compare as equal the second argument is returned.

Special cases:

- If either argument is a NaN, then NaN is returned.
- If both arguments are signed zeros, `direction` is returned unchanged (as implied by the requirement of returning the second argument if the arguments compare as equal).

- If `start` is ±`Double.MIN_VALUE` and `direction` has a value such that the result should have a smaller magnitude, then a zero with the same sign as `start` is returned.
- If `start` is infinite and `direction` has a value such that the result should have a smaller magnitude, `Double.MAX_VALUE` with the same sign as `start` is returned.
- If `start` is equal to ± `Double.MAX_VALUE` and `direction` has a value such that the result should have a larger magnitude, an infinity with same sign as `start` is returned.

Parameters:

`start` - starting floating-point value

`direction` - value indicating which of `start`'s neighbors or `start` should be returned

Returns:

The floating-point number adjacent to `start` in the direction of `direction`.

Since:

1.6

nextAfter

```
public static float nextAfter(float start,
                              double direction)
```

Returns the floating-point number adjacent to the first argument in the direction of the second argument. If both arguments compare as equal a value equivalent to the second argument is returned.

Special cases:

- If either argument is a NaN, then NaN is returned.
- If both arguments are signed zeros, a value equivalent to `direction` is returned.
- If `start` is ±`Float.MIN_VALUE` and `direction` has a value such that the result should have a smaller magnitude, then a zero with the same sign as `start` is returned.
- If `start` is infinite and `direction` has a value such that the result should have a smaller magnitude, `Float.MAX_VALUE` with the same sign as `start` is returned.
- If `start` is equal to ± `Float.MAX_VALUE` and `direction` has a value such that the result should have a larger magnitude, an infinity with same sign as `start` is returned.

Parameters:

`start` - starting floating-point value

`direction` - value indicating which of `start`'s neighbors or `start` should be returned

Returns:

The floating-point number adjacent to `start` in the direction of `direction`.

Since:

1.6

nextUp

```
public static double nextUp(double d)
```

Returns the floating-point value adjacent to `d` in the direction of positive infinity. This method is semantically equivalent to `nextAfter(d, Double.POSITIVE_INFINITY);` however, a `nextUp` implementation may run faster than its equivalent `nextAfter` call.

Special Cases:

- If the argument is NaN, the result is NaN.
- If the argument is positive infinity, the result is positive infinity.
- If the argument is zero, the result is `Double.MIN_VALUE`

Parameters:

`d` - starting floating-point value

Returns:

The adjacent floating-point value closer to positive infinity.

Since:

1.6

nextUp

```
public static float nextUp(float f)
```

Returns the floating-point value adjacent to `f` in the direction of positive infinity. This method is semantically equivalent to `nextAfter(f, Float.POSITIVE_INFINITY);` however, a `nextUp` implementation may run faster than its equivalent `nextAfter` call.

Special Cases:

- If the argument is NaN, the result is NaN.
- If the argument is positive infinity, the result is positive infinity.
- If the argument is zero, the result is `Float.MIN_VALUE`

Parameters:

`f` - starting floating-point value

Returns:

The adjacent floating-point value closer to positive infinity.

Since:

1.6

nextDown

```
public static double nextDown(double d)
```

Returns the floating-point value adjacent to `d` in the direction of negative infinity. This method is semantically equivalent to `nextAfter(d, Double.NEGATIVE_INFINITY);` however, a `nextDown` implementation may run faster than its equivalent `nextAfter` call.

Special Cases:

- If the argument is NaN, the result is NaN.
- If the argument is negative infinity, the result is negative infinity.
- If the argument is zero, the result is `-Double.MIN_VALUE`

Parameters:

`d` - starting floating-point value

Returns:

The adjacent floating-point value closer to negative infinity.

Since:

1.8

nextDown

```
public static float nextDown(float f)
```

Returns the floating-point value adjacent to `f` in the direction of negative infinity. This method is semantically equivalent to `nextAfter(f, Float.NEGATIVE_INFINITY);` however, a `nextDown` implementation may run faster than its equivalent `nextAfter` call.

Special Cases:

- If the argument is NaN, the result is NaN.
- If the argument is negative infinity, the result is negative infinity.
- If the argument is zero, the result is `-Float.MIN_VALUE`

Parameters:

`f` - starting floating-point value

Returns:

The adjacent floating-point value closer to negative infinity.

Since:

1.8

scalb

```
public static double scalb(double d,
                           int scaleFactor)
```

Returns `d` × $2^{\texttt{scaleFactor}}$ rounded as if performed by a single correctly rounded floating-point multiply. If the exponent of the result is between `Double.MIN_EXPONENT` and `Double.MAX_EXPONENT`, the answer is calculated exactly. If the exponent of the result would be larger than `Double.MAX_EXPONENT`, an infinity is returned. Note that if the result is subnormal, precision may be lost; that is, when `scalb(x, n)` is subnormal, `scalb(scalb(x, n), -n)` may not equal *x*. When the result is non-NaN, the result has the same sign as `d`.

Special cases:

- If the first argument is NaN, NaN is returned.
- If the first argument is infinite, then an infinity of the same sign is returned.
- If the first argument is zero, then a zero of the same sign is returned.

Parameters:

`d` - number to be scaled by a power of two.

`scaleFactor` - power of 2 used to scale `d`

Returns:

`d` × $2^{\texttt{scaleFactor}}$

Since:

1.6

scalb

```
public static float scalb(float f,
                          int scaleFactor)
```

Returns `f` × $2^{\texttt{scaleFactor}}$ rounded as if performed by a single correctly rounded floating-point multiply. If the exponent of the result is between `Float.MIN_EXPONENT` and `Float.MAX_EXPONENT`, the answer is calculated exactly. If the exponent of the result would be larger than `Float.MAX_EXPONENT`, an infinity is returned. Note that if the result is subnormal, precision may be lost; that is, when `scalb(x, n)` is subnormal, `scalb(scalb(x, n), -n)` may not equal *x*. When the result is non-NaN, the result has the same sign as `f`.

Special cases:

- If the first argument is NaN, NaN is returned.
- If the first argument is infinite, then an infinity of the same sign is returned.
- If the first argument is zero, then a zero of the same sign is returned.

Parameters:

`f` - number to be scaled by a power of two.

`scaleFactor` - power of 2 used to scale `f`

Returns:

$f \times 2^{scaleFactor}$

Since:

1.6

unsignedMultiplyExact

```
public static int unsignedMultiplyExact(int x,
                                        int y)
```

Returns the product of the unsigned arguments, throwing an exception if the result overflows an unsigned `int`.

Parameters:

`x` - the first unsigned value

`y` - the second unsigned value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an unsigned int

Since:

25

unsignedMultiplyExact

```
public static long unsignedMultiplyExact(long x,
                                         int y)
```

Returns the product of the unsigned arguments, throwing an exception if the result overflows an unsigned `long`.

Parameters:

`x` - the first unsigned value

y - the second unsigned value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an unsigned long

Since:

25

unsignedMultiplyExact

```
public static long unsignedMultiplyExact(long x,
                                         long y)
```

Returns the product of the unsigned arguments, throwing an exception if the result overflows an unsigned `long`.

Parameters:

x - the first unsigned value

y - the second unsigned value

Returns:

the result

Throws:

`ArithmeticException` - if the result overflows an unsigned long

Since:

25

powExact

```
public static int powExact(int x,
                           int n)
```

Returns `x` raised to the power of `n`, throwing an exception if the result overflows an `int`. When `n` is 0, the returned value is 1.

Parameters:

x - the base.

n - the exponent.

Returns:

`x` raised to the power of `n`.

Throws:

`ArithmeticException` - when `n` is negative, or when the result overflows an int.

Since:

25

unsignedPowExact

```
public static int unsignedPowExact(int x,
                                   int n)
```

Returns unsigned `x` raised to the power of `n`, throwing an exception if the result overflows an unsigned `int`. When `n` is 0, the returned value is 1.

Parameters:

`x` - the unsigned base.

`n` - the exponent.

Returns:

`x` raised to the power of `n`.

Throws:

`ArithmeticException` - when `n` is negative, or when the result overflows an unsigned int.

Since:

25

powExact

```
public static long powExact(long x,
                            int n)
```

Returns `x` raised to the power of `n`, throwing an exception if the result overflows a `long`. When `n` is 0, the returned value is 1.

Parameters:

`x` - the base.

`n` - the exponent.

Returns:

`x` raised to the power of `n`.

Throws:

`ArithmeticException` - when `n` is negative, or when the result overflows a long.

Since:

25

unsignedPowExact

```
public static long unsignedPowExact(long x,
                                    int n)
```

Returns unsigned `x` raised to the power of `n`, throwing an exception if the result overflows an unsigned `long`. When `n` is 0, the returned value is 1.

Parameters:

`x` - the unsigned base.

`n` - the exponent.

Returns:

`x` raised to the power of `n`.

Throws:

`ArithmeticException` - when `n` is negative, or when the result overflows an unsigned long.

Since:

25

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.