JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class DateTimeParseException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.time.DateTimeException
          java.time.format.DateTimeParseException

All Implemented Interfaces:

Serializable

```
public class DateTimeParseException
extends DateTimeException
```

An exception thrown when an error occurs during parsing.

This exception includes the text being parsed and the error index.

Implementation Requirements:

This class is intended for use in a single thread.

Since:

1.8

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
DateTimeParseException(String message, CharSequence parsedData, int errorIndex)	Constructs a new exception with the specified message.
DateTimeParseException(String message, CharSequence parsedData, int errorIndex, Throwable cause)	Constructs a new exception with the specified message and cause.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description

int	**getErrorIndex**()	Returns the index where the error was found.
String	**getParsedString**()	Returns the string that was being parsed.

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

DateTimeParseException

```
public DateTimeParseException(String message,
                              CharSequence parsedData,
                              int errorIndex)
```

Constructs a new exception with the specified message.

Parameters:

`message` - the message to use for this exception, may be null

`parsedData` - the parsed text, should not be null

`errorIndex` - the index in the parsed string that was invalid, should be a valid index

DateTimeParseException

```
public DateTimeParseException(String message,
                              CharSequence parsedData,
                              int errorIndex,
                              Throwable cause)
```

Constructs a new exception with the specified message and cause.

Parameters:

`message` - the message to use for this exception, may be null

`parsedData` - the parsed text, should not be null

`errorIndex` - the index in the parsed string that was invalid, should be a valid index

`cause` - the cause exception, may be null

Method Details

getParsedString

```
public String getParsedString()
```

Returns the string that was being parsed.

Returns:

the string that was being parsed, should not be null.

getErrorIndex

```
public int getErrorIndex()
```

Returns the index where the error was found.

Returns:

the index in the parsed string that was invalid, should be a valid index

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.