JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface PrimitiveIterator<T,T_CONS>

Type Parameters:

T - the type of elements returned by this PrimitiveIterator. The type must be a wrapper type for a primitive type, such as `Integer` for the primitive `int` type.

T_CONS - the type of primitive consumer. The type must be a primitive specialization of `Consumer` for `T`, such as `IntConsumer` for `Integer`.

All Superinterfaces:

`Iterator`<T>

All Known Subinterfaces:

`PrimitiveIterator.OfDouble`, `PrimitiveIterator.OfInt`, `PrimitiveIterator.OfLong`

```
public interface PrimitiveIterator<T,T_CONS>
extends Iterator<T>
```

A base type for primitive specializations of `Iterator`. Specialized subtypes are provided for `int`, `long`, and `double` values.

The specialized subtype default implementations of `Iterator.next()` and `Iterator.forEachRemaining(java.util.function.Consumer)` box primitive values to instances of their corresponding wrapper class. Such boxing may offset any advantages gained when using the primitive specializations. To avoid boxing, the corresponding primitive-based methods should be used. For example, `PrimitiveIterator.OfInt.nextInt()` and `PrimitiveIterator.OfInt.forEachRemaining(java.util.function.IntConsumer)` should be used in preference to `PrimitiveIterator.OfInt.next()` and `PrimitiveIterator.OfInt.forEachRemaining(java.util.function.Consumer)`.

Iteration of primitive values using boxing-based methods `next()` and `forEachRemaining()`, does not affect the order in which the values, transformed to boxed values, are encountered.

Implementation Note:

If the boolean system property `org.openjdk.java.util.stream.tripwire` is set to `true` then diagnostic warnings are reported if boxing of primitive values occur when operating on primitive subtype specializations.

Since:

1.8

Nested Class Summary

Nested Classes

Modifier and Type	Interface	Description
static interface	PrimitiveIterator.OfDoub	An Iterator specialized for double values.
static interface	PrimitiveIterator.OfInt	An Iterator specialized for int values.
static interface	PrimitiveIterator.OfLong	An Iterator specialized for long values.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
void	forEachRemaining (T_CONS action)	Performs the given action for each remaining element until all elements have been processed or the action throws an exception.

Methods declared in interface Iterator

forEachRemaining, hasNext, next, remove

Method Details

forEachRemaining

```
void forEachRemaining(T_CONS action)
```

Performs the given action for each remaining element until all elements have been processed or the action throws an exception. Actions are performed in the order of iteration, if that order is specified. Exceptions thrown by the action are relayed to the caller.

The behavior of an iterator is unspecified if the action modifies the source of elements in any way (even by calling the `remove` method or other mutator methods of `Iterator` subtypes), unless an overriding class has specified a concurrent modification policy.

Subsequent behavior of an iterator is unspecified if the action throws an exception.

Parameters:

`action` - The action to be performed for each element

Throws:

`NullPointerException` - if the specified action is null

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.