JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class CharArrayWriter

java.lang.Object
    java.io.Writer
        java.io.CharArrayWriter

All Implemented Interfaces:

`Closeable`, `Flushable`, `Appendable`, `AutoCloseable`

```
public class CharArrayWriter
extends Writer
```

This class implements a character buffer that can be used as an Writer. The buffer automatically grows when data is written to the stream. The data can be retrieved using toCharArray() and toString().

Note: Invoking close() on this class has no effect, and methods of this class can be called after the stream has closed without generating an IOException.

Since:

JDK1.1

Field Summary

Fields

Modifier and Type	Field	Description
protected char[]	buf	The buffer where data is stored.
protected int	count	The number of chars in the buffer.

Fields inherited from class java.io.Writer

lock

Constructor Summary

Constructors

Constructor	Description
CharArrayWriter()	Creates a new CharArrayWriter.
CharArrayWriter(int initialSize)	Creates a new CharArrayWriter with the specified initial size.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
CharArrayWriter	append(char c)	Appends the specified character to this writer.
CharArrayWriter	append(CharSequence csq)	Appends the specified character sequence to this writer.
CharArrayWriter	append(CharSequence csq, int start, int end)	Appends a subsequence of the specified character sequence to this writer.
void	close()	Close the stream.
void	flush()	Flush the stream.
void	reset()	Resets the buffer so that you can use it again without throwing away the already allocated buffer.
int	size()	Returns the current size of the buffer.
char[]	toCharArray()	

		Returns a copy of the input data.
String	toString()	Converts input data to a string.
void	write(char[] c, int off, int len)	Writes characters to the buffer.
void	write(int c)	Writes a character to the buffer.
void	write(String str, int off, int len)	Write a portion of a string to the buffer.
void	writeTo(Writer out)	Writes the contents of the buffer to another character stream.

Methods inherited from class java.io.Writer

write, write

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Field Detail

buf

```
protected char[] buf
```

The buffer where data is stored.

count

```
protected int count
```

The number of chars in the buffer.

Constructor Detail

CharArrayWriter

```
public CharArrayWriter()
```

Creates a new CharArrayWriter.

CharArrayWriter

```
public CharArrayWriter(int initialSize)
```

Creates a new CharArrayWriter with the specified initial size.

Parameters:

`initialSize - an int specifying the initial buffer size.`

Throws:

`IllegalArgumentException - if initialSize is negative`

Method Detail

write

```
public void write(int c)
```

Writes a character to the buffer.

Overrides:

`write in class Writer`

Parameters:

`c - int specifying a character to be written`

write

```
public void write(char[] c,
                  int off,
                  int len)
```

Writes characters to the buffer.

Specified by:

`write in class Writer`

Parameters:

c - the data to be written

off - the start offset in the data

len - the number of chars that are written

write

```
public void write(String str,
                  int off,
                  int len)
```

Write a portion of a string to the buffer.

Overrides:

write in class Writer

Parameters:

str - String to be written from

off - Offset from which to start reading characters

len - Number of characters to be written

writeTo

```
public void writeTo(Writer out)
             throws IOException
```

Writes the contents of the buffer to another character stream.

Parameters:

out - the output stream to write to

Throws:

IOException - If an I/O error occurs.

append

```
public CharArrayWriter append(CharSequence csq)
```

Appends the specified character sequence to this writer.

An invocation of this method of the form `out.append(csq)` behaves in exactly the same way as the invocation

```
out.write(csq.toString())
```

Depending on the specification of `toString` for the character sequence `csq`, the entire sequence may not be appended. For instance, invoking the

toString method of a character buffer will return a subsequence whose content depends upon the buffer's position and limit.

Specified by:

append in interface Appendable

Overrides:

append in class Writer

Parameters:

csq - The character sequence to append. If csq is null, then the four characters "null" are appended to this writer.

Returns:

This writer

Since:

1.5

append

```
public CharArrayWriter append(CharSequence csq,
                              int start,
                              int end)
```

Appends a subsequence of the specified character sequence to this writer.

An invocation of this method of the form out.append(csq, start, end) when csq is not null, behaves in exactly the same way as the invocation

```
out.write(csq.subSequence(start, end).toString())
```

Specified by:

append in interface Appendable

Overrides:

append in class Writer

Parameters:

csq - The character sequence from which a subsequence will be appended. If csq is null, then characters will be appended as if csq contained the four characters "null".

start - The index of the first character in the subsequence

end - The index of the character following the last character in the subsequence

Returns:

This writer

Throws:

IndexOutOfBoundsException - If start or end are negative, start is greater than end, or end is greater than csq.length()

Since:

1.5

append

```
public CharArrayWriter append(char c)
```

Appends the specified character to this writer.

An invocation of this method of the form `out.append(c)` behaves in exactly the same way as the invocation

```
out.write(c)
```

Specified by:

append in interface Appendable

Overrides:

append in class Writer

Parameters:

c - The 16-bit character to append

Returns:

This writer

Since:

1.5

reset

```
public void reset()
```

Resets the buffer so that you can use it again without throwing away the already allocated buffer.

toCharArray

```
public char[] toCharArray()
```

Returns a copy of the input data.

Returns:

an array of chars copied from the input data.

size

```
public int size()
```

Returns the current size of the buffer.

Returns:

an int representing the current size of the buffer.

toString

```
public String toString()
```

Converts input data to a string.

Overrides:

toString in class Object

Returns:

the string.

flush

```
public void flush()
```

Flush the stream.

Specified by:

flush in interface Flushable

Specified by:

flush in class Writer

close

```
public void close()
```

Close the stream. This method does not release the buffer, since its contents might still be required. Note: Invoking this method in this class will have no effect.

Specified by:

close in interface Closeable

Specified by:

close in interface AutoCloseable

Specified by:

close in class Writer

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.