JavaScript is disabled on your browser.

compact1, compact2, compact3

java.io

Class StringReader

java.lang.Object
    java.io.Reader
        java.io.StringReader

All Implemented Interfaces:

`Closeable`, `AutoCloseable`, `Readable`

```
public class StringReader
extends Reader
```

A character stream whose source is a string.

Since:

JDK1.1

Field Summary

Fields inherited from class java.io.Reader

`lock`

Constructor Summary

Constructors

Constructor	Description
`StringReader(String s)`	Creates a new string reader.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	close()	Closes the stream and releases any system resources associated with it.
void	mark(int readAheadLimit)	Marks the present position in the stream.
boolean	markSupported()	Tells whether this stream supports the mark() operation, which it does.
int	read()	Reads a single character.
int	read(char[] cbuf, int off, int len)	Reads characters into a portion of an array.
boolean	ready()	Tells whether this stream is ready to be read.
void	reset()	Resets the stream to the most recent mark, or to the beginning of the string if it has never been marked.
long	skip(long ns)	Skips the specified number of characters in the stream.

Methods inherited from class java.io.Reader

read, read

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

StringReader

```
public StringReader(String s)
```

Creates a new string reader.

Parameters:

`s - String providing the character stream.`

Method Detail

read

```
public int read()
         throws IOException
```

Reads a single character.

Overrides:

`read in class Reader`

Returns:

`The character read, or -1 if the end of the stream has been reached`

Throws:

`IOException - If an I/O error occurs`

read

```
public int read(char[] cbuf,
                int off,
                int len)
         throws IOException
```

Reads characters into a portion of an array.

Specified by:

`read in class Reader`

Parameters:

`cbuf - Destination buffer`

`off - Offset at which to start writing characters`

`len - Maximum number of characters to read`

Returns:

The number of characters read, or -1 if the end of the stream has been reached

Throws:

IOException - If an I/O error occurs

skip

```
public long skip(long ns)
          throws IOException
```

Skips the specified number of characters in the stream. Returns the number of characters that were skipped.

The ns parameter may be negative, even though the skip method of the Reader superclass throws an exception in this case. Negative values of ns cause the stream to skip backwards. Negative return values indicate a skip backwards. It is not possible to skip backwards past the beginning of the string.

If the entire string has been read or skipped, then this method has no effect and always returns 0.

Overrides:

skip in class Reader

Parameters:

ns - The number of characters to skip

Returns:

The number of characters actually skipped

Throws:

IOException - If an I/O error occurs

ready

```
public boolean ready()
              throws IOException
```

Tells whether this stream is ready to be read.

Overrides:

ready in class Reader

Returns:

True if the next read() is guaranteed not to block for input

Throws:

IOException - If the stream is closed

markSupported

```
public boolean markSupported()
```

Tells whether this stream supports the mark() operation, which it does.

Overrides:

markSupported in class Reader

Returns:

true if and only if this stream supports the mark operation.

mark

```
public void mark(int readAheadLimit)
          throws IOException
```

Marks the present position in the stream. Subsequent calls to reset() will reposition the stream to this point.

Overrides:

mark in class Reader

Parameters:

readAheadLimit - Limit on the number of characters that may be read while still preserving the mark. Because the stream's input comes from a string, there is no actual limit, so this argument must not be negative, but is otherwise ignored.

Throws:

IllegalArgumentException - If readAheadLimit < 0

IOException - If an I/O error occurs

reset

```
public void reset()
           throws IOException
```

Resets the stream to the most recent mark, or to the beginning of the string if it has never been marked.

Overrides:

`reset` in class `Reader`

Throws:

`IOException` - If an I/O error occurs

close

```
public void close()
```

Closes the stream and releases any system resources associated with it. Once the stream has been closed, further read(), ready(), mark(), or reset() invocations will throw an IOException. Closing a previously closed stream has no effect.

Specified by:

`close` in interface `Closeable`

Specified by:

`close` in interface `AutoCloseable`

Specified by:

`close` in class `Reader`

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.