JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time

Class ZonedDateTime

java.lang.Object
  java.time.ZonedDateTime

All Implemented Interfaces:

`Serializable`, `Comparable<ChronoZonedDateTime<?>>`, `ChronoZonedDateTime<LocalDate>`, `Temporal`, `TemporalAccessor`

```
public final class ZonedDateTime
extends Object
implements Temporal, ChronoZonedDateTime<LocalDate>, Serializable
```

A date-time with a time-zone in the ISO-8601 calendar system, such as `2007-12-03T10:15:30+01:00 Europe/Paris`.

`ZonedDateTime` is an immutable representation of a date-time with a time-zone. This class stores all date and time fields, to a precision of nanoseconds, and a time-zone, with a zone offset used to handle ambiguous local date-times. For example, the value "2nd October 2007 at 13:45.30.123456789 +02:00 in the Europe/Paris time-zone" can be stored in a `ZonedDateTime`.

This class handles conversion from the local time-line of `LocalDateTime` to the instant time-line of `Instant`. The difference between the two time-lines is the offset from UTC/Greenwich, represented by a `ZoneOffset`.

Converting between the two time-lines involves calculating the offset using the `rules` accessed from the `ZoneId`. Obtaining the offset for an instant is simple, as there is exactly one valid offset for each instant. By contrast, obtaining the offset for a local date-time is not straightforward. There are three cases:

- Normal, with one valid offset. For the vast majority of the year, the normal case applies, where there is a single valid offset for the local date-time.

- Gap, with zero valid offsets. This is when clocks jump forward typically due to the spring daylight savings change from "winter" to "summer". In a gap there are local date-time values with no valid offset.
- Overlap, with two valid offsets. This is when clocks are set back typically due to the autumn daylight savings change from "summer" to "winter". In an overlap there are local date-time values with two valid offsets.

Any method that converts directly or implicitly from a local date-time to an instant by obtaining the offset has the potential to be complicated.

For Gaps, the general strategy is that if the local date-time falls in the middle of a Gap, then the resulting zoned date-time will have a local date-time shifted forwards by the length of the Gap, resulting in a date-time in the later offset, typically "summer" time.

For Overlaps, the general strategy is that if the local date-time falls in the middle of an Overlap, then the previous offset will be retained. If there is no previous offset, or the previous offset is invalid, then the earlier offset is used, typically "summer" time.. Two additional methods, `withEarlierOffsetAtOverlap()` and `withLaterOffsetAtOverlap()`, help manage the case of an overlap.

In terms of design, this class should be viewed primarily as the combination of a `LocalDateTime` and a `ZoneId`. The `ZoneOffset` is a vital, but secondary, piece of information, used to ensure that the class represents an instant, especially during a daylight savings overlap.

This is a value-based class; use of identity-sensitive operations (including reference equality (==), identity hash code, or synchronization) on instances of `ZonedDateTime` may have unpredictable results and should be avoided. The `equals` method should be used for comparisons.

Implementation Requirements:

`A ZonedDateTime holds state equivalent to three separate objects, a LocalDateTime, a ZoneId and the resolved ZoneOffset. The offset and local date-time are used to define an instant when necessary. The zone ID is used to obtain the rules for how and when the offset changes. The offset cannot be freely set, as the zone controls which offsets are valid.`

`This class is immutable and thread-safe.`

Since:

`1.8`

See Also:

`Serialized Form`

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	equals(Object obj)	Checks if this date-tim another date-time.
String	format(DateTimeFormatter formatter)	Formats this date-time specified formatter.
static ZonedDateTime	from(TemporalAccessor temporal)	Obtains an instance of from a temporal object
int	get(TemporalField field)	Gets the value of the sp from this date-time as
int	getDayOfMonth()	Gets the day-of-month
DayOfWeek	getDayOfWeek()	Gets the day-of-week fi enum DayOfWeek.
int	getDayOfYear()	Gets the day-of-year fie
int	getHour()	Gets the hour-of-day fie
long	getLong(TemporalField field)	Gets the value of the sp from this date-time as
int	getMinute()	Gets the minute-of-hou
Month	getMonth()	Gets the month-of-year Month enum.
int	getMonthValue()	Gets the month-of-year 12.
int	getNano()	Gets the nano-of-secon
ZoneOffset	getOffset()	Gets the zone offset, su
int	getSecond()	Gets the second-of-min
int	getYear()	Gets the year field.
ZoneId	getZone()	Gets the time-zone, suc Paris'.
int	hashCode()	A hash code for this da
boolean	isSupported(TemporalField field)	Checks if the specified supported.

boolean	**isSupported**(**TemporalUnit** unit)	Checks if the specified supported.
ZonedDateTime	**minus**(long amountToSubtract, **TemporalUnit** unit)	Returns a copy of this the specified amount s
ZonedDateTime	**minus**(**TemporalAmount** amountToSubtract)	Returns a copy of this the specified amount s
ZonedDateTime	**minusDays**(long days)	Returns a copy of this with the specified num subtracted.
ZonedDateTime	**minusHours**(long hours)	Returns a copy of this with the specified num subtracted.
ZonedDateTime	**minusMinutes**(long minutes)	Returns a copy of this with the specified num subtracted.
ZonedDateTime	**minusMonths**(long months)	Returns a copy of this with the specified num subtracted.
ZonedDateTime	**minusNanos**(long nanos)	Returns a copy of this with the specified num nanoseconds subtracte
ZonedDateTime	**minusSeconds**(long seconds)	Returns a copy of this with the specified num subtracted.
ZonedDateTime	**minusWeeks**(long weeks)	Returns a copy of this with the specified num subtracted.
ZonedDateTime	**minusYears**(long years)	Returns a copy of this with the specified num subtracted.
static **ZonedDateTime**	**now**()	Obtains the current da system clock in the def
static **ZonedDateTime**	**now**(**Clock** clock)	Obtains the current da specified clock.

static **ZonedDateTime**	**now**(**ZoneId** zone)	Obtains the current da system clock in the spe zone.
static **ZonedDateTime**	**of**(int year, int month, int dayOfMonth, int hour, int minute, int second, int nanoOfSecond, **ZoneId** zone)	Obtains an instance of from a year, month, da second, nanosecond an
static **ZonedDateTime**	**of**(**LocalDate** date, **LocalTime** time, **ZoneId** zone)	Obtains an instance of from a local date and t
static **ZonedDateTime**	**of**(**LocalDateTime** localDateTime, **ZoneId** zone)	Obtains an instance of from a local date-time.
static **ZonedDateTime**	**ofInstant**(**Instant** instant, **ZoneId** zone)	Obtains an instance of from an `Instant`.
static **ZonedDateTime**	**ofInstant**(**LocalDateTime** localDateTime, **ZoneOffset** offset, **ZoneId** zone)	Obtains an instance of from the instant forme the local date-time and
static **ZonedDateTime**	**ofLocal**(**LocalDateTime** localDateTime, **ZoneId** zone, **ZoneOffset** preferredOffset)	Obtains an instance of from a local date-time preferred offset if poss
static **ZonedDateTime**	**ofStrict**(**LocalDateTime** localDateTime, **ZoneOffset** offset, **ZoneId** zone)	Obtains an instance of strictly validating the c local date-time, offset a
static **ZonedDateTime**	**parse**(**CharSequence** text)	Obtains an instance of from a text string such `2007-12-03T10:15:30-` `Paris]`.
static **ZonedDateTime**	**parse**(**CharSequence** text, **DateTimeFormatter** formatter)	Obtains an instance of from a text string using formatter.
ZonedDateTime	**plus**(long amountToAdd, **TemporalUnit** unit)	Returns a copy of this the specified amount a
ZonedDateTime	**plus**(**TemporalAmount** amountToAdd)	Returns a copy of this the specified amount a
ZonedDateTime	**plusDays**(long days)	Returns a copy of this with the specified num added.
ZonedDateTime	**plusHours**(long hours)	

		Returns a copy of this with the specified num added.
ZonedDateTime	plusMinutes(long minutes)	Returns a copy of this with the specified num added.
ZonedDateTime	plusMonths(long months)	Returns a copy of this with the specified num added.
ZonedDateTime	plusNanos(long nanos)	Returns a copy of this with the specified num nanoseconds added.
ZonedDateTime	plusSeconds(long seconds)	Returns a copy of this with the specified num added.
ZonedDateTime	plusWeeks(long weeks)	Returns a copy of this with the specified num added.
ZonedDateTime	plusYears(long years)	Returns a copy of this with the specified num added.
<R> R	query(TemporalQuery<R> query)	Queries this date-time specified query.
ValueRange	range(TemporalField field)	Gets the range of valid specified field.
LocalDate	toLocalDate()	Gets the LocalDate pa time.
LocalDateTime	toLocalDateTime()	Gets the LocalDateTim date-time.
LocalTime	toLocalTime()	Gets the LocalTime pa time.
OffsetDateTime	toOffsetDateTime()	Converts this date-time OffsetDateTime.
String	toString()	Outputs this date-time such as 2007-12-03T10:15:30 Paris].

ZonedDateTime	**truncatedTo**(**TemporalUnit** unit)	Returns a copy of this with the time truncate
long	**until**(**Temporal** endExclusive, **TemporalUnit** unit)	Calculates the amount another date-time in te specified unit.
ZonedDateTime	**with**(**TemporalAdjuster** adjuster)	Returns an adjusted co time.
ZonedDateTime	**with**(**TemporalField** field, long newValue)	Returns a copy of this the specified field set t
ZonedDateTime	**withDayOfMonth**(int dayOfMonth)	Returns a copy of this with the day-of-month
ZonedDateTime	**withDayOfYear**(int dayOfYear)	Returns a copy of this with the day-of-year alt
ZonedDateTime	**withEarlierOffsetAtOverlap**()	Returns a copy of this changing the zone offs of the two valid offsets line overlap.
ZonedDateTime	**withFixedOffsetZone**()	Returns a copy of this the zone ID set to the c
ZonedDateTime	**withHour**(int hour)	Returns a copy of this with the hour-of-day al
ZonedDateTime	**withLaterOffsetAtOverlap**()	Returns a copy of this changing the zone offs the two valid offsets at line overlap.
ZonedDateTime	**withMinute**(int minute)	Returns a copy of this with the minute-of-hou
ZonedDateTime	**withMonth**(int month)	Returns a copy of this with the month-of-year
ZonedDateTime	**withNano**(int nanoOfSecond)	Returns a copy of this with the nano-of-secon
ZonedDateTime	**withSecond**(int second)	Returns a copy of this with the second-of-min
ZonedDateTime	**withYear**(int year)	Returns a copy of this with the year altered.

ZonedDateTime	withZoneSameInstant(ZoneId zone)	Returns a copy of this d different time-zone, ret instant.
ZonedDateTime	withZoneSameLocal(ZoneId zone)	Returns a copy of this d different time-zone, ret date-time if possible.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Methods inherited from interface java.time.chrono.ChronoZonedDateTime

compareTo, getChronology, isAfter, isBefore, isEqual, timeLineOrder, toEpochSecond, toInstant

Method Detail

now

```
public static ZonedDateTime now()
```

Obtains
the current date-time from the system clock in the default time-zone.

This will query the system clock in the default time-zone to obtain the current date-time. The zone and offset will be set based on the time-zone in the clock.

Using this method will prevent the ability to use an alternate clock for testing because the clock is hard-coded.

Returns:

the current date-time using the system clock, not null

now

```
public static ZonedDateTime now(ZoneId zone)
```

Obtains the current date-time from the system clock in the specified time-zone.

This will query the system clock to obtain the current date-time. Specifying the time-zone avoids dependence on the default time-zone. The offset will be calculated from the specified time-zone.

Using this method will prevent the ability to use an alternate clock for testing because the clock is hard-coded.

Parameters:

`zone - the zone ID to use, not null`

Returns:

`the current date-time using the system clock, not null`

now

```
public static ZonedDateTime now(Clock clock)
```

Obtains the current date-time from the specified clock.

This will query the specified clock to obtain the current date-time. The zone and offset will be set based on the time-zone in the clock.

Using this method allows the use of an alternate clock for testing. The alternate clock may be introduced using dependency injection.

Parameters:

`clock - the clock to use, not null`

Returns:

`the current date-time, not null`

of

```
public static ZonedDateTime of(LocalDate date,
                               LocalTime time,
                               ZoneId zone)
```

Obtains an instance of `ZonedDateTime` from a local date and time.

This creates a zoned date-time matching the input local date and time as closely as possible. Time-zone rules, such as daylight savings, mean that not every local date-time is valid for the specified zone, thus the local date-time may be adjusted.

The local date time and first combined to form a local date-time. The local date-time is then resolved to a single instant on the time-line. This is achieved by finding a valid offset from UTC/Greenwich for the local date-time as defined by the rules of the zone ID.

In most cases, there is only one valid offset for a local date-time. In the case of an overlap, when clocks are set back, there are two valid offsets. This method uses the earlier offset typically corresponding to "summer".

In the case of a gap, when clocks jump forward, there is no valid offset. Instead, the local date-time is adjusted to be later by the length of the gap. For a typical one hour daylight savings change, the local date-time will be moved one hour later into the offset typically corresponding to "summer".

Parameters:

`date - the local date, not null`

`time - the local time, not null`

`zone - the time-zone, not null`

Returns:

`the offset date-time, not null`

of

```
public static ZonedDateTime of(LocalDateTime localDateTime,
                               ZoneId zone)
```

Obtains an instance of `ZonedDateTime` from a local date-time.

This creates a zoned date-time matching the input local date-time as closely as possible. Time-zone rules, such as daylight savings, mean that not every local date-time is valid for the specified zone, thus the local date-time may be adjusted.

The local date-time is resolved to a single instant on the time-line. This is achieved by finding a valid offset from UTC/Greenwich for the local date-time as defined by the `rules` of the zone ID.

In most cases, there is only one valid offset for a local date-time. In the case of an overlap, when clocks are set back, there are two valid offsets. This method uses the earlier offset typically corresponding to "summer".

In the case of a gap, when clocks jump forward, there is no valid offset. Instead, the local date-time is adjusted to be later by the length of the gap. For a typical one hour daylight savings change, the local date-time will be moved one hour later into the offset typically corresponding to "summer".

Parameters:

`localDateTime - the local date-time, not null`

`zone - the time-zone, not null`

Returns:

`the zoned date-time, not null`

of

```
public static ZonedDateTime of(int year,
                               int month,
                               int dayOfMonth,
                               int hour,
                               int minute,
                               int second,
                               int nanoOfSecond,
                               ZoneId zone)
```

Obtains an instance of `ZonedDateTime` from a year, month, day, hour, minute, second, nanosecond and time-zone.

This creates a zoned date-time matching the local date-time of the seven specified fields as closely as possible. Time-zone rules, such as daylight savings, mean that not every local date-time is valid for the specified zone, thus the local date-time may be adjusted.

The local date-time is resolved to a single instant on the time-line. This is achieved by finding a valid offset from UTC/Greenwich for the local date-time as defined by the `rules` of the zone ID.

In most cases, there is only one valid offset for a local date-time. In the case of an overlap, when clocks are set back, there are two valid offsets. This method uses the earlier offset typically corresponding to "summer".

In the case of a gap, when clocks jump forward, there is no valid offset. Instead, the local date-time is adjusted to be later by the length of the gap. For a typical one hour daylight savings change, the local date-time will be moved one hour later into the offset typically corresponding to "summer".

This method exists primarily for writing test cases. Non test-code will typically use other methods to create an offset time. `LocalDateTime` has five additional convenience variants of the equivalent factory method taking fewer arguments. They are not provided here to reduce the footprint of the API.

Parameters:

`year - the year to represent, from MIN_YEAR to MAX_YEAR`

`month - the month-of-year to represent, from 1 (January) to 12 (December)`

`dayOfMonth - the day-of-month to represent, from 1 to 31`

`hour - the hour-of-day to represent, from 0 to 23`

`minute - the minute-of-hour to represent, from 0 to 59`

`second - the second-of-minute to represent, from 0 to 59`

nanoOfSecond - the nano-of-second to represent, from 0 to 999,999,999

zone - the time-zone, not null

Returns:

the offset date-time, not null

Throws:

DateTimeException - if the value of any field is out of range, or if the day-of-month is invalid for the month-year

ofLocal

```
public static ZonedDateTime ofLocal(LocalDateTime localDateTime,
                                    ZoneId zone,
                                    ZoneOffset preferredOffset)
```

Obtains an instance of ZonedDateTime from a local date-time using the preferred offset if possible.

The local date-time is resolved to a single instant on the time-line. This is achieved by finding a valid offset from UTC/Greenwich for the local date-time as defined by the rules of the zone ID.

In most cases, there is only one valid offset for a local date-time. In the case of an overlap, where clocks are set back, there are two valid offsets. If the preferred offset is one of the valid offsets then it is used. Otherwise the earlier valid offset is used, typically corresponding to "summer".

In the case of a gap, where clocks jump forward, there is no valid offset. Instead, the local date-time is adjusted to be later by the length of the gap. For a typical one hour daylight savings change, the local date-time will be moved one hour later into the offset typically corresponding to "summer".

Parameters:

localDateTime - the local date-time, not null

zone - the time-zone, not null

preferredOffset - the zone offset, null if no preference

Returns:

the zoned date-time, not null

ofInstant

```
public static ZonedDateTime ofInstant(Instant instant,
                                      ZoneId zone)
```

Obtains an instance of ZonedDateTime from an Instant.

This creates a zoned date-time with the same instant as that specified. Calling ChronoZonedDateTime.toInstant() will return an instant equal to the one used here.

Converting an instant to a zoned date-time is simple as there is only one valid offset for each instant.

Parameters:

instant - the instant to create the date-time from, not null

zone - the time-zone, not null

Returns:

the zoned date-time, not null

Throws:

DateTimeException - if the result exceeds the supported range

ofInstant

```
public static ZonedDateTime ofInstant(LocalDateTime localDateTime,
                                      ZoneOffset offset,
                                      ZoneId zone)
```

Obtains an instance of ZonedDateTime from the instant formed by combining the local date-time and offset.

This creates a zoned date-time by combining the LocalDateTime and ZoneOffset. This combination uniquely specifies an instant without ambiguity.

Converting an instant to a zoned date-time is simple as there is only one valid offset for each instant. If the valid offset is different to the offset specified, then the date-time and offset of the zoned date-time will differ from those specified.

If the ZoneId to be used is a ZoneOffset, this method is equivalent to of(LocalDateTime, ZoneId).

Parameters:

localDateTime - the local date-time, not null

offset - the zone offset, not null

zone - the time-zone, not null

Returns:

the zoned date-time, not null

ofStrict

```
public static ZonedDateTime ofStrict(LocalDateTime localDateTime,
                                     ZoneOffset offset,
                                     ZoneId zone)
```

Obtains an instance of `ZonedDateTime` strictly validating the combination of local date-time, offset and zone ID.

This creates a zoned date-time ensuring that the offset is valid for the local date-time according to the rules of the specified zone. If the offset is invalid, an exception is thrown.

Parameters:

`localDateTime - the local date-time, not null`

`offset - the zone offset, not null`

`zone - the time-zone, not null`

Returns:

`the zoned date-time, not null`

from

```
public static ZonedDateTime from(TemporalAccessor temporal)
```

Obtains an instance of `ZonedDateTime` from a temporal object.

This obtains a zoned date-time based on the specified temporal. A `TemporalAccessor` represents an arbitrary set of date and time information, which this factory converts to an instance of `ZonedDateTime`.

The conversion will first obtain a `ZoneId` from the temporal object, falling back to a `ZoneOffset` if necessary. It will then try to obtain an `Instant`, falling back to a `LocalDateTime` if necessary. The result will be either the combination of `ZoneId` or `ZoneOffset` with `Instant` or `LocalDateTime`. Implementations are permitted to perform optimizations such as accessing those fields that are equivalent to the relevant objects.

This method matches the signature of the functional interface `TemporalQuery` allowing it to be used as a query via method reference, `ZonedDateTime::from`.

Specified by:

`from` in interface `ChronoZonedDateTime<LocalDate>`

Parameters:

`temporal - the temporal object to convert, not null`

Returns:

the zoned date-time, not null

Throws:

DateTimeException - if unable to convert to an ZonedDateTime

See Also:

Chronology.zonedDateTime(TemporalAccessor)

parse

```
public static ZonedDateTime parse(CharSequence text)
```

Obtains an instance of ZonedDateTime from a text string such as 2007-12-03T10:15:30+01:00[Europe/Paris].

The string must represent a valid date-time and is parsed using DateTimeFormatter.ISO_ZONED_DATE_TIME.

Parameters:

text - the text to parse such as "2007-12-03T10:15:30+01:00[Europe/Paris]", not null

Returns:

the parsed zoned date-time, not null

Throws:

DateTimeParseException - if the text cannot be parsed

parse

```
public static ZonedDateTime parse(CharSequence text,
                                  DateTimeFormatter formatter)
```

Obtains an instance of ZonedDateTime from a text string using a specific formatter.

The text is parsed using the formatter, returning a date-time.

Parameters:

text - the text to parse, not null

formatter - the formatter to use, not null

Returns:

the parsed zoned date-time, not null

Throws:

DateTimeParseException - if the text cannot be parsed

isSupported

```
public boolean isSupported(TemporalField field)
```

Checks if the specified field is supported.

This checks if this date-time can be queried for the specified field. If false, then calling the `range`, `get` and `with(TemporalField, long)` methods will throw an exception.

If the field is a `ChronoField` then the query is implemented here. The supported fields are:

- `NANO_OF_SECOND`
- `NANO_OF_DAY`
- `MICRO_OF_SECOND`
- `MICRO_OF_DAY`
- `MILLI_OF_SECOND`
- `MILLI_OF_DAY`
- `SECOND_OF_MINUTE`
- `SECOND_OF_DAY`
- `MINUTE_OF_HOUR`
- `MINUTE_OF_DAY`
- `HOUR_OF_AMPM`
- `CLOCK_HOUR_OF_AMPM`
- `HOUR_OF_DAY`
- `CLOCK_HOUR_OF_DAY`
- `AMPM_OF_DAY`
- `DAY_OF_WEEK`
- `ALIGNED_DAY_OF_WEEK_IN_MONTH`
- `ALIGNED_DAY_OF_WEEK_IN_YEAR`
- `DAY_OF_MONTH`
- `DAY_OF_YEAR`
- `EPOCH_DAY`
- `ALIGNED_WEEK_OF_MONTH`
- `ALIGNED_WEEK_OF_YEAR`
- `MONTH_OF_YEAR`
- `PROLEPTIC_MONTH`
- `YEAR_OF_ERA`
- `YEAR`
- `ERA`
- `INSTANT_SECONDS`
- `OFFSET_SECONDS`

All other `ChronoField` instances will return false.

If the field is not a `ChronoField`, then the result of this method is obtained by invoking `TemporalField.isSupportedBy(TemporalAccessor)` passing `this` as the argument. Whether the field is supported is determined by the field.

Specified by:

isSupported in interface ChronoZonedDateTime<LocalDate>

Specified by:

isSupported in interface TemporalAccessor

Parameters:

field - the field to check, null returns false

Returns:

true if the field is supported on this date-time, false if not

isSupported

public boolean isSupported(TemporalUnit unit)

Checks if the specified unit is supported.

This checks if the specified unit can be added to, or subtracted from, this date-time. If false, then calling the plus(long, TemporalUnit) and minus methods will throw an exception.

If the unit is a ChronoUnit then the query is implemented here. The supported units are:

- NANOS
- MICROS
- MILLIS
- SECONDS
- MINUTES
- HOURS
- HALF_DAYS
- DAYS
- WEEKS
- MONTHS
- YEARS
- DECADES
- CENTURIES
- MILLENNIA
- ERAS

All other ChronoUnit instances will return false.

If the unit is not a ChronoUnit, then the result of this method is obtained by invoking TemporalUnit.isSupportedBy(Temporal) passing this as the argument. Whether the unit is supported is determined by the unit.

Specified by:

isSupported in interface ChronoZonedDateTime<LocalDate>

Specified by:

isSupported in interface Temporal

Parameters:

`unit - the unit to check, null returns false`

Returns:

`true if the unit can be added/subtracted, false if not`

range

```
public ValueRange range(TemporalField field)
```

Gets the range of valid values for the specified field.

The range object expresses the minimum and maximum valid values for a field. This date-time is used to enhance the accuracy of the returned range. If it is not possible to return the range, because the field is not supported or for some other reason, an exception is thrown.

If the field is a `ChronoField` then the query is implemented here. The `supported fields` will return appropriate range instances. All other `ChronoField` instances will throw an `UnsupportedTemporalTypeException`.

If the field is not a `ChronoField`, then the result of this method is obtained by invoking `TemporalField.rangeRefinedBy(TemporalAccessor)` passing `this` as the argument. Whether the range can be obtained is determined by the field.

Specified by:

`range in interface ChronoZonedDateTime<LocalDate>`

Specified by:

`range in interface TemporalAccessor`

Parameters:

`field - the field to query the range for, not null`

Returns:

`the range of valid values for the field, not null`

Throws:

`DateTimeException - if the range for the field cannot be obtained`

`UnsupportedTemporalTypeException - if the field is not supported`

get

```
public int get(TemporalField field)
```

Gets the value of the specified field from this date-time as an `int`.

This queries this date-time for the value of the specified field. The returned value will always be within the valid range of values for the field. If it is not possible to return the value, because the field is not supported or for some other reason, an exception is thrown.

If the field is a ChronoField then the query is implemented here. The supported fields will return valid values based on this date-time, except NANO_OF_DAY, MICRO_OF_DAY, EPOCH_DAY, PROLEPTIC_MONTH and INSTANT_SECONDS which are too large to fit in an int and throw a DateTimeException. All other ChronoField instances will throw an UnsupportedTemporalTypeException.

If the field is not a ChronoField, then the result of this method is obtained by invoking TemporalField.getFrom(TemporalAccessor) passing this as the argument. Whether the value can be obtained, and what the value represents, is determined by the field.

Specified by:

get in interface ChronoZonedDateTime<LocalDate>

Specified by:

get in interface TemporalAccessor

Parameters:

field - the field to get, not null

Returns:

the value for the field

Throws:

DateTimeException - if a value for the field cannot be obtained or the value is outside the range of valid values for the field

UnsupportedTemporalTypeException - if the field is not supported or the range of values exceeds an int

ArithmeticException - if numeric overflow occurs

getLong

public long getLong(TemporalField field)

Gets the value of the specified field from this date-time as a long.

This queries this date-time for the value of the specified field. If it is not possible to return the value, because the field is not supported or for some other reason, an exception is thrown.

If the field is a ChronoField then the query is implemented here. The supported fields will return valid values based on this date-time. All other ChronoField instances will throw an UnsupportedTemporalTypeException.

If the field is not a `ChronoField`, then the result of this method is obtained by invoking `TemporalField.getFrom(TemporalAccessor)` passing `this` as the argument. Whether the value can be obtained, and what the value represents, is determined by the field.

Specified by:

`getLong` in interface `ChronoZonedDateTime<LocalDate>`

Specified by:

`getLong` in interface `TemporalAccessor`

Parameters:

`field - the field to get, not null`

Returns:

`the value for the field`

Throws:

`DateTimeException - if a value for the field cannot be obtained`

`UnsupportedTemporalTypeException - if the field is not supported`

`ArithmeticException - if numeric overflow occurs`

getOffset

`public ZoneOffset getOffset()`

Gets the zone offset, such as '+01:00'.

This is the offset of the local date-time from UTC/Greenwich.

Specified by:

`getOffset` in interface `ChronoZonedDateTime<LocalDate>`

Returns:

`the zone offset, not null`

withEarlierOffsetAtOverlap

`public ZonedDateTime withEarlierOffsetAtOverlap()`

Returns a copy of this date-time changing the zone offset to the earlier of the two valid offsets at a local time-line overlap.

This method only has any effect when the local time-line overlaps, such as at an autumn daylight savings cutover. In this scenario, there are two valid offsets for the local date-time. Calling this method will return a zoned date-time with the earlier of the two selected.

If this method is called when it is not an overlap, `this` is returned.

This instance is immutable and unaffected by this method call.

Specified by:

withEarlierOffsetAtOverlap in interface ChronoZonedDateTime<LocalDate>

Returns:

a ZonedDateTime based on this date-time with the earlier offset, not null

withLaterOffsetAtOverlap

```
public ZonedDateTime withLaterOffsetAtOverlap()
```

Returns a copy of this date-time changing the zone offset to the later of the two valid offsets at a local time-line overlap.

This method only has any effect when the local time-line overlaps, such as at an autumn daylight savings cutover. In this scenario, there are two valid offsets for the local date-time. Calling this method will return a zoned date-time with the later of the two selected.

If this method is called when it is not an overlap, `this` is returned.

This instance is immutable and unaffected by this method call.

Specified by:

withLaterOffsetAtOverlap in interface ChronoZonedDateTime<LocalDate>

Returns:

a ZonedDateTime based on this date-time with the later offset, not null

getZone

```
public ZoneId getZone()
```

Gets the time-zone, such as 'Europe/Paris'.

This returns the zone ID. This identifies the time-zone `rules` that determine when and how the offset from UTC/Greenwich changes.

The zone ID may be same as the offset. If this is true, then any future calculations, such as addition or subtraction, have no complex edge cases due to time-zone rules. See also `withFixedOffsetZone()`.

Specified by:

getZone in interface ChronoZonedDateTime<LocalDate>

Returns:

the time-zone, not null

withZoneSameLocal

public ZonedDateTime withZoneSameLocal(ZoneId zone)

Returns a copy of this date-time with a different time-zone, retaining the local date-time if possible.

This method changes the time-zone and retains the local date-time. The local date-time is only changed if it is invalid for the new zone, determined using the same approach as ofLocal(LocalDateTime, ZoneId, ZoneOffset).

To change the zone and adjust the local date-time, use withZoneSameInstant(ZoneId).

This instance is immutable and unaffected by this method call.

Specified by:

withZoneSameLocal in interface ChronoZonedDateTime<LocalDate>

Parameters:

zone - the time-zone to change to, not null

Returns:

a ZonedDateTime based on this date-time with the requested zone, not null

withZoneSameInstant

public ZonedDateTime withZoneSameInstant(ZoneId zone)

Returns a copy of this date-time with a different time-zone, retaining the instant.

This method changes the time-zone and retains the instant. This normally results in a change to the local date-time.

This method is based on retaining the same instant, thus gaps and overlaps in the local time-line have no effect on the result.

To change the offset while keeping the local time, use withZoneSameLocal(ZoneId).

Specified by:

withZoneSameInstant in interface ChronoZonedDateTime<LocalDate>

Parameters:

zone - the time-zone to change to, not null

Returns:

a ZonedDateTime based on this date-time with the requested zone, not null

Throws:

DateTimeException - if the result exceeds the supported date range

withFixedOffsetZone

```
public ZonedDateTime withFixedOffsetZone()
```

Returns a copy of this date-time with the zone ID set to the offset.

This returns a zoned date-time where the zone ID is the same as `getOffset()`. The local date-time, offset and instant of the result will be the same as in this date-time.

Setting the date-time to a fixed single offset means that any future calculations, such as addition or subtraction, have no complex edge cases due to time-zone rules. This might also be useful when sending a zoned date-time across a network, as most protocols, such as ISO-8601, only handle offsets, and not region-based zone IDs.

This is equivalent to `ZonedDateTime.of(zdt.toLocalDateTime(), zdt.getOffset())`.

Returns:

a ZonedDateTime with the zone ID set to the offset, not null

toLocalDateTime

```
public LocalDateTime toLocalDateTime()
```

Gets the `LocalDateTime` part of this date-time.

This returns a `LocalDateTime` with the same year, month, day and time as this date-time.

Specified by:

toLocalDateTime in interface ChronoZonedDateTime<LocalDate>

Returns:

the local date-time part of this date-time, not null

toLocalDate

```
public LocalDate toLocalDate()
```

Gets the `LocalDate` part of this date-time.

This returns a `LocalDate` with the same year, month and day as this date-time.

Specified by:

`toLocalDate` in interface `ChronoZonedDateTime<LocalDate>`

Returns:

the date part of this date-time, not null

getYear

```
public int getYear()
```

Gets the year field.

This method returns the primitive `int` value for the year.

The year returned by this method is proleptic as per `get(YEAR)`. To obtain the year-of-era, use `get(YEAR_OF_ERA)`.

Returns:

the year, from MIN_YEAR to MAX_YEAR

getMonthValue

```
public int getMonthValue()
```

Gets the month-of-year field from 1 to 12.

This method returns the month as an `int` from 1 to 12. Application code is frequently clearer if the enum `Month` is used by calling `getMonth()`.

Returns:

the month-of-year, from 1 to 12

See Also:

`getMonth()`

getMonth

```
public Month getMonth()
```

Gets the month-of-year field using the `Month` enum.

This method returns the enum `Month` for the month. This avoids confusion as to what `int` values mean. If you need access to the primitive `int` value then the enum provides the `int value`.

Returns:

`the month-of-year, not null`

See Also:

`getMonthValue()`

getDayOfMonth

```
public int getDayOfMonth()
```

Gets the day-of-month field.

This method returns the primitive `int` value for the day-of-month.

Returns:

`the day-of-month, from 1 to 31`

getDayOfYear

```
public int getDayOfYear()
```

Gets the day-of-year field.

This method returns the primitive `int` value for the day-of-year.

Returns:

`the day-of-year, from 1 to 365, or 366 in a leap year`

getDayOfWeek

```
public DayOfWeek getDayOfWeek()
```

Gets the day-of-week field, which is an enum `DayOfWeek`.

This method returns the enum `DayOfWeek` for the day-of-week. This avoids confusion as to what `int` values mean. If you need access to the primitive `int` value then the enum provides the `int value`.

Additional information can be obtained from the `DayOfWeek`. This includes textual names of the values.

Returns:

`the day-of-week, not null`

toLocalTime

```
public LocalTime toLocalTime()
```

Gets the `LocalTime` part of this date-time.

This returns a `LocalTime` with the same hour, minute, second and nanosecond as this date-time.

Specified by:

`toLocalTime` in interface `ChronoZonedDateTime<LocalDate>`

Returns:

the time part of this date-time, not null

getHour

```
public int getHour()
```

Gets the hour-of-day field.

Returns:

the hour-of-day, from 0 to 23

getMinute

```
public int getMinute()
```

Gets the minute-of-hour field.

Returns:

the minute-of-hour, from 0 to 59

getSecond

```
public int getSecond()
```

Gets the second-of-minute field.

Returns:

the second-of-minute, from 0 to 59

getNano

```
public int getNano()
```

Gets the nano-of-second field.

Returns:

`the nano-of-second, from 0 to 999,999,999`

with

`public ZonedDateTime with(TemporalAdjuster adjuster)`

Returns an adjusted copy of this date-time.

This returns a `ZonedDateTime`, based on this one, with the date-time adjusted. The adjustment takes place using the specified adjuster strategy object. Read the documentation of the adjuster to understand what adjustment will be made.

A simple adjuster might simply set the one of the fields, such as the year field. A more complex adjuster might set the date to the last day of the month. A selection of common adjustments is provided in `TemporalAdjusters`. These include finding the "last day of the month" and "next Wednesday". Key date-time classes also implement the `TemporalAdjuster` interface, such as `Month` and `MonthDay`. The adjuster is responsible for handling special cases, such as the varying lengths of month and leap years.

For example this code returns a date on the last day of July:

```
  import static java.time.Month.*;
  import static java.time.temporal.TemporalAdjusters.*;

  result = zonedDateTime.with(JULY).with(lastDayOfMonth());
```

The classes `LocalDate` and `LocalTime` implement `TemporalAdjuster`, thus this method can be used to change the date, time or offset:

```
  result = zonedDateTime.with(date);
  result = zonedDateTime.with(time);
```

`ZoneOffset` also implements `TemporalAdjuster` however using it as an argument typically has no effect. The offset of a `ZonedDateTime` is controlled primarily by the time-zone. As such, changing the offset does not generally make sense, because there is only one valid offset for the local date-time and zone. If the zoned date-time is in a daylight savings overlap, then the offset is used to switch between the two valid offsets. In all other cases, the offset is ignored.

The result of this method is obtained by invoking the `TemporalAdjuster.adjustInto(Temporal)` method on the specified adjuster passing `this` as the argument.

This instance is immutable and unaffected by this method call.

Specified by:

`with` in interface `ChronoZonedDateTime<LocalDate>`

Specified by:

`with` in interface `Temporal`

Parameters:

`adjuster` - the adjuster to use, not null

Returns:

a ZonedDateTime based on this with the adjustment made, not null

Throws:

`DateTimeException` - if the adjustment cannot be made

`ArithmeticException` - if numeric overflow occurs

with

```
public ZonedDateTime with(TemporalField field,
                          long newValue)
```

Returns a copy of this date-time with the specified field set to a new value.

This returns a `ZonedDateTime`, based on this one, with the value for the specified field changed. This can be used to change any supported field, such as the year, month or day-of-month. If it is not possible to set the value, because the field is not supported or for some other reason, an exception is thrown.

In some cases, changing the specified field can cause the resulting date-time to become invalid, such as changing the month from 31st January to February would make the day-of-month invalid. In cases like this, the field is responsible for resolving the date. Typically it will choose the previous valid date, which would be the last valid day of February in this example.

If the field is a `ChronoField` then the adjustment is implemented here.

The `INSTANT_SECONDS` field will return a date-time with the specified instant. The zone and nano-of-second are unchanged. The result will have an offset derived from the new instant and original zone. If the new instant value is outside the valid range then a `DateTimeException` will be thrown.

The `OFFSET_SECONDS` field will typically be ignored. The offset of a `ZonedDateTime` is controlled primarily by the time-zone. As such, changing the offset does not generally make sense, because there is only one valid offset for the local date-time and zone. If the zoned date-time is in a daylight savings overlap, then the offset is used to switch between the two valid offsets. In all other cases, the offset is ignored. If the new offset value is outside the valid range then a `DateTimeException` will be thrown.

The other supported fields will behave as per the matching method on LocalDateTime. The zone is not part of the calculation and will be unchanged. When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

All other ChronoField instances will throw an UnsupportedTemporalTypeException.

If the field is not a ChronoField, then the result of this method is obtained by invoking TemporalField.adjustInto(Temporal, long) passing this as the argument. In this case, the field determines whether and how to adjust the instant.

This instance is immutable and unaffected by this method call.

Specified by:

with in interface ChronoZonedDateTime<LocalDate>

Specified by:

with in interface Temporal

Parameters:

field - the field to set in the result, not null

newValue - the new value of the field in the result

Returns:

a ZonedDateTime based on this with the specified field set, not null

Throws:

DateTimeException - if the field cannot be set

UnsupportedTemporalTypeException - if the field is not supported

ArithmeticException - if numeric overflow occurs

withYear

public ZonedDateTime withYear(int year)

Returns a copy of this ZonedDateTime with the year altered.

This operates on the local time-line, changing the year of the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier

offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

`year - the year to set in the result, from MIN_YEAR to MAX_YEAR`

Returns:

`a ZonedDateTime based on this date-time with the requested year, not null`

Throws:

`DateTimeException - if the year value is invalid`

withMonth

`public ZonedDateTime withMonth(int month)`

Returns a copy of this `ZonedDateTime` with the month-of-year altered.

This operates on the local time-line, `changing the month` of the local date-time. This is then converted back to a `ZonedDateTime`, using the zone ID to obtain the offset.

When converting back to `ZonedDateTime`, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

`month - the month-of-year to set in the result, from 1 (January) to 12 (December)`

Returns:

`a ZonedDateTime based on this date-time with the requested month, not null`

Throws:

`DateTimeException - if the month-of-year value is invalid`

withDayOfMonth

`public ZonedDateTime withDayOfMonth(int dayOfMonth)`

Returns a copy of this `ZonedDateTime` with the day-of-month altered.

This operates on the local time-line, changing the day-of-month of the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

dayOfMonth - the day-of-month to set in the result, from 1 to 28-31

Returns:

a ZonedDateTime based on this date-time with the requested day, not null

Throws:

DateTimeException - if the day-of-month value is invalid, or if the day-of-month is invalid for the month-year

withDayOfYear

```
public ZonedDateTime withDayOfYear(int dayOfYear)
```

Returns a copy of this ZonedDateTime with the day-of-year altered.

This operates on the local time-line, changing the day-of-year of the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

dayOfYear - the day-of-year to set in the result, from 1 to 365-366

Returns:

a ZonedDateTime based on this date with the requested day, not null

Throws:

DateTimeException - if the day-of-year value is invalid, or if the day-of-year is invalid for the year

withHour

```
public ZonedDateTime withHour(int hour)
```

Returns a copy of this ZonedDateTime with the hour-of-day altered.

This operates on the local time-line, changing the time of the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

hour - the hour-of-day to set in the result, from 0 to 23

Returns:

a ZonedDateTime based on this date-time with the requested hour, not null

Throws:

DateTimeException - if the hour value is invalid

withMinute

public ZonedDateTime withMinute(int minute)

Returns a copy of this ZonedDateTime with the minute-of-hour altered.

This operates on the local time-line, changing the time of the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

minute - the minute-of-hour to set in the result, from 0 to 59

Returns:

a ZonedDateTime based on this date-time with the requested minute, not null

Throws:

DateTimeException - if the minute value is invalid

withSecond

public ZonedDateTime withSecond(int second)

Returns a copy of this ZonedDateTime with the second-of-minute altered.

This operates on the local time-line, changing the time of the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

second - the second-of-minute to set in the result, from 0 to 59

Returns:

a ZonedDateTime based on this date-time with the requested second, not null

Throws:

DateTimeException - if the second value is invalid

withNano

public ZonedDateTime withNano(int nanoOfSecond)

Returns a copy of this ZonedDateTime with the nano-of-second altered.

This operates on the local time-line, changing the time of the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

nanoOfSecond - the nano-of-second to set in the result, from 0 to 999,999,999

Returns:

a ZonedDateTime based on this date-time with the requested nanosecond, not null

Throws:

DateTimeException - if the nano value is invalid

truncatedTo

public ZonedDateTime truncatedTo(TemporalUnit unit)

Returns a copy of this ZonedDateTime with the time truncated.

Truncation returns a copy of the original date-time with fields smaller than the specified unit set to zero. For example, truncating with the minutes unit will set the second-of-minute and nano-of-second field to zero.

The unit must have a duration that divides into the length of a standard day without remainder. This includes all supplied time units on ChronoUnit and DAYS. Other units throw an exception.

This operates on the local time-line, truncating the underlying local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

unit - the unit to truncate to, not null

Returns:

a ZonedDateTime based on this date-time with the time truncated, not null

Throws:

DateTimeException - if unable to truncate

UnsupportedTemporalTypeException - if the unit is not supported

plus

public ZonedDateTime plus(TemporalAmount amountToAdd)

Returns a copy of this date-time with the specified amount added.

This returns a ZonedDateTime, based on this one, with the specified amount added. The amount is typically Period or Duration but may be any other type implementing the TemporalAmount interface.

The calculation is delegated to the amount object by calling TemporalAmount.addTo(Temporal). The amount implementation is free to implement the addition in any way it wishes, however it typically calls back to plus(long, TemporalUnit). Consult the documentation of the amount implementation to determine if it can be successfully added.

This instance is immutable and unaffected by this method call.

Specified by:

plus in interface ChronoZonedDateTime<LocalDate>

Specified by:

plus in interface Temporal

Parameters:

amountToAdd - the amount to add, not null

Returns:

a ZonedDateTime based on this date-time with the addition made, not null

Throws:

DateTimeException - if the addition cannot be made

ArithmeticException - if numeric overflow occurs

plus

```
public ZonedDateTime plus(long amountToAdd,
                          TemporalUnit unit)
```

Returns a copy of this date-time with the specified amount added.

This returns a ZonedDateTime, based on this one, with the amount in terms of the unit added. If it is not possible to add the amount, because the unit is not supported or for some other reason, an exception is thrown.

If the field is a ChronoUnit then the addition is implemented here. The zone is not part of the calculation and will be unchanged in the result. The calculation for date and time units differ.

Date units operate on the local time-line. The period is first added to the local date-time, then converted back to a zoned date-time using the zone ID. The conversion uses ofLocal(LocalDateTime, ZoneId, ZoneOffset) with the offset before the addition.

Time units operate on the instant time-line. The period is first added to the local date-time, then converted back to a zoned date-time using the zone ID. The conversion uses ofInstant(LocalDateTime, ZoneOffset, ZoneId) with the offset before the addition.

If the field is not a ChronoUnit, then the result of this method is obtained by invoking TemporalUnit.addTo(Temporal, long) passing this as the argument. In this case, the unit determines whether and how to perform the addition.

This instance is immutable and unaffected by this method call.

Specified by:

plus in interface ChronoZonedDateTime<LocalDate>

Specified by:

plus in interface Temporal

Parameters:

amountToAdd - the amount of the unit to add to the result, may be negative

unit - the unit of the amount to add, not null

Returns:

a ZonedDateTime based on this date-time with the specified amount added, not null

Throws:

DateTimeException - if the addition cannot be made

UnsupportedTemporalTypeException - if the unit is not supported

ArithmeticException - if numeric overflow occurs

plusYears

public ZonedDateTime plusYears(long years)

Returns a copy of this ZonedDateTime with the specified number of years added.

This operates on the local time-line, adding years to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

years - the years to add, may be negative

Returns:

a ZonedDateTime based on this date-time with the years added, not null

Throws:

DateTimeException - if the result exceeds the supported date range

plusMonths

public ZonedDateTime plusMonths(long months)

Returns a copy of this ZonedDateTime with the specified number of months added.

This operates on the local time-line, adding months to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

months - the months to add, may be negative

Returns:

a ZonedDateTime based on this date-time with the months added, not null

Throws:

DateTimeException - if the result exceeds the supported date range

plusWeeks

```
public ZonedDateTime plusWeeks(long weeks)
```

Returns a copy of this ZonedDateTime with the specified number of weeks added.

This operates on the local time-line, adding weeks to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

weeks - the weeks to add, may be negative

Returns:

a ZonedDateTime based on this date-time with the weeks added, not null

Throws:

DateTimeException - if the result exceeds the supported date range

plusDays

```
public ZonedDateTime plusDays(long days)
```

Returns a copy of this ZonedDateTime with the specified number of days added.

This operates on the local time-line, adding days to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

days - the days to add, may be negative

Returns:

a ZonedDateTime based on this date-time with the days added, not null

Throws:

DateTimeException - if the result exceeds the supported date range

plusHours

```
public ZonedDateTime plusHours(long hours)
```

Returns a copy of this ZonedDateTime with the specified number of hours added.

This operates on the instant time-line, such that adding one hour will always be a duration of one hour later. This may cause the local date-time to change by an amount other than one hour. Note that this is a different approach to that used by days, months and years, thus adding one day is not the same as adding 24 hours.

For example, consider a time-zone where the spring DST cutover means that the local times 01:00 to 01:59 occur twice changing from offset +02:00 to +01:00.

- Adding one hour to 00:30+02:00 will result in 01:30+02:00
- Adding one hour to 01:30+02:00 will result in 01:30+01:00
- Adding one hour to 01:30+01:00 will result in 02:30+01:00
- Adding three hours to 00:30+02:00 will result in 02:30+01:00

This instance is immutable and unaffected by this method call.

Parameters:

`hours - the hours to add, may be negative`

Returns:

`a ZonedDateTime based on this date-time with the hours added, not null`

Throws:

`DateTimeException - if the result exceeds the supported date range`

plusMinutes

```
public ZonedDateTime plusMinutes(long minutes)
```

Returns a copy of this `ZonedDateTime` with the specified number of minutes added.

This operates on the instant time-line, such that adding one minute will always be a duration of one minute later. This may cause the local date-time to change by an amount other than one minute. Note that this is a different approach to that used by days, months and years.

This instance is immutable and unaffected by this method call.

Parameters:

`minutes - the minutes to add, may be negative`

Returns:

`a ZonedDateTime based on this date-time with the minutes added, not null`

Throws:

`DateTimeException - if the result exceeds the supported date range`

plusSeconds

```
public ZonedDateTime plusSeconds(long seconds)
```

Returns a copy of this `ZonedDateTime` with the specified number of seconds added.

This operates on the instant time-line, such that adding one second will always be a duration of one second later. This may cause the local date-time to change by an amount other than one second. Note that this is a different approach to that used by days, months and years.

This instance is immutable and unaffected by this method call.

Parameters:

`seconds - the seconds to add, may be negative`

Returns:

`a ZonedDateTime based on this date-time with the seconds added, not null`

Throws:

`DateTimeException - if the result exceeds the supported date range`

plusNanos

`public ZonedDateTime plusNanos(long nanos)`

Returns a copy of this `ZonedDateTime` with the specified number of nanoseconds added.

This operates on the instant time-line, such that adding one nano will always be a duration of one nano later. This may cause the local date-time to change by an amount other than one nano. Note that this is a different approach to that used by days, months and years.

This instance is immutable and unaffected by this method call.

Parameters:

`nanos - the nanos to add, may be negative`

Returns:

`a ZonedDateTime based on this date-time with the nanoseconds added, not null`

Throws:

`DateTimeException - if the result exceeds the supported date range`

minus

`public ZonedDateTime minus(TemporalAmount amountToSubtract)`

Returns a copy of this date-time with the specified amount subtracted.

This returns a `ZonedDateTime`, based on this one, with the specified amount subtracted. The amount is typically `Period` or `Duration` but may be any other type implementing the `TemporalAmount` interface.

The calculation is delegated to the amount object by calling `TemporalAmount.subtractFrom(Temporal)`. The amount implementation is free to implement the subtraction in any way it wishes, however it typically calls back to `minus(long, TemporalUnit)`. Consult the documentation of the amount implementation to determine if it can be successfully subtracted.

This instance is immutable and unaffected by this method call.

Specified by:

`minus` in interface `ChronoZonedDateTime<LocalDate>`

Specified by:

`minus` in interface `Temporal`

Parameters:

`amountToSubtract` - the amount to subtract, not null

Returns:

a ZonedDateTime based on this date-time with the subtraction made, not null

Throws:

`DateTimeException` - if the subtraction cannot be made

`ArithmeticException` - if numeric overflow occurs

minus

```
public ZonedDateTime minus(long amountToSubtract,
                           TemporalUnit unit)
```

Returns a copy of this date-time with the specified amount subtracted.

This returns a ZonedDateTime, based on this one, with the amount in terms of the unit subtracted. If it is not possible to subtract the amount, because the unit is not supported or for some other reason, an exception is thrown.

The calculation for date and time units differ.

Date units operate on the local time-line. The period is first subtracted from the local date-time, then converted back to a zoned date-time using the zone ID. The conversion uses `ofLocal(LocalDateTime, ZoneId, ZoneOffset)` with the offset before the subtraction.

Time units operate on the instant time-line. The period is first subtracted from the local date-time, then converted back to a zoned date-time using the zone ID. The conversion uses `ofInstant(LocalDateTime, ZoneOffset, ZoneId)` with the offset before the subtraction.

This method is equivalent to `plus(long, TemporalUnit)` with the amount negated. See that method for a full description of how addition, and thus subtraction, works.

This instance is immutable and unaffected by this method call.

Specified by:

`minus` in interface `ChronoZonedDateTime<LocalDate>`

Specified by:

minus in interface Temporal

Parameters:

amountToSubtract - the amount of the unit to subtract from the result, may be negative

unit - the unit of the amount to subtract, not null

Returns:

a ZonedDateTime based on this date-time with the specified amount subtracted, not null

Throws:

DateTimeException - if the subtraction cannot be made

UnsupportedTemporalTypeException - if the unit is not supported

ArithmeticException - if numeric overflow occurs

minusYears

public ZonedDateTime minusYears(long years)

Returns a copy of this ZonedDateTime with the specified number of years subtracted.

This operates on the local time-line, subtracting years to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

years - the years to subtract, may be negative

Returns:

a ZonedDateTime based on this date-time with the years subtracted, not null

Throws:

DateTimeException - if the result exceeds the supported date range

minusMonths

public ZonedDateTime minusMonths(long months)

Returns a copy of this ZonedDateTime with the specified number of months subtracted.

This operates on the local time-line, subtracting months to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

months - the months to subtract, may be negative

Returns:

a ZonedDateTime based on this date-time with the months subtracted, not null

Throws:

DateTimeException - if the result exceeds the supported date range

minusWeeks

```
public ZonedDateTime minusWeeks(long weeks)
```

Returns a copy of this ZonedDateTime with the specified number of weeks subtracted.

This operates on the local time-line, subtracting weeks to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

weeks - the weeks to subtract, may be negative

Returns:

a ZonedDateTime based on this date-time with the weeks subtracted, not null

Throws:

DateTimeException - if the result exceeds the supported date range

minusDays

```
public ZonedDateTime minusDays(long days)
```

Returns a copy of this ZonedDateTime with the specified number of days subtracted.

This operates on the local time-line, subtracting days to the local date-time. This is then converted back to a ZonedDateTime, using the zone ID to obtain the offset.

When converting back to ZonedDateTime, if the local date-time is in an overlap, then the offset will be retained if possible, otherwise the earlier offset will be used. If in a gap, the local date-time will be adjusted forward by the length of the gap.

This instance is immutable and unaffected by this method call.

Parameters:

days - the days to subtract, may be negative

Returns:

a ZonedDateTime based on this date-time with the days subtracted, not null

Throws:

DateTimeException - if the result exceeds the supported date range

minusHours

```
public ZonedDateTime minusHours(long hours)
```

Returns a copy of this ZonedDateTime with the specified number of hours subtracted.

This operates on the instant time-line, such that subtracting one hour will always be a duration of one hour earlier. This may cause the local date-time to change by an amount other than one hour. Note that this is a different approach to that used by days, months and years, thus subtracting one day is not the same as adding 24 hours.

For example, consider a time-zone where the spring DST cutover means that the local times 01:00 to 01:59 occur twice changing from offset +02:00 to +01:00.

- Subtracting one hour from 02:30+01:00 will result in 01:30+02:00
- Subtracting one hour from 01:30+01:00 will result in 01:30+02:00
- Subtracting one hour from 01:30+02:00 will result in 00:30+01:00
- Subtracting three hours from 02:30+01:00 will result in 00:30+02:00

This instance is immutable and unaffected by this method call.

Parameters:

hours - the hours to subtract, may be negative

Returns:

a ZonedDateTime based on this date-time with the hours subtracted, not null

Throws:

DateTimeException - if the result exceeds the supported date range

minusMinutes

```
public ZonedDateTime minusMinutes(long minutes)
```

Returns a copy of this ZonedDateTime with the specified number of minutes subtracted.

This operates on the instant time-line, such that subtracting one minute will always be a duration of one minute earlier. This may cause the local date-

time to change by an amount other than one minute. Note that this is a different approach to that used by days, months and years.

This instance is immutable and unaffected by this method call.

Parameters:

`minutes - the minutes to subtract, may be negative`

Returns:

`a ZonedDateTime based on this date-time with the minutes subtracted, not null`

Throws:

`DateTimeException - if the result exceeds the supported date range`

minusSeconds

```
public ZonedDateTime minusSeconds(long seconds)
```

Returns a copy of this `ZonedDateTime` with the specified number of seconds subtracted.

This operates on the instant time-line, such that subtracting one second will always be a duration of one second earlier. This may cause the local date-time to change by an amount other than one second. Note that this is a different approach to that used by days, months and years.

This instance is immutable and unaffected by this method call.

Parameters:

`seconds - the seconds to subtract, may be negative`

Returns:

`a ZonedDateTime based on this date-time with the seconds subtracted, not null`

Throws:

`DateTimeException - if the result exceeds the supported date range`

minusNanos

```
public ZonedDateTime minusNanos(long nanos)
```

Returns a copy of this `ZonedDateTime` with the specified number of nanoseconds subtracted.

This operates on the instant time-line, such that subtracting one nano will always be a duration of one nano earlier. This may cause the local date-time to change by an amount other than one nano. Note that this is a different approach to that used by days, months and years.

This instance is immutable and unaffected by this method call.

Parameters:

`nanos - the nanos to subtract, may be negative`

Returns:

`a ZonedDateTime based on this date-time with the nanoseconds subtracted, not null`

Throws:

`DateTimeException - if the result exceeds the supported date range`

query

```
public <R> R query(TemporalQuery<R> query)
```

Queries this date-time using the specified query.

This queries this date-time using the specified query strategy object. The `TemporalQuery` object defines the logic to be used to obtain the result. Read the documentation of the query to understand what the result of this method will be.

The result of this method is obtained by invoking the `TemporalQuery.queryFrom(TemporalAccessor)` method on the specified query passing `this` as the argument.

Specified by:

`query in interface ChronoZonedDateTime<LocalDate>`

Specified by:

`query in interface TemporalAccessor`

Type Parameters:

`R - the type of the result`

Parameters:

`query - the query to invoke, not null`

Returns:

`the query result, null may be returned (defined by the query)`

Throws:

`DateTimeException - if unable to query (defined by the query)`

`ArithmeticException - if numeric overflow occurs (defined by the query)`

until

```
public long until(Temporal endExclusive,
                  TemporalUnit unit)
```

Calculates the amount of time until another date-time in terms of the specified unit.

This calculates the amount of time between two `ZonedDateTime` objects in terms of a single `TemporalUnit`. The start and end points are `this` and the specified date-time. The result will be negative if the end is before the start. For example, the amount in days between two date-times can be calculated using `startDateTime.until(endDateTime, DAYS)`.

The `Temporal` passed to this method is converted to a `ZonedDateTime` using `from(TemporalAccessor)`. If the time-zone differs between the two zoned date-times, the specified end date-time is normalized to have the same zone as this date-time.

The calculation returns a whole number, representing the number of complete units between the two date-times. For example, the amount in months between 2012-06-15T00:00Z and 2012-08-14T23:59Z will only be one month as it is one minute short of two months.

There are two equivalent ways of using this method. The first is to invoke this method. The second is to use `TemporalUnit.between(Temporal, Temporal)`:

```
// these two lines are equivalent
amount = start.until(end, MONTHS);
amount = MONTHS.between(start, end);
```

The choice should be made based on which makes the code more readable.

The calculation is implemented in this method for `ChronoUnit`. The units `NANOS`, `MICROS`, `MILLIS`, `SECONDS`, `MINUTES`, `HOURS` and `HALF_DAYS`, `DAYS`, `WEEKS`, `MONTHS`, `YEARS`, `DECADES`, `CENTURIES`, `MILLENNIA` and `ERAS` are supported. Other `ChronoUnit` values will throw an exception.

The calculation for date and time units differ.

Date units operate on the local time-line, using the local date-time. For example, the period from noon on day 1 to noon the following day in days will always be counted as exactly one day, irrespective of whether there was a daylight savings change or not.

Time units operate on the instant time-line. The calculation effectively converts both zoned date-times to instants and then calculates the period between the instants. For example, the period from noon on day 1 to noon

the following day in hours may be 23, 24 or 25 hours (or some other amount) depending on whether there was a daylight savings change or not.

If the unit is not a `ChronoUnit`, then the result of this method is obtained by invoking `TemporalUnit.between(Temporal, Temporal)` passing `this` as the first argument and the converted input temporal as the second argument.

This instance is immutable and unaffected by this method call.

Specified by:

`until` in interface `Temporal`

Parameters:

`endExclusive - the end date, exclusive, which is converted to a ZonedDateTime, not null`

`unit - the unit to measure the amount in, not null`

Returns:

`the amount of time between this date-time and the end date-time`

Throws:

`DateTimeException - if the amount cannot be calculated, or the end temporal cannot be converted to a ZonedDateTime`

`UnsupportedTemporalTypeException - if the unit is not supported`

`ArithmeticException - if numeric overflow occurs`

format

```
public String format(DateTimeFormatter formatter)
```

Formats this date-time using the specified formatter.

This date-time will be passed to the formatter to produce a string.

Specified by:

`format` in interface `ChronoZonedDateTime<LocalDate>`

Parameters:

`formatter - the formatter to use, not null`

Returns:

`the formatted date-time string, not null`

Throws:

`DateTimeException - if an error occurs during printing`

toOffsetDateTime

```
public OffsetDateTime toOffsetDateTime()
```

Converts this date-time to an `OffsetDateTime`.

This creates an offset date-time using the local date-time and offset. The zone ID is ignored.

Returns:

an offset date-time representing the same local date-time and offset, not null

equals

```
public boolean equals(Object obj)
```

Checks if this date-time is equal to another date-time.

The comparison is based on the offset date-time and the zone. Only objects of type `ZonedDateTime` are compared, other types return false.

Specified by:

`equals` in interface `ChronoZonedDateTime<LocalDate>`

Overrides:

`equals` in class `Object`

Parameters:

obj - the object to check, null returns false

Returns:

true if this is equal to the other date-time

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

A hash code for this date-time.

Specified by:

`hashCode` in interface `ChronoZonedDateTime<LocalDate>`

Overrides:

`hashCode` in class `Object`

Returns:

a suitable hash code

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

toString

```
public String toString()
```

Outputs this date-time as a `String`, such as `2007-12-03T10:15:30+01:00[Europe/Paris]`.

The format consists of the `LocalDateTime` followed by the `ZoneOffset`. If the `ZoneId` is not the same as the offset, then the ID is output. The output is compatible with ISO-8601 if the offset and ID are the same.

Specified by:

`toString` in interface `ChronoZonedDateTime<LocalDate>`

Overrides:

`toString` in class `Object`

Returns:

a string representation of this date-time, not null

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.