JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time.format

Class DateTimeParseException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.time.DateTimeException
          java.time.format.DateTimeParseException

All Implemented Interfaces:

Serializable

```
public class DateTimeParseException
extends DateTimeException
```

An exception thrown when an error occurs during parsing.

This exception includes the text being parsed and the error index.

Implementation Requirements:

This class is intended for use in a single thread.

Since:

1.8

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor
`DateTimeParseException(String message, CharSequence parsedData, int errorIndex)`

```
DateTimeParseException(String message, CharSequence parsedData, int errorIndex, T
```

Method Summary

Concrete Methods

Modifier and Type	Method	Description
int	getErrorIndex()	Returns the index where the error was found.
String	getParsedString()	Returns the string that was being parsed.

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

DateTimeParseException

```
public DateTimeParseException(String message,
                              CharSequence parsedData,
                              int errorIndex)
```

Constructs a new exception with the specified message.

Parameters:

`message` - the message to use for this exception, may be null

`parsedData` - the parsed text, should not be null

`errorIndex` - the index in the parsed string that was invalid, should be a valid index

DateTimeParseException

```
public DateTimeParseException(String message,
                              CharSequence parsedData,
                              int errorIndex,
                              Throwable cause)
```

Constructs a new exception with the specified message and cause.

Parameters:

`message` - the message to use for this exception, may be null

`parsedData` - the parsed text, should not be null

`errorIndex` - the index in the parsed string that was invalid, should be a valid index

`cause` - the cause exception, may be null

Method Detail

getParsedString

```
public String getParsedString()
```

Returns the string that was being parsed.

Returns:

`the string that was being parsed, should not be null.`

getErrorIndex

```
public int getErrorIndex()
```

Returns the index where the error was found.

Returns:

`the index in the parsed string that was invalid, should be a valid index`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.