JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Interface PrimitiveIterator<T,T_CONS>

Type Parameters:

`T` - the type of elements returned by this `PrimitiveIterator`. The type must be a wrapper type for a primitive type, such as `Integer` for the primitive `int` type.

`T_CONS` - the type of primitive consumer. The type must be a primitive specialization of `Consumer` for `T`, such as `IntConsumer` for `Integer`.

All Superinterfaces:

`Iterator`<T>

All Known Subinterfaces:

`PrimitiveIterator.OfDouble`, `PrimitiveIterator.OfInt`, `PrimitiveIterator.OfLong`

```
public interface PrimitiveIterator<T,T_CONS>
extends Iterator<T>
```

A base type for primitive specializations of `Iterator`. Specialized subtypes are provided for `int`, `long`, and `double` values.

The specialized subtype default implementations of `Iterator.next()` and `Iterator.forEachRemaining(java.util.function.Consumer)` box primitive values to instances of their corresponding wrapper class. Such boxing may offset any advantages gained when using the primitive specializations. To avoid boxing, the corresponding primitive-based methods should be used. For example, `PrimitiveIterator.OfInt.nextInt()` and `PrimitiveIterator.OfInt.forEachRemaining(java.util.function.IntConsumer)` should be used in preference to `PrimitiveIterator.OfInt.next()` and `PrimitiveIterator.OfInt.forEachRemaining(java.util.function.Consumer)`.

Iteration of primitive values using boxing-based methods `next()` and `forEachRemaining()`, does not affect the order in which the values, transformed to boxed values, are encountered.

Implementation Note:

`If the boolean system property org.openjdk.java.util.stream.tripwire is set to true then diagnostic warnings are reported if boxing of primitive values occur when operating on primitive subtype specializations.`

Since:

`1.8`

Nested Class Summary

Nested Classes

Modifier and Type	Interface	Description
`static interface`	**`PrimitiveIterator.OfDouble`**	An Iterator specialized for `double` values.
`static interface`	**`PrimitiveIterator.OfInt`**	An Iterator specialized for `int` values.
`static interface`	**`PrimitiveIterator.OfLong`**	An Iterator specialized for `long` values.

Method Summary

Abstract Methods

Modifier and Type	Method	Description
`void`	**`forEachRemaining`**`(`**`T_CONS`** `action)`	Performs the given action for each remaining element, in the order elements occur when iterating, until all elements have been processed or the action

		throws an exception.

Methods inherited from interface java.util.Iterator

forEachRemaining, hasNext, next, remove

Method Detail

forEachRemaining

```
void forEachRemaining(T_CONS action)
```

Performs the given action for each remaining element, in the order elements occur when iterating, until all elements have been processed or the action throws an exception. Errors or runtime exceptions thrown by the action are relayed to the caller.

Parameters:

`action - The action to be performed for each element`

Throws:

`NullPointerException - if the specified action is null`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.