JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class TimeZone

java.lang.Object
    java.util.TimeZone

All Implemented Interfaces:

`Serializable, Cloneable`

Direct Known Subclasses:

`SimpleTimeZone`

```
public abstract class TimeZone
extends Object
implements Serializable, Cloneable
```

`TimeZone` represents a time zone offset, and also figures out daylight savings.

Typically, you get a `TimeZone` using `getDefault` which creates a `TimeZone` based on the time zone where the program is running. For example, for a program running in Japan, `getDefault` creates a `TimeZone` object based on Japanese Standard Time.

You can also get a `TimeZone` using `getTimeZone` along with a time zone ID. For instance, the time zone ID for the U.S. Pacific Time zone is "America/Los_Angeles". So, you can get a U.S. Pacific Time `TimeZone` object with:

```
TimeZone tz = TimeZone.getTimeZone("America/Los_Angeles");
```

You can use the `getAvailableIDs` method to iterate through all the supported time zone IDs. You can then choose a supported ID to get a `TimeZone`. If the time zone you want is not represented by one of the supported IDs, then a custom time zone ID
can be specified to produce a TimeZone. The syntax of a custom time zone ID is:

```
CustomID:
        GMT Sign Hours : Minutes
        GMT Sign Hours Minutes
        GMT Sign Hours
Sign: one of
        + -
Hours:
        Digit
        Digit Digit
Minutes:
        Digit Digit
Digit: one of
        0 1 2 3 4 5 6 7 8 9
```

Hours must be between 0 to 23 and *Minutes* must be between 00 to 59. For example, "GMT+10" and "GMT+0010" mean ten hours and ten minutes ahead of GMT, respectively.

The format is locale independent and digits must be taken from the Basic Latin block of the Unicode standard. No daylight saving time transition schedule can be specified with a custom time zone ID. If the specified string doesn't match the syntax, `"GMT"` is used.

When creating a `TimeZone`, the specified custom time zone ID is normalized in the following syntax:

```
NormalizedCustomID:
        GMT Sign TwoDigitHours : Minutes
Sign: one of
        + -
TwoDigitHours:
        Digit Digit
Minutes:
        Digit Digit
Digit: one of
        0 1 2 3 4 5 6 7 8 9
```

For example, TimeZone.getTimeZone("GMT-8").getID() returns "GMT-08:00".

Three-letter time zone IDs

For compatibility with JDK 1.1.x, some other three-letter time zone IDs (such as "PST", "CTT", "AST") are also supported. However, **their use is deprecated** because the same abbreviation is often used for multiple time zones (for example, "CST" could be U.S. "Central Standard Time" and "China Standard Time"), and the Java platform can then only recognize one of them.

Since:

`JDK1.1`

See Also:

Calendar, GregorianCalendar, SimpleTimeZone, Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
static int	LONG	A style specifier for getDisplayName() indicating a long name, such as "Pacific Standard Time."
static int	SHORT	A style specifier for getDisplayName() indicating a short name, such as "PST."

Constructor Summary

Constructors

Constructor	Description
TimeZone()	Sole constructor.

Method Summary

Instance Methods | **Abstract Methods** | **Concrete Methods**

Modifier and Type	Method	Description
Object	clone()	Creates a copy of this TimeZone.
static String[]	getAvailableIDs()	Gets all the available IDs supported.
static String[]	getAvailableIDs(int rawOffset)	Gets the available IDs according to the given time zone

		offset in milliseconds.
static **TimeZone**	**getDefault**()	Gets the default `TimeZone` of the Java virtual machine.
String	**getDisplayName**()	Returns a long standard time name of this `TimeZone` suitable for presentation to the user in the default locale.
String	**getDisplayName**(boolean daylight, int style)	Returns a name in the specified `style` of this `TimeZone` suitable for presentation to the user in the default locale.
String	**getDisplayName**(boolean daylight, int style, **Locale** locale)	Returns a name in the specified `style` of this `TimeZone` suitable for presentation to the user in the specified `locale`.
String	**getDisplayName**(**Locale** locale)	Returns a long standard time name of this `TimeZone` suitable for presentation to the user in the specified `locale`.
int	**getDSTSavings**()	Returns the amount of time to be added to

		local standard time to get local wall clock time.
String	**getID**()	Gets the ID of this time zone.
abstract int	**getOffset**(int era, int year, int month, int day, int dayOfWeek, int milliseconds)	Gets the time zone offset, for current date, modified in case of daylight savings.
int	**getOffset**(long date)	Returns the offset of this time zone from UTC at the specified date.
abstract int	**getRawOffset**()	Returns the amount of time in milliseconds to add to UTC to get standard time in this time zone.
static **TimeZone**	**getTimeZone**(**String** ID)	Gets the TimeZone for the given ID.
static **TimeZone**	**getTimeZone**(**ZoneId** zoneId)	Gets the TimeZone for the given zoneId.
boolean	**hasSameRules**(**TimeZone** other)	Returns true if this zone has the same rule and offset as another zone.
abstract boolean	**inDaylightTime**(**Date** date)	Queries if the given date is in Daylight Saving Time in this time zone.
boolean	**observesDaylightTime**()	

		Returns `true` if this `TimeZone` is currently in Daylight Saving Time, or if a transition from Standard Time to Daylight Saving Time occurs at any future time.
static void	**setDefault**(**TimeZone** zone)	Sets the `TimeZone` that is returned by the `getDefault` method.
void	**setID**(**String** ID)	Sets the time zone ID.
abstract void	**setRawOffset**(int offsetMillis)	Sets the base time zone offset to GMT.
ZoneId	**toZoneId**()	Converts this `TimeZone` object to a `ZoneId`.
abstract boolean	**useDaylightTime**()	Queries if this `TimeZone` uses Daylight Saving Time.

Methods inherited from class java.lang.Object

equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

SHORT

```
public static final int SHORT
```

A style specifier for `getDisplayName()` indicating a short name, such as "PST."

Since:

1.2

See Also:

LONG, Constant Field Values

LONG

```
public static final int LONG
```

A style specifier for `getDisplayName()` indicating a long name, such as "Pacific Standard Time."

Since:

1.2

See Also:

SHORT, Constant Field Values

Constructor Detail

TimeZone

```
public TimeZone()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

getOffset

```
public abstract int getOffset(int era,
                              int year,
                              int month,
                              int day,
                              int dayOfWeek,
                              int milliseconds)
```

Gets the time zone offset, for current date, modified in case of daylight savings. This is the offset to add to UTC to get local time.

This method returns a historically correct offset if an underlying TimeZone implementation subclass supports historical Daylight Saving Time schedule and GMT offset changes.

Parameters:

era - the era of the given date.

year - the year in the given date.

month - the month in the given date. Month is 0-based. e.g., 0 for January.

day - the day-in-month of the given date.

dayOfWeek - the day-of-week of the given date.

milliseconds - the milliseconds in day in *standard* local time.

Returns:

the offset in milliseconds to add to GMT to get local time.

See Also:

Calendar.ZONE_OFFSET, Calendar.DST_OFFSET

getOffset

public int getOffset(long date)

Returns the offset of this time zone from UTC at the specified date. If Daylight Saving Time is in effect at the specified date, the offset value is adjusted with the amount of daylight saving.

This method returns a historically correct offset value if an underlying TimeZone implementation subclass supports historical Daylight Saving Time schedule and GMT offset changes.

Parameters:

date - the date represented in milliseconds since January 1, 1970 00:00:00 GMT

Returns:

the amount of time in milliseconds to add to UTC to get local time.

Since:

1.4

See Also:

Calendar.ZONE_OFFSET, Calendar.DST_OFFSET

setRawOffset

```
public abstract void setRawOffset(int offsetMillis)
```

Sets the base time zone offset to GMT. This is the offset to add to UTC to get local time.

If an underlying `TimeZone` implementation subclass supports historical GMT offset changes, the specified GMT offset is set as the latest GMT offset and the difference from the known latest GMT offset value is used to adjust all historical GMT offset values.

Parameters:

`offsetMillis - the given base time zone offset to GMT.`

getRawOffset

```
public abstract int getRawOffset()
```

Returns the amount of time in milliseconds to add to UTC to get standard time in this time zone. Because this value is not affected by daylight saving time, it is called *raw offset*.

If an underlying `TimeZone` implementation subclass supports historical GMT offset changes, the method returns the raw offset value of the current date. In Honolulu, for example, its raw offset changed from GMT-10:30 to GMT-10:00 in 1947, and this method always returns -36000000 milliseconds (i.e., -10 hours).

Returns:

`the amount of raw offset time in milliseconds to add to UTC.`

See Also:

`Calendar.ZONE_OFFSET`

getID

```
public String getID()
```

Gets the ID of this time zone.

Returns:

`the ID of this time zone.`

setID

```
public void setID(String ID)
```

Sets the time zone ID. This does not change any other data in the time zone object.

Parameters:

`ID - the new time zone ID.`

getDisplayName

```
public final String getDisplayName()
```

Returns a long standard time name of this `TimeZone` suitable for presentation to the user in the default locale.

This method is equivalent to:

```
getDisplayName(false, LONG,
               Locale.getDefault(Locale.Category.DISPLAY))
```

Returns:

`the human-readable name of this time zone in the default locale.`

Since:

`1.2`

See Also:

`getDisplayName(boolean, int, Locale)`, `Locale.getDefault(Locale.Category)`, `Locale.Category`

getDisplayName

```
public final String getDisplayName(Locale locale)
```

Returns a long standard time name of this `TimeZone` suitable for presentation to the user in the specified `locale`.

This method is equivalent to:

```
getDisplayName(false, LONG, locale)
```

Parameters:

`locale - the locale in which to supply the display name.`

Returns:

the human-readable name of this time zone in the given locale.

Throws:

NullPointerException - if locale is null.

Since:

1.2

See Also:

getDisplayName(boolean, int, Locale)

getDisplayName

```
public final String getDisplayName(boolean daylight,
                                   int style)
```

Returns a name in the specified style of this TimeZone suitable for presentation to the user in the default locale. If the specified daylight is true, a Daylight Saving Time name is returned (even if this TimeZone doesn't observe Daylight Saving Time). Otherwise, a Standard Time name is returned.

This method is equivalent to:

```
getDisplayName(daylight, style,
               Locale.getDefault(Locale.Category.DISPLAY))
```

Parameters:

daylight - true specifying a Daylight Saving Time name, or false specifying a Standard Time name

style - either LONG or SHORT

Returns:

the human-readable name of this time zone in the default locale.

Throws:

IllegalArgumentException - if style is invalid.

Since:

1.2

See Also:

getDisplayName(boolean, int, Locale), Locale.getDefault(Locale.Category), Locale.Category, DateFormatSymbols.getZoneStrings()

getDisplayName

```
public String getDisplayName(boolean daylight,
                             int style,
                             Locale locale)
```

Returns a name in the specified `style` of this `TimeZone` suitable for presentation to the user in the specified `locale`. If the specified `daylight` is `true`, a Daylight Saving Time name is returned (even if this `TimeZone` doesn't observe Daylight Saving Time). Otherwise, a Standard Time name is returned.

When looking up a time zone name, the default `Locale` search path of `ResourceBundle` derived from the specified `locale` is used. (No fallback `Locale` search is performed.) If a time zone name in any `Locale` of the search path, including `Locale.ROOT`, is found, the name is returned. Otherwise, a string in the normalized custom ID format is returned.

Parameters:

`daylight - true specifying a Daylight Saving Time name, or false specifying a Standard Time name`

`style - either LONG or SHORT`

`locale - the locale in which to supply the display name.`

Returns:

`the human-readable name of this time zone in the given locale.`

Throws:

`IllegalArgumentException - if style is invalid.`

`NullPointerException - if locale is null.`

Since:

`1.2`

See Also:

`DateFormatSymbols.getZoneStrings()`

getDSTSavings

```
public int getDSTSavings()
```

Returns the amount of time to be added to local standard time to get local wall clock time.

The default implementation returns 3600000 milliseconds (i.e., one hour) if a call to `useDaylightTime()` returns `true`. Otherwise, 0 (zero) is returned.

If an underlying TimeZone implementation subclass supports historical and future Daylight Saving Time schedule changes, this method returns the amount of saving time of the last known Daylight Saving Time rule that can be a future prediction.

If the amount of saving time at any given time stamp is required, construct a Calendar with this TimeZone and the time stamp, and call Calendar.get(Calendar.DST_OFFSET).

Returns:

the amount of saving time in milliseconds

Since:

1.4

See Also:

inDaylightTime(Date), getOffset(long), getOffset(int,int,int,int,int,int), Calendar.ZONE_OFFSET

useDaylightTime

```
public abstract boolean useDaylightTime()
```

Queries if this TimeZone uses Daylight Saving Time.

If an underlying TimeZone implementation subclass supports historical and future Daylight Saving Time schedule changes, this method refers to the last known Daylight Saving Time rule that can be a future prediction and may not be the same as the current rule. Consider calling observesDaylightTime() if the current rule should also be taken into account.

Returns:

true if this TimeZone uses Daylight Saving Time, false, otherwise.

See Also:

inDaylightTime(Date), Calendar.DST_OFFSET

observesDaylightTime

```
public boolean observesDaylightTime()
```

Returns true if this TimeZone is currently in Daylight Saving Time, or if a transition from Standard Time to Daylight Saving Time occurs at any future time.

The default implementation returns true if useDaylightTime() or inDaylightTime(new Date()) returns true.

Returns:

true if this TimeZone is currently in Daylight Saving Time, or if a transition from Standard Time to Daylight Saving Time occurs at any future time; false otherwise.

Since:

1.7

See Also:

useDaylightTime(), inDaylightTime(Date), Calendar.DST_OFFSET

inDaylightTime

```
public abstract boolean inDaylightTime(Date date)
```

Queries if the given date is in Daylight Saving Time in this time zone.

Parameters:

date - the given Date.

Returns:

true if the given date is in Daylight Saving Time, false, otherwise.

getTimeZone

```
public static TimeZone getTimeZone(String ID)
```

Gets the TimeZone for the given ID.

Parameters:

ID - the ID for a TimeZone, either an abbreviation such as "PST", a full name such as "America/Los_Angeles", or a custom ID such as "GMT-8:00". Note that the support of abbreviations is for JDK 1.1.x compatibility only and full names should be used.

Returns:

the specified TimeZone, or the GMT zone if the given ID cannot be understood.

getTimeZone

```
public static TimeZone getTimeZone(ZoneId zoneId)
```

Gets the TimeZone for the given zoneId.

Parameters:

zoneId - a ZoneId from which the time zone ID is obtained

Returns:

the specified TimeZone, or the GMT zone if the given ID cannot be understood.

Throws:

NullPointerException - if zoneId is null

Since:

1.8

toZoneId

public ZoneId toZoneId()

Converts this TimeZone object to a ZoneId.

Returns:

a ZoneId representing the same time zone as this TimeZone

Since:

1.8

getAvailableIDs

public static String[] getAvailableIDs(int rawOffset)

Gets the available IDs according to the given time zone offset in milliseconds.

Parameters:

rawOffset - the given time zone GMT offset in milliseconds.

Returns:

an array of IDs, where the time zone for that ID has the specified GMT offset. For example, "America/Phoenix" and "America/Denver" both have GMT-07:00, but differ in daylight saving behavior.

See Also:

getRawOffset()

getAvailableIDs

public static String[] getAvailableIDs()

Gets all the available IDs supported.

Returns:

an array of IDs.

getDefault

```
public static TimeZone getDefault()
```

Gets the default `TimeZone` of the Java virtual machine. If the cached default `TimeZone` is available, its clone is returned. Otherwise, the method takes the following steps to determine the default time zone.

- Use the `user.timezone` property value as the default time zone ID if it's available.
- Detect the platform time zone ID. The source of the platform time zone and ID mapping may vary with implementation.
- Use `GMT` as the last resort if the given or detected time zone ID is unknown.

The default `TimeZone` created from the ID is cached, and its clone is returned. The `user.timezone` property value is set to the ID upon return.

Returns:

`the default TimeZone`

See Also:

`setDefault(TimeZone)`

setDefault

```
public static void setDefault(TimeZone zone)
```

Sets the `TimeZone` that is returned by the `getDefault` method. `zone` is cached. If `zone` is null, the cached default `TimeZone` is cleared. This method doesn't change the value of the `user.timezone` property.

Parameters:

`zone - the new default TimeZone, or null`

Throws:

`SecurityException - if the security manager's checkPermission denies PropertyPermission("user.timezone", "write")`

See Also:

`getDefault(), PropertyPermission`

hasSameRules

```
public boolean hasSameRules(TimeZone other)
```

Returns true if this zone has the same rule and offset as another zone. That is, if this zone differs only in ID, if at all. Returns false if the other zone is null.

Parameters:

`other - the TimeZone object to be compared with`

Returns:

`true if the other zone is not null and is the same as this one, with the possible exception of the ID`

Since:

`1.2`

clone

```
public Object clone()
```

Creates a copy of this TimeZone.

Overrides:

`clone` in class `Object`

Returns:

`a clone of this TimeZone`

See Also:

`Cloneable`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.