compact1, compact2, compact3

java.util.concurrent

Class LinkedBlockingQueue<E>

java.lang.Object
  java.util.AbstractCollection<E>
    java.util.AbstractQueue<E>
      java.util.concurrent.LinkedBlockingQueue<E>

Type Parameters:

`E - the type of elements held in this collection`

All Implemented Interfaces:

`Serializable, Iterable<E>, Collection<E>, BlockingQueue<E>, Queue<E>`

```
public class LinkedBlockingQueue<E>
extends AbstractQueue<E>
implements BlockingQueue<E>, Serializable
```

An optionally-bounded blocking queue based on linked nodes. This queue orders elements FIFO (first-in-first-out). The *head* of the queue is that element that has been on the queue the longest time. The *tail* of the queue is that element that has been on the queue the shortest time. New elements are inserted at the tail of the queue, and the queue retrieval operations obtain elements at the head of the queue. Linked queues typically have higher throughput than array-based queues but less predictable performance in most concurrent applications.

The optional capacity bound constructor argument serves as a way to prevent excessive queue expansion. The capacity, if unspecified, is equal to `Integer.MAX_VALUE`. Linked nodes are dynamically created upon each insertion unless this would bring the queue above capacity.

This class and its iterator implement all of the *optional* methods of the `Collection` and `Iterator` interfaces.

This class is a member of the Java Collections Framework.

Since:

1.5

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`LinkedBlockingQueue()`	Creates a `LinkedBlockingQueue` with a capacity of `Integer.MAX_VALUE`.
`LinkedBlockingQueue(Collection<? extends E> c)`	Creates a `LinkedBlockingQueue` with a capacity of `Integer.MAX_VALUE`, initially containing the elements of the given collection, added in traversal order of the collection's iterator.
`LinkedBlockingQueue(int capacity)`	Creates a `LinkedBlockingQueue` with the given (fixed) capacity.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`void`	`clear()`	Atomically removes all of the elements from this queue.
`boolean`	`contains(Object o)`	Returns `true` if this queue contains the specified element.

int	**drainTo**(**Collection**<? super **E**> c)	Removes all available elements from this queue and adds them to the given collection.
int	**drainTo**(**Collection**<? super **E**> c, int maxElements)	Removes at most the given number of available elements from this queue and adds them to the given collection.
Iterator<**E**>	**iterator**()	Returns an iterator over the elements in this queue in proper sequence.
boolean	**offer**(**E** e)	Inserts the specified element at the tail of this queue if it is possible to do so immediately without exceeding the queue's capacity, returning `true` upon success and `false` if this queue is full.
boolean	**offer**(**E** e, long timeout, **TimeUnit** unit)	Inserts the specified element at the tail of this queue, waiting if necessary up to the specified wait time for space to become available.
E	**peek**()	Retrieves, but does not remove, the head of this queue, or returns `null` if this queue is empty.
E	**poll**()	Retrieves and removes the head of this queue, or returns `null` if this queue is empty.
E	**poll**(long timeout, **TimeUnit** unit)	Retrieves and removes the head of this queue, waiting up to the specified wait time if necessary for an element to become available.
void	**put**(**E** e)	Inserts the specified element at the tail of this queue, waiting if necessary for space to become available.
int	**remainingCapacity**()	

		Returns the number of additional elements that this queue can ideally (in the absence of memory or resource constraints) accept without blocking.
boolean	**remove**(**Object** o)	Removes a single instance of the specified element from this queue, if it is present.
int	**size**()	Returns the number of elements in this queue.
Spliterator<**E**>	**spliterator**()	Returns a **Spliterator** over the elements in this queue.
E	**take**()	Retrieves and removes the head of this queue, waiting if necessary until an element becomes available.
Object[]	**toArray**()	Returns an array containing all of the elements in this queue, in proper sequence.
<T> T[]	**toArray**(T[] a)	Returns an array containing all of the elements in this queue, in proper sequence; the runtime type of the returned array is that of the specified array.
String	**toString**()	Returns a string representation of this collection.

Methods inherited from class java.util.AbstractQueue

add, addAll, element, remove

Methods inherited from class java.util.AbstractCollection

containsAll, isEmpty, removeAll, retainAll

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Methods inherited from interface java.util.concurrent.BlockingQueue

add

Methods inherited from interface java.util.Queue

element, remove

Methods inherited from interface java.util.Collection

addAll, containsAll, equals, hashCode, isEmpty, parallelStream, removeAll, removeIf, retainAll, stream

Methods inherited from interface java.lang.Iterable

forEach

Constructor Detail

LinkedBlockingQueue

```
public LinkedBlockingQueue()
```

Creates a `LinkedBlockingQueue` with a capacity of `Integer.MAX_VALUE`.

LinkedBlockingQueue

```
public LinkedBlockingQueue(int capacity)
```

Creates a `LinkedBlockingQueue` with the given (fixed) capacity.

Parameters:

`capacity` - the capacity of this queue

Throws:

`IllegalArgumentException` - if `capacity` is not greater than zero

LinkedBlockingQueue

```
public LinkedBlockingQueue(Collection<? extends E> c)
```

Creates a `LinkedBlockingQueue` with a capacity of `Integer.MAX_VALUE`, initially containing the elements of the given collection, added in traversal order of the collection's iterator.

Parameters:

`c - the collection of elements to initially contain`

Throws:

`NullPointerException - if the specified collection or any of its elements are null`

Method Detail

size

```
public int size()
```

Returns the number of elements in this queue.

Specified by:

`size in interface Collection<E>`

Specified by:

`size in class AbstractCollection<E>`

Returns:

`the number of elements in this queue`

remainingCapacity

```
public int remainingCapacity()
```

Returns the number of additional elements that this queue can ideally (in the absence of memory or resource constraints) accept without blocking. This is always equal to the initial capacity of this queue less the current `size` of this queue.

Note that you *cannot* always tell if an attempt to insert an element will succeed by inspecting `remainingCapacity` because it may be the case that another thread is about to insert or remove an element.

Specified by:

`remainingCapacity in interface BlockingQueue<E>`

Returns:

the remaining capacity

put

```
public void put(E e)
         throws InterruptedException
```

Inserts the specified element at the tail of this queue, waiting if necessary for space to become available.

Specified by:

put in interface BlockingQueue<E>

Parameters:

e - the element to add

Throws:

InterruptedException - if interrupted while waiting

NullPointerException - if the specified element is null

offer

```
public boolean offer(E e,
                     long timeout,
                     TimeUnit unit)
              throws InterruptedException
```

Inserts the specified element at the tail of this queue, waiting if necessary up to the specified wait time for space to become available.

Specified by:

`offer` in interface `BlockingQueue<E>`

Parameters:

`e` - the element to add

`timeout` - how long to wait before giving up, in units of `unit`

`unit` - a `TimeUnit` determining how to interpret the `timeout` parameter

Returns:

`true` if successful, or `false` if the specified waiting time elapses before space is available

Throws:

`InterruptedException` - if interrupted while waiting

`NullPointerException` - if the specified element is null

offer

```
public boolean offer(E e)
```

Inserts the specified element at the tail of this queue if it is possible to do so immediately without exceeding the queue's capacity, returning `true` upon success and `false` if this queue is full. When using a capacity-restricted queue, this method is generally preferable to method `add`, which can fail to insert an element only by throwing an exception.

Specified by:

`offer` in interface `BlockingQueue<E>`

Specified by:

`offer` in interface `Queue<E>`

Parameters:

`e` - the element to add

Returns:

`true` if the element was added to this queue, else `false`

Throws:

`NullPointerException` - if the specified element is null

take

```
public E take()
       throws InterruptedException
```

Description copied from interface: `BlockingQueue`

Retrieves and removes the head of this queue, waiting if necessary until an element becomes available.

Specified by:

`take` in interface `BlockingQueue<E>`

Returns:

the head of this queue

Throws:

`InterruptedException` - if interrupted while waiting

poll

```
public E poll(long timeout,
              TimeUnit unit)
       throws InterruptedException
```

Description copied from interface: `BlockingQueue`

Retrieves and removes the head of this queue, waiting up to the specified wait time if necessary for an element to become available.

Specified by:

`poll` in interface `BlockingQueue<E>`

Parameters:

`timeout` - how long to wait before giving up, in units of `unit`

`unit` - a `TimeUnit` determining how to interpret the `timeout` parameter

Returns:

the head of this queue, or null if the specified waiting time elapses before an element is available

Throws:

`InterruptedException` - if interrupted while waiting

poll

```
public E poll()
```

Description copied from interface: Queue

Retrieves and removes the head of this queue, or returns `null` if this queue is empty.

Specified by:

`poll` in interface `Queue<E>`

Returns:

the head of this queue, or null if this queue is empty

peek

```
public E peek()
```

Description copied from interface: Queue

Retrieves, but does not remove, the head of this queue, or returns `null` if this queue is empty.

Specified by:

`peek` in interface `Queue<E>`

Returns:

the head of this queue, or null if this queue is empty

remove

```
public boolean remove(Object o)
```

Removes a single instance of the specified element from this queue, if it is present. More formally, removes an element `e` such that `o.equals(e)`, if this queue contains one or more such elements. Returns `true` if this queue contained the specified element (or equivalently, if this queue changed as a result of the call).

Specified by:

`remove` in interface `Collection<E>`

Specified by:

`remove` in interface `BlockingQueue<E>`

Overrides:

`remove` in class `AbstractCollection<E>`

Parameters:

o - element to be removed from this queue, if present

Returns:

`true if this queue changed as a result of the call`

contains

```
public boolean contains(Object o)
```

Returns `true` if this queue contains the specified element. More formally, returns `true` if and only if this queue contains at least one element `e` such that `o.equals(e)`.

Specified by:

`contains in interface Collection<E>`

Specified by:

`contains in interface BlockingQueue<E>`

Overrides:

`contains in class AbstractCollection<E>`

Parameters:

`o - object to be checked for containment in this queue`

Returns:

`true if this queue contains the specified element`

toArray

```
public Object[] toArray()
```

Returns an array containing all of the elements in this queue, in proper sequence.

The returned array will be "safe" in that no references to it are maintained by this queue. (In other words, this method must allocate a new array). The caller is thus free to modify the returned array.

This method acts as bridge between array-based and collection-based APIs.

Specified by:

`toArray in interface Collection<E>`

Overrides:

`toArray in class AbstractCollection<E>`

Returns:

`an array containing all of the elements in this queue`

toArray

```
public <T> T[] toArray(T[] a)
```

Returns an array containing all of the elements in this queue, in proper sequence; the runtime type of the returned array is that of the specified array. If the queue fits in the specified array, it is returned therein. Otherwise, a new array is allocated with the runtime type of the specified array and the size of this queue.

If this queue fits in the specified array with room to spare (i.e., the array has more elements than this queue), the element in the array immediately following the end of the queue is set to `null`.

Like the `toArray()` method, this method acts as bridge between array-based and collection-based APIs. Further, this method allows precise control over the runtime type of the output array, and may, under certain circumstances, be used to save allocation costs.

Suppose `x` is a queue known to contain only strings. The following code can be used to dump the queue into a newly allocated array of `String`:

```
  String[] y = x.toArray(new String[0]);
```

Note that `toArray(new Object[0])` is identical in function to `toArray()`.

Specified by:

`toArray` in interface `Collection<E>`

Overrides:

`toArray` in class `AbstractCollection<E>`

Type Parameters:

`T` - the runtime type of the array to contain the collection

Parameters:

`a` - the array into which the elements of the queue are to be stored, if it is big enough; otherwise, a new array of the same runtime type is allocated for this purpose

Returns:

an array containing all of the elements in this queue

Throws:

`ArrayStoreException` - if the runtime type of the specified array is not a supertype of the runtime type of every element in this queue

`NullPointerException` - if the specified array is null

toString

```
public String toString()
```

Description copied from class: AbstractCollection

Returns a string representation of this collection. The string representation consists of a list of the collection's elements in the order they are returned by its iterator, enclosed in square brackets (`"[]"`). Adjacent elements are separated by the characters `", "` (comma and space). Elements are converted to strings as by `String.valueOf(Object)`.

Overrides:

`toString` in class `AbstractCollection<E>`

Returns:

a string representation of this collection

clear

```
public void clear()
```

Atomically removes all of the elements from this queue. The queue will be empty after this call returns.

Specified by:

`clear` in interface `Collection<E>`

Overrides:

`clear` in class `AbstractQueue<E>`

drainTo

```
public int drainTo(Collection<? super E> c)
```

Description copied from interface: BlockingQueue

Removes all available elements from this queue and adds them to the given collection. This operation may be more efficient than repeatedly polling this queue. A failure encountered while attempting to add elements to collection `c` may result in elements being in neither, either or both collections when the associated exception is thrown. Attempts to drain a queue to itself result in `IllegalArgumentException`. Further, the behavior of this operation is undefined if the specified collection is modified while the operation is in progress.

Specified by:

`drainTo` in interface `BlockingQueue<E>`

Parameters:

c - the collection to transfer elements into

Returns:

the number of elements transferred

Throws:

UnsupportedOperationException - if addition of elements is not supported by the specified collection

ClassCastException - if the class of an element of this queue prevents it from being added to the specified collection

NullPointerException - if the specified collection is null

IllegalArgumentException - if the specified collection is this queue, or some property of an element of this queue prevents it from being added to the specified collection

drainTo

```
public int drainTo(Collection<? super E> c,
                   int maxElements)
```

Description copied from interface: BlockingQueue

Removes at most the given number of available elements from this queue and adds them to the given collection. A failure encountered while attempting to add elements to collection `c` may result in elements being in neither, either or both collections when the associated exception is thrown. Attempts to drain a queue to itself result in `IllegalArgumentException`. Further, the behavior of this operation is undefined if the specified collection is modified while the operation is in progress.

Specified by:

drainTo in interface BlockingQueue<E>

Parameters:

c - the collection to transfer elements into

maxElements - the maximum number of elements to transfer

Returns:

the number of elements transferred

Throws:

UnsupportedOperationException - if addition of elements is not supported by the specified collection

ClassCastException - if the class of an element of this queue prevents it from being added to the specified collection

NullPointerException - if the specified collection is null

IllegalArgumentException - if the specified collection is this queue, or some property of an element of this queue prevents it from being added to the specified collection

iterator

```
public Iterator<E> iterator()
```

Returns an iterator over the elements in this queue in proper sequence. The elements will be returned in order from first (head) to last (tail).

The returned iterator is *weakly consistent*.

Specified by:

iterator in interface Iterable<E>

Specified by:

iterator in interface Collection<E>

Specified by:

iterator in class AbstractCollection<E>

Returns:

an iterator over the elements in this queue in proper sequence

spliterator

```
public Spliterator<E> spliterator()
```

Returns a Spliterator over the elements in this queue.

The returned spliterator is *weakly consistent*.

The Spliterator reports Spliterator.CONCURRENT, Spliterator.ORDERED, and Spliterator.NONNULL.

Specified by:

spliterator in interface Iterable<E>

Specified by:

spliterator in interface Collection<E>

Implementation Note:

The Spliterator implements trySplit to permit limited parallelism.

Returns:

a Spliterator over the elements in this queue

Since:

1.8

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.