JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Class Boolean

java.lang.Object
    java.lang.Boolean

All Implemented Interfaces:

Serializable, Comparable<Boolean>

```
public final class Boolean
extends Object
implements Serializable, Comparable<Boolean>
```

The Boolean class wraps a value of the primitive type `boolean` in an object. An object of type `Boolean` contains a single field whose type is `boolean`.

In addition, this class provides many methods for converting a `boolean` to a `String` and a `String` to a `boolean`, as well as other constants and methods useful when dealing with a `boolean`.

Since:

`JDK1.0`

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description

static Boolean	FALSE	The Boolean object corresponding to the primitive value false.
static Boolean	TRUE	The Boolean object corresponding to the primitive value true.
static Class<Boolean>	TYPE	The Class object representing the primitive type boolean.

Constructor Summary

Constructors

Constructor	Description
Boolean(boolean value)	Allocates a Boolean object representing the value argument.
Boolean(String s)	Allocates a Boolean object representing the value true if the string argument is not null and is equal, ignoring case, to the string "true".

Method Summary

Instance Methods

Concrete Methods

Modifier and Type	Method	Description
boolean	booleanValue()	Returns the value of this Boolean object as a boolean primitive.
static int	compare(boolean x, boolean y)	Compares two boolean values.
int	compareTo(Boolean b)	Compares this Boolean instance with another.
boolean	equals(Object obj)	Returns true if and only if the argument is not null and is a Boolean object that represents the same

		boolean value as this object.
static boolean	**getBoolean**(**String** name)	Returns true if and only if the system property named by the argument exists and is equal to the string "true".
int	**hashCode**()	Returns a hash code for this Boolean object.
static int	**hashCode**(boolean value)	Returns a hash code for a boolean value; compatible with Boolean.hashCode().
static boolean	**logicalAnd**(boolean a, boolean b)	Returns the result of applying the logical AND operator to the specified boolean operands.
static boolean	**logicalOr**(boolean a, boolean b)	Returns the result of applying the logical OR operator to the specified boolean operands.
static boolean	**logicalXor**(boolean a, boolean b)	Returns the result of applying the logical XOR operator to the specified boolean operands.
static boolean	**parseBoolean**(**String** s)	Parses the string argument as a boolean.
String	**toString**()	Returns a String object representing this Boolean's value.
static **String**	**toString**(boolean b)	Returns a String object representing the specified boolean.
static **Boolean**	**valueOf**(boolean b)	Returns a Boolean instance representing the specified boolean value.
static **Boolean**	**valueOf**(**String** s)	Returns a Boolean with a value represented by the specified string.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

TRUE

```
public static final Boolean TRUE
```

The Boolean object corresponding to the primitive value true.

FALSE

```
public static final Boolean FALSE
```

The Boolean object corresponding to the primitive value false.

TYPE

```
public static final Class<Boolean> TYPE
```

The Class object representing the primitive type boolean.

Since:

JDK1.1

Constructor Detail

Boolean

```
public Boolean(boolean value)
```

Allocates a Boolean object representing the value argument.

Note: It is rarely appropriate to use this constructor. Unless a *new* instance is required, the static factory `valueOf(boolean)` is generally a better choice. It is likely to yield significantly better space and time performance.

Parameters:

value - the value of the Boolean.

Boolean

```
public Boolean(String s)
```

Allocates a `Boolean` object representing the value `true` if the string argument is not `null` and is equal, ignoring case, to the string `"true"`. Otherwise, allocate a `Boolean` object representing the value `false`. Examples:

`new Boolean("True")` produces a `Boolean` object that represents `true`.
`new Boolean("yes")` produces a `Boolean` object that represents `false`.

Parameters:

`s - the string to be converted to a Boolean.`

Method Detail

parseBoolean

```
public static boolean parseBoolean(String s)
```

Parses the string argument as a boolean. The `boolean` returned represents the value `true` if the string argument is not `null` and is equal, ignoring case, to the string `"true"`.

Example: `Boolean.parseBoolean("True")` returns `true`.
Example: `Boolean.parseBoolean("yes")` returns `false`.

Parameters:

`s - the String containing the boolean representation to be parsed`

Returns:

`the boolean represented by the string argument`

Since:

`1.5`

booleanValue

```
public boolean booleanValue()
```

Returns the value of this `Boolean` object as a boolean primitive.

Returns:

`the primitive boolean value of this object.`

valueOf

```
public static Boolean valueOf(boolean b)
```

Returns a `Boolean` instance representing the specified `boolean` value. If the specified `boolean` value is `true`, this method returns `Boolean.TRUE`; if it is `false`, this method returns `Boolean.FALSE`. If a new `Boolean` instance is not required, this method should generally be used in preference to the constructor `Boolean(boolean)`, as this method is likely to yield significantly better space and time performance.

Parameters:

`b - a boolean value.`

Returns:

`a Boolean instance representing b.`

Since:

`1.4`

valueOf

```
public static Boolean valueOf(String s)
```

Returns a `Boolean` with a value represented by the specified string. The `Boolean` returned represents a true value if the string argument is not `null` and is equal, ignoring case, to the string `"true"`.

Parameters:

`s - a string.`

Returns:

`the Boolean value represented by the string.`

toString

```
public static String toString(boolean b)
```

Returns a `String` object representing the specified boolean. If the specified boolean is `true`, then the string `"true"` will be returned, otherwise the string `"false"` will be returned.

Parameters:

`b - the boolean to be converted`

Returns:

`the string representation of the specified boolean`

Since:

1.4

toString

```
public String toString()
```

Returns a `String` object representing this Boolean's value. If this object represents the value `true`, a string equal to `"true"` is returned. Otherwise, a string equal to `"false"` is returned.

Overrides:

`toString` in class `Object`

Returns:

a string representation of this object.

hashCode

```
public int hashCode()
```

Returns a hash code for this `Boolean` object.

Overrides:

`hashCode` in class `Object`

Returns:

the integer 1231 if this object represents true; returns the integer 1237 if this object represents false.

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

hashCode

```
public static int hashCode(boolean value)
```

Returns a hash code for a `boolean` value; compatible with `Boolean.hashCode()`.

Parameters:

`value - the value to hash`

Returns:

`a hash code value for a boolean value.`

Since:

`1.8`

equals

```
public boolean equals(Object obj)
```

Returns `true` if and only if the argument is not `null` and is a `Boolean` object that represents the same `boolean` value as this object.

Overrides:

`equals` in class `Object`

Parameters:

`obj - the object to compare with.`

Returns:

`true if the Boolean objects represent the same value; false otherwise.`

See Also:

`Object.hashCode()`, `HashMap`

getBoolean

```
public static boolean getBoolean(String name)
```

Returns `true` if and only if the system property named by the argument exists and is equal to the string `"true"`. (Beginning with version 1.0.2 of the Java™ platform, the test of this string is case insensitive.) A system property is accessible through `getProperty`, a method defined by the `System` class.

If there is no property with the specified name, or if the specified name is empty or null, then `false` is returned.

Parameters:

name - the system property name.

Returns:

the boolean value of the system property.

Throws:

SecurityException - for the same reasons as System.getProperty

See Also:

System.getProperty(java.lang.String), System.getProperty(java.lang.String, java.lang.String)

compareTo

```
public int compareTo(Boolean b)
```

Compares this Boolean instance with another.

Specified by:

compareTo in interface Comparable<Boolean>

Parameters:

b - the Boolean instance to be compared

Returns:

zero if this object represents the same boolean value as the argument; a positive value if this object represents true and the argument represents false; and a negative value if this object represents false and the argument represents true

Throws:

NullPointerException - if the argument is null

Since:

1.5

See Also:

Comparable

compare

```
public static int compare(boolean x,
                          boolean y)
```

Compares two boolean values. The value returned is identical to what would be returned by:

```
    Boolean.valueOf(x).compareTo(Boolean.valueOf(y))
```

Parameters:

x - the first boolean to compare

y - the second boolean to compare

Returns:

the value 0 if x == y; a value less than 0 if !x && y; and a value greater than 0 if x && !y

Since:

1.7

logicalAnd

```
public static boolean logicalAnd(boolean a,
                                 boolean b)
```

Returns the result of applying the logical AND operator to the specified boolean operands.

Parameters:

a - the first operand

b - the second operand

Returns:

the logical AND of a and b

Since:

1.8

See Also:

BinaryOperator

logicalOr

```
public static boolean logicalOr(boolean a,
                                boolean b)
```

Returns the result of applying the logical OR operator to the specified boolean operands.

Parameters:

a - the first operand

b - the second operand

Returns:

the logical OR of a and b

Since:

1.8

See Also:

BinaryOperator

logicalXor

```
public static boolean logicalXor(boolean a,
                                 boolean b)
```

Returns the result of applying the logical XOR operator to the specified `boolean` operands.

Parameters:

`a - the first operand`

`b - the second operand`

Returns:

`the logical XOR of a and b`

Since:

`1.8`

See Also:

BinaryOperator

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.