JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class IllegalAccessException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.ReflectiveOperationException
        java.lang.IllegalAccessException

All Implemented Interfaces:

Serializable

```
public class IllegalAccessException
extends ReflectiveOperationException
```

An IllegalAccessException is thrown when an application tries to reflectively create an instance (other than an array), set or get a field, or invoke a method, but the currently executing method does not have access to the definition of the specified class, field, method or constructor.

Since:

1.0

See Also:

Class.newInstance(),
Field.set(Object, Object),
Field.setBoolean(Object, boolean),
Field.setByte(Object, byte),
Field.setShort(Object, short),
Field.setChar(Object, char),
Field.setInt(Object, int),
Field.setLong(Object, long),
Field.setFloat(Object, float),
Field.setDouble(Object, double),
Field.get(Object),
Field.getBoolean(Object),
Field.getByte(Object),
Field.getShort(Object),
Field.getChar(Object),
Field.getInt(Object),
Field.getLong(Object),
Field.getFloat(Object),
Field.getDouble(Object),
Method.invoke(Object, Object[]),
Constructor.newInstance(Object[]),

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IllegalAccessException()`	Constructs an `IllegalAccessException` without a detail message.
`IllegalAccessException(String s)`	Constructs an `IllegalAccessException` with a detail message.

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

IllegalAccessException

```
public IllegalAccessException()
```

Constructs an `IllegalAccessException` without a detail message.

IllegalAccessException

```
public IllegalAccessException(String s)
```

Constructs an `IllegalAccessException` with a detail message.

Parameters:

`s` - the detail message.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.