JavaScript is disabled on your browser.

Class IllegalAccessException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.ReflectiveOperationException
        java.lang.IllegalAccessException

All Implemented Interfaces:

Serializable

```
public class IllegalAccessException
extends ReflectiveOperationException
```

An IllegalAccessException is thrown when an application tries to reflectively create an instance (other than an array), set or get a field, or invoke a method, but the currently executing method does not have access to the definition of the specified class, field, method or constructor.

Since:

JDK1.0

See Also:

Class.newInstance(), Field.set(Object, Object), Field.setBoolean(Object, boolean), Field.setByte(Object, byte), Field.setShort(Object, short), Field.setChar(Object, char), Field.setInt(Object, int), Field.setLong(Object, long), Field.setFloat(Object, float), Field.setDouble(Object, double), Field.get(Object), Field.getBoolean(Object), Field.getByte(Object), Field.getShort(Object), Field.getChar(Object), Field.getInt(Object), Field.getLong(Object), Field.getFloat(Object), Field.getDouble(Object), Method.invoke(Object, Object[]), Constructor.newInstance(Object[]), Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IllegalAccessException()`	Constructs an `IllegalAccessException` without a detail message.
`IllegalAccessException(String s)`	Constructs an `IllegalAccessException` with a detail message.

Method Summary

Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Detail

IllegalAccessException

```
public IllegalAccessException()
```

Constructs an `IllegalAccessException` without a detail message.

IllegalAccessException

```
public IllegalAccessException(String s)
```

Constructs an `IllegalAccessException` with a detail message.

Parameters:

`s - the detail message.`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.