JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class AssertionError

java.lang.Object
    java.lang.Throwable
        java.lang.Error
            java.lang.AssertionError

All Implemented Interfaces:

Serializable

```
public class AssertionError
extends Error
```

Thrown to indicate that an assertion has failed.

The seven one-argument public constructors provided by this class ensure that the assertion error returned by the invocation:

```
    new AssertionError(expression)
```

has as its detail message the *string conversion* of *expression* (as defined in section §5.1.11 of *The Java Language Specification*), regardless of the type of *expression*.

Since:

1.4

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
AssertionError()	Constructs an AssertionError with no detail message.
AssertionError(boolean detailMessage)	Constructs an AssertionError with its detail message derived from the specified `boolean`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.
AssertionError(char detailMessage)	Constructs an AssertionError with its detail message derived from the

	specified `char`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.
AssertionError `(double detailMessage)`	Constructs an AssertionError with its detail message derived from the specified `double`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.
AssertionError `(float detailMessage)`	Constructs an AssertionError with its detail message derived from the specified `float`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.
AssertionError`(int detailMessage)`	Constructs an AssertionError with its detail message derived from the specified `int`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.
AssertionError `(long detailMessage)`	Constructs an AssertionError with its detail message derived from the specified `long`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.
AssertionError `(Object detailMessage)`	Constructs an AssertionError with its detail message derived from the specified object, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.
AssertionError`(String message,` `Throwable cause)`	Constructs a new `AssertionError` with the specified detail message and cause.

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

AssertionError

```
public AssertionError()
```

Constructs an AssertionError with no detail message.

AssertionError

```
public AssertionError(Object detailMessage)
```

Constructs an AssertionError with its detail message derived from the specified object, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.

If the specified object is an instance of `Throwable`, it becomes the *cause* of the newly constructed assertion error.

Parameters:

`detailMessage` - value to be used in constructing detail message

See Also:

`Throwable.getCause()`

AssertionError

```
public AssertionError(boolean detailMessage)
```

Constructs an AssertionError with its detail message derived from the specified `boolean`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.

Parameters:

detailMessage - value to be used in constructing detail message

AssertionError

```
public AssertionError(char detailMessage)
```

Constructs an AssertionError with its detail message derived from the specified `char`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.

Parameters:

detailMessage - value to be used in constructing detail message

AssertionError

```
public AssertionError(int detailMessage)
```

Constructs an AssertionError with its detail message derived from the specified `int`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.

Parameters:

detailMessage - value to be used in constructing detail message

AssertionError

```
public AssertionError(long detailMessage)
```

Constructs an AssertionError with its detail message derived from the specified `long`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.

Parameters:

detailMessage - value to be used in constructing detail message

AssertionError

```
public AssertionError(float detailMessage)
```

Constructs an AssertionError with its detail message derived from the specified `float`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.

Parameters:

detailMessage - value to be used in constructing detail message

AssertionError

```
public AssertionError(double detailMessage)
```

Constructs an AssertionError with its detail message derived from the specified `double`, which is converted to a string as defined in section §5.1.11 of *The Java Language Specification*.

Parameters:

`detailMessage` - value to be used in constructing detail message

AssertionError

```
public AssertionError(String message,
                      Throwable cause)
```

Constructs a new `AssertionError` with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this error's detail message.

Parameters:

`message` - the detail message, may be `null`

`cause` - the cause, may be `null`

Since:

1.7

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.