JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class UnsupportedOperationException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.UnsupportedOperationException

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

HeadlessException, ReadOnlyBufferException, ReadOnlyFileSystemException, VMCannotBeModifiedException

---

```
public class UnsupportedOperationException
extends RuntimeException
```

Thrown to indicate that the requested operation is not supported.

This class is a member of the Java Collections Framework.

Since:

1.2

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`UnsupportedOperationException()`	Constructs a new `UnsupportedOperationException` with `null` as its detail message.
`UnsupportedOperationException (String message)`	Constructs a new `UnsupportedOperationException` with the specified detail message.
`UnsupportedOperationException (String message, Throwable cause)`	Constructs a new `UnsupportedOperationException` with the specified detail message and cause.
`UnsupportedOperationException (Throwable cause)`	Constructs a new `UnsupportedOperationException`

	with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

UnsupportedOperationException

```
public UnsupportedOperationException()
```

Constructs a new `UnsupportedOperationException` with `null` as its detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(Throwable)`.

UnsupportedOperationException

```
public UnsupportedOperationException(String message)
```

Constructs a new `UnsupportedOperationException` with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(Throwable)`.

Parameters:

`message` - the detail message

UnsupportedOperationException

```
public UnsupportedOperationException(String message,
                                     Throwable cause)
```

Constructs a new `UnsupportedOperationException` with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this exception's detail message.

Parameters:

`message` - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.5

UnsupportedOperationException

```
public UnsupportedOperationException(Throwable cause)
```

Constructs a new `UnsupportedOperationException` with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `PrivilegedActionException`).

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.5

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.