JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Class ReflectiveOperationException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.ReflectiveOperationException

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

ClassNotFoundException, IllegalAccessException, InstantiationException, InvocationTargetException, NoSuchFieldException, NoSuchMethodException

---

```
public class ReflectiveOperationException
extends Exception
```

Common superclass of exceptions thrown by reflective operations in core reflection.

Since:

1.7

See Also:

LinkageError, Serialized Form

Constructor Summary

Constructors

Constructor	Description
ReflectiveOperationException()	Constructs a new exception with null

	as its detail message.
ReflectiveOperationException(**String** message)	Constructs a new exception with the specified detail message.
ReflectiveOperationException(**String** message, **Throwable** cause)	Constructs a new exception with the specified detail message and cause.
ReflectiveOperationException(**Throwable** cause)	Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

ReflectiveOperationException

```
public ReflectiveOperationException()
```

Constructs a new exception with `null` as its detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

ReflectiveOperationException

```
public ReflectiveOperationException(String message)
```

Constructs a new exception with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

Parameters:

`message - the detail message. The detail message is saved for later retrieval by the Throwable.getMessage() method.`

ReflectiveOperationException

```
public ReflectiveOperationException(String message,
                                    Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this exception's detail message.

Parameters:

`message - the detail message (which is saved for later retrieval by the Throwable.getMessage() method).`

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

ReflectiveOperationException

```
public ReflectiveOperationException(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Parameters:

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.