JavaScript is disabled on your browser.



compact1, compact2, compact3

java.lang

# Class UnsupportedOperationException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.UnsupportedOperationException

**All Implemented Interfaces:**

Serializable

**Direct Known Subclasses:**

HeadlessException, ReadOnlyBufferException, ReadOnlyFileSystemException

---

```
public class UnsupportedOperationException
extends RuntimeException
```

Thrown to indicate that the requested operation is not supported.

This class is a member of the Java Collections Framework.

**Since:**

1.2

**See Also:**

Serialized Form

## *Constructor Summary*

**Constructors**

| Constructor | Description |
| --- | --- |
| `UnsupportedOperationException()` | |

| | |
|---|---|
| | Constructs an UnsupportedOperat with no detail messa |
| `UnsupportedOperationException(String message)` | Constructs an UnsupportedOperat with the specified d message. |
| `UnsupportedOperationException(String message, Throwable cause)` | Constructs a new ex the specified detail cause. |
| `UnsupportedOperationException(Throwable cause)` | Constructs a new ex the specified cause message of (cause= null : cause.toSt (which typically con class and detail mes cause). |

## *Method Summary*

### Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

## *Constructor Detail*

### UnsupportedOperationException

```
public UnsupportedOperationException()
```

Constructs an UnsupportedOperationException with no detail message.

### UnsupportedOperationException

```
public UnsupportedOperationException(String message)
```

Constructs an UnsupportedOperationException with the specified detail message.

**Parameters:**

`message - the detail message`

### UnsupportedOperationException

```
public UnsupportedOperationException(String message,
                                     Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this exception's detail message.

**Parameters:**

`message - the detail message (which is saved for later retrieval by the Throwable.getMessage() method).`

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

**Since:**

`1.5`

### UnsupportedOperationException

```
public UnsupportedOperationException(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `PrivilegedActionException`).

**Parameters:**

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

**Since:**

`1.5`




Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.