JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface Readable

All Known Implementing Classes:

BufferedReader, CharArrayReader, CharBuffer, FileReader, FilterReader, InputStreamReader, LineNumberReader, PipedReader, PushbackReader, Reader, StringReader

---

`public interface Readable`

A `Readable` is a source of characters. Characters from a `Readable` are made available to callers of the read method via a `CharBuffer`.

Since:

1.5

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
`int`	`read(CharBuffer cb)`	Attempts to read characters into the specified character buffer.

Method Details

read

```
int read(CharBuffer cb)
  throws IOException
```

Attempts to read characters into the specified character buffer. The buffer is used as a repository of characters as-is: the only changes made are the results of a put operation. No flipping or rewinding of the buffer is performed. If the length of the specified character buffer is zero, then no characters will be read and zero will be returned.

Parameters:

`cb` - the buffer to read characters into

Returns:

The number of `char` values added to the buffer, possibly zero, or -1 if this source of characters is at its end

Throws:

`IOException` - if an I/O error occurs

`NullPointerException` - if cb is null

`ReadOnlyBufferException` - if cb is a read only buffer, even if its length is zero

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.