JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Interface Appendable

All Known Implementing Classes:

BufferedWriter, CharArrayWriter, CharBuffer, FileWriter, FilterWriter, LogStream, OutputStreamWriter, PipedWriter, PrintStream, PrintWriter, StringBuffer, StringBuilder, StringWriter, Writer

---

```
public interface Appendable
```

An object to which `char` sequences and values can be appended. The `Appendable` interface must be implemented by any class whose instances are intended to receive formatted output from a `Formatter`.

The characters to be appended should be valid Unicode characters as described in Unicode Character Representation. Note that supplementary characters may be composed of multiple 16-bit `char` values.

Appendables are not necessarily safe for multithreaded access. Thread safety is the responsibility of classes that extend and implement this interface.

Since this interface may be implemented by existing classes with different styles of error handling there is no guarantee that errors will be propagated to the invoker.

Since:

1.5

Method Summary

Abstract Methods

Modifier and Type	Method	Description
Appendable	append(char c)	

		Appends the specified character to this Appendable.
Appendable	append(CharSequence csq)	Appends the specified character sequence to this Appendable.
Appendable	append(CharSequence csq, int start, int end)	Appends a subsequence of the specified character sequence to this Appendable.

Method Detail

append

```
Appendable append(CharSequence csq)
           throws IOException
```

Appends the specified character sequence to this Appendable.

Depending on which class implements the character sequence csq, the entire sequence may not be appended. For instance, if csq is a CharBuffer then the subsequence to append is defined by the buffer's position and limit.

Parameters:

csq - The character sequence to append. If csq is null, then the four characters "null" are appended to this Appendable.

Returns:

A reference to this Appendable

Throws:

IOException - If an I/O error occurs

append

```
Appendable append(CharSequence csq,
                  int start,
                  int end)
           throws IOException
```

Appends a subsequence of the specified character sequence to this Appendable.

An invocation of this method of the form out.append(csq, start, end) when csq is not null, behaves in exactly the same way as the invocation

```
out.append(csq.subSequence(start, end))
```

Parameters:

csq - The character sequence from which a subsequence will be appended. If csq is null, then characters will be appended as if csq contained the four characters "null".

start - The index of the first character in the subsequence

end - The index of the character following the last character in the subsequence

Returns:

A reference to this Appendable

Throws:

IndexOutOfBoundsException - If start or end are negative, start is greater than end, or end is greater than csq.length()

IOException - If an I/O error occurs

append

```
Appendable append(char c)
           throws IOException
```

Appends the specified character to this Appendable.

Parameters:

c - The character to append

Returns:

A reference to this Appendable

Throws:

IOException - If an I/O error occurs

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.