JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Interface Readable

All Known Implementing Classes:

BufferedReader, CharArrayReader, CharBuffer, FileReader, FilterReader, InputStreamReader, LineNumberReader, PipedReader, PushbackReader, Reader, StringReader

---

public interface **Readable**

A Readable is a source of characters. Characters from a Readable are made available to callers of the read method via a CharBuffer.

Since:

1.5

Method Summary

Abstract Methods

Modifier and Type	Method	Description
int	**read**(**CharBuffer** cb)	Attempts to read characters into the specified character buffer.

Method Detail

read

```
int read(CharBuffer cb)
  throws IOException
```

Attempts to read characters into the specified character buffer. The buffer is used as a repository of characters as-is: the only changes made are the results of a put operation. No flipping or rewinding of the buffer is performed.

Parameters:

`cb - the buffer to read characters into`

Returns:

`The number of char values added to the buffer, or -1 if this source of characters is at its end`

Throws:

`IOException - if an I/O error occurs`

`NullPointerException - if cb is null`

`ReadOnlyBufferException - if cb is a read only buffer`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.