JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Interface Runnable

All Known Subinterfaces:

RunnableFuture<V>, RunnableScheduledFuture<V>

All Known Implementing Classes:

AsyncBoxView.ChildState, ForkJoinWorkerThread, FutureTask, RenderableImageProducer, SwingWorker, Thread, TimerTask

Functional Interface:

This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.

```
@FunctionalInterface
public interface Runnable
```

The Runnable interface should be implemented by any class whose instances are intended to be executed by a thread. The class must define a method of no arguments called run.

This interface is designed to provide a common protocol for objects that wish to execute code while they are active. For example, Runnable is implemented by class Thread. Being active simply means that a thread has been started and has not yet been stopped.

In addition, Runnable provides the means for a class to be active while not subclassing Thread. A class that implements Runnable can run without subclassing Thread by instantiating a Thread instance and passing itself in as the target. In most cases, the Runnable interface should be used if you are only planning to override the run() method and no other Thread methods. This is important because classes should not be subclassed unless the programmer intends on modifying or enhancing the fundamental behavior of the class.

Since:

JDK1.0

See Also:

`Thread`, `Callable`

Method Summary

Abstract Methods

Modifier and Type	Method	Description
`void`	**`run`**()	When an object implementing interface `Runnable` is used to create a thread, starting the thread causes the object's `run` method to be called in that separately executing thread.

Method Detail

run

`void run()`

When an object implementing interface `Runnable` is used to create a thread, starting the thread causes the object's `run` method to be called in that separately executing thread.

The general contract of the method `run` is that it may take any action whatsoever.

See Also:

`Thread.run()`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.