JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class Base64

java.lang.Object
    java.util.Base64

```
public class Base64
extends Object
```

This class consists exclusively of static methods for obtaining encoders and decoders for the Base64 encoding scheme. The implementation of this class supports the following types of Base64 as specified in RFC 4648 and RFC 2045.

- **Basic**

  Uses "The Base64 Alphabet" as specified in Table 1 of RFC 4648 and RFC 2045 for encoding and decoding operation. The encoder does not add any line feed (line separator) character. The decoder rejects data that contains characters outside the base64 alphabet.

- **URL and Filename safe**

  Uses the "URL and Filename safe Base64 Alphabet" as specified in Table 2 of RFC 4648 for encoding and decoding. The encoder does not add any line feed (line separator) character. The decoder rejects data that contains characters outside the base64 alphabet.

- **MIME**

  Uses the "The Base64 Alphabet" as specified in Table 1 of RFC 2045 for encoding and decoding operation. The encoded output must be represented in lines of no more than 76 characters each and uses a carriage return `'\r'` followed immediately by a linefeed `'\n'` as the line separator. No line separator is added to the end of the encoded output. All line separators or other characters not found in the base64 alphabet table are ignored in decoding operation.

Unless otherwise noted, passing a `null` argument to a method of this class will cause a `NullPointerException` to be thrown.

Since:

1.8

Nested Class Summary

Nested Classes

Modifier and Type	Class	Description
static class	**Base64.Decoder**	This class implements a decoder for decoding byte data using the Base64 encoding scheme as specified in RFC 4648 and RFC 2045.
static class	**Base64.Encoder**	This class implements an encoder for encoding byte data using the Base64 encoding scheme as specified in RFC 4648 and RFC 2045.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
static **Base64.Decoder**	**getDecoder**()	Returns a **Base64.Decoder** that decodes using the **Basic** type base64 encoding scheme.
static **Base64.Encoder**	**getEncoder**()	Returns a **Base64.Encoder** that encodes using the **Basic** type base64 encoding scheme.
static **Base64.Decoder**	**getMimeDecoder**()	

		Returns a **Base64.Decoder** that decodes using the **MIME** type base64 decoding scheme.
static **Base64.Encoder**	**getMimeEncoder**()	Returns a **Base64.Encoder** that encodes using the **MIME** type base64 encoding scheme.
static **Base64.Encoder**	**getMimeEncoder**(int lineLength, byte[] lineSeparator)	Returns a **Base64.Encoder** that encodes using the **MIME** type base64 encoding scheme with specified line length and line separators.
static **Base64.Decoder**	**getUrlDecoder**()	Returns a **Base64.Decoder** that decodes using the **URL and Filename safe** type base64 encoding scheme.

static Base64.Encoder	getUrlEncoder()	Returns a **Base64.Encoder** that encodes using the **URL and Filename safe** type base64 encoding scheme.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

getEncoder

```
public static Base64.Encoder getEncoder()
```

Returns a Base64.Encoder that encodes using the Basic type base64 encoding scheme.

Returns:

A Base64 encoder.

getUrlEncoder

```
public static Base64.Encoder getUrlEncoder()
```

Returns a Base64.Encoder that encodes using the URL and Filename safe type base64 encoding scheme.

Returns:

A Base64 encoder.

getMimeEncoder

```
public static Base64.Encoder getMimeEncoder()
```

Returns a Base64.Encoder that encodes using the MIME type base64 encoding scheme.

Returns:

A Base64 encoder.

getMimeEncoder

```
public static Base64.Encoder getMimeEncoder(int lineLength,
                                            byte[] lineSeparator)
```

Returns a Base64.Encoder that encodes using the MIME type base64 encoding scheme with specified line length and line separators.

Parameters:

lineLength - the length of each output line (rounded down to nearest multiple of 4). If lineLength <= 0 the output will not be separated in lines

lineSeparator - the line separator for each output line

Returns:

A Base64 encoder.

Throws:

IllegalArgumentException - if lineSeparator includes any character of "The Base64 Alphabet" as specified in Table 1 of RFC 2045.

getDecoder

```
public static Base64.Decoder getDecoder()
```

Returns a Base64.Decoder that decodes using the Basic type base64 encoding scheme.

Returns:

A Base64 decoder.

getUrlDecoder

```
public static Base64.Decoder getUrlDecoder()
```

Returns a Base64.Decoder that decodes using the URL and Filename safe type base64 encoding scheme.

Returns:

A Base64 decoder.

getMimeDecoder

```
public static Base64.Decoder getMimeDecoder()
```

Returns a `Base64.Decoder` that decodes using the MIME type base64 decoding scheme.

Returns:

`A Base64 decoder.`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.