JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class GregorianCalendar

java.lang.Object
    java.util.Calendar
        java.util.GregorianCalendar

All Implemented Interfaces:

`Serializable`, `Cloneable`, `Comparable<Calendar>`

```
public class GregorianCalendar
extends Calendar
```

`GregorianCalendar` is a concrete subclass of `Calendar` and provides the standard calendar system used by most of the world.

`GregorianCalendar` is a hybrid calendar that supports both the Julian and Gregorian calendar systems with the support of a single discontinuity, which corresponds by default to the Gregorian date when the Gregorian calendar was instituted (October 15, 1582 in some countries, later in others). The cutover date may be changed by the caller by calling `setGregorianChange()`.

Historically, in those countries which adopted the Gregorian calendar first, October 4, 1582 (Julian) was thus followed by October 15, 1582 (Gregorian). This calendar models this correctly. Before the Gregorian cutover, `GregorianCalendar` implements the Julian calendar. The only difference between the Gregorian and the Julian calendar is the leap year rule. The Julian calendar specifies leap years every four years, whereas the Gregorian calendar omits century years which are not divisible by 400.

`GregorianCalendar` implements *proleptic* Gregorian and Julian calendars. That is, dates are computed by extrapolating the current rules indefinitely far backward and forward in time. As a result, `GregorianCalendar` may be used for all years to generate meaningful and consistent results. However, dates obtained using `GregorianCalendar` are historically accurate only from March 1, 4 AD onward,

when modern Julian calendar rules were adopted. Before this date, leap year rules were applied irregularly, and before 45 BC the Julian calendar did not even exist.

Prior to the institution of the Gregorian calendar, New Year's Day was March 25. To avoid confusion, this calendar always uses January 1. A manual adjustment may be made if desired for dates that are prior to the Gregorian changeover and which fall between January 1 and March 24.

Week Of Year and Week Year

Values calculated for the `WEEK_OF_YEAR` field range from 1 to 53. The first week of a calendar year is the earliest seven day period starting on `getFirstDayOfWeek()` that contains at least `getMinimalDaysInFirstWeek()` days from that year. It thus depends on the values of `getMinimalDaysInFirstWeek()`, `getFirstDayOfWeek()`, and the day of the week of January 1. Weeks between week 1 of one year and week 1 of the following year (exclusive) are numbered sequentially from 2 to 52 or 53 (except for year(s) involved in the Julian-Gregorian transition).

The `getFirstDayOfWeek()` and `getMinimalDaysInFirstWeek()` values are initialized using locale-dependent resources when constructing a `GregorianCalendar`. The week determination is compatible with the ISO 8601 standard when `getFirstDayOfWeek()` is `MONDAY` and `getMinimalDaysInFirstWeek()` is 4, which values are used in locales where the standard is preferred. These values can explicitly be set by calling `setFirstDayOfWeek()` and `setMinimalDaysInFirstWeek()`.

A *week year* is in sync with a `WEEK_OF_YEAR` cycle. All weeks between the first and last weeks (inclusive) have the same *week year* value. Therefore, the first and last days of a week year may have different calendar year values.

For example, January 1, 1998 is a Thursday. If `getFirstDayOfWeek()` is `MONDAY` and `getMinimalDaysInFirstWeek()` is 4 (ISO 8601 standard compatible setting), then week 1 of 1998 starts on December 29, 1997, and ends on January 4, 1998. The week year is 1998 for the last three days of calendar year 1997. If, however, `getFirstDayOfWeek()` is `SUNDAY`, then week 1 of 1998 starts on January 4, 1998, and ends on January 10, 1998; the first three days of 1998 then are part of week 53 of 1997 and their week year is 1997.

Week Of Month

Values calculated for the `WEEK_OF_MONTH` field range from 0 to 6. Week 1 of a month (the days with `WEEK_OF_MONTH = 1`) is the earliest set of at least `getMinimalDaysInFirstWeek()` contiguous days in that month, ending on the day before `getFirstDayOfWeek()`. Unlike week 1 of a year, week 1 of a month may be shorter than 7 days, need not start on `getFirstDayOfWeek()`, and will not include days of the previous month. Days of a month before week 1 have a `WEEK_OF_MONTH` of 0.

For example, if `getFirstDayOfWeek()` is `SUNDAY` and `getMinimalDaysInFirstWeek()` is 4, then the first week of January 1998 is Sunday, January 4 through Saturday, January 10. These days have a `WEEK_OF_MONTH` of 1.

Thursday, January 1 through Saturday, January 3 have a WEEK_OF_MONTH of 0. If getMinimalDaysInFirstWeek() is changed to 3, then January 1 through January 3 have a WEEK_OF_MONTH of 1.

Default Fields Values

The clear method sets calendar field(s) undefined. GregorianCalendar uses the following default value for each calendar field if its value is undefined.

Field	Default Value
ERA	AD
YEAR	1970
MONTH	JANUARY
DAY_OF_MONTH	1
DAY_OF_WEEK	the first day of week
WEEK_OF_MONTH	0
DAY_OF_WEEK_IN_MONTH	1
AM_PM	AM
HOUR, HOUR_OF_DAY, MINUTE, SECOND, MILLISECOND	0

Default values are not applicable for the fields not listed above.

Example:

```
// get the supported ids for GMT-08:00 (Pacific Standard Time)
String[] ids = TimeZone.getAvailableIDs(-8 * 60 * 60 * 1000);
// if no ids were returned, something is wrong. get out.
if (ids.length == 0)
    System.exit(0);

 // begin output
System.out.println("Current Time");

// create a Pacific Standard Time time zone
SimpleTimeZone pdt = new SimpleTimeZone(-8 * 60 * 60 * 1000, ids[0]);

// set up rules for Daylight Saving Time
pdt.setStartRule(Calendar.APRIL, 1, Calendar.SUNDAY, 2 * 60 * 60 * 1000);
pdt.setEndRule(Calendar.OCTOBER, -1, Calendar.SUNDAY, 2 * 60 * 60 * 1000);

// create a GregorianCalendar with the Pacific Daylight time zone
// and the current date and time
Calendar calendar = new GregorianCalendar(pdt);
Date trialTime = new Date();
calendar.setTime(trialTime);
```

```
        // print out a bunch of interesting things
        System.out.println("ERA: " + calendar.get(Calendar.ERA));
        System.out.println("YEAR: " + calendar.get(Calendar.YEAR));
        System.out.println("MONTH: " + calendar.get(Calendar.MONTH));
        System.out.println("WEEK_OF_YEAR: " + calendar.get(Calendar.WEEK_OF_YEAR));
        System.out.println("WEEK_OF_MONTH: " + calendar.get(Calendar.WEEK_OF_MONTH));
        System.out.println("DATE: " + calendar.get(Calendar.DATE));
        System.out.println("DAY_OF_MONTH: " + calendar.get(Calendar.DAY_OF_MONTH));
        System.out.println("DAY_OF_YEAR: " + calendar.get(Calendar.DAY_OF_YEAR));
        System.out.println("DAY_OF_WEEK: " + calendar.get(Calendar.DAY_OF_WEEK));
        System.out.println("DAY_OF_WEEK_IN_MONTH: "
                           + calendar.get(Calendar.DAY_OF_WEEK_IN_MONTH));
        System.out.println("AM_PM: " + calendar.get(Calendar.AM_PM));
        System.out.println("HOUR: " + calendar.get(Calendar.HOUR));
        System.out.println("HOUR_OF_DAY: " + calendar.get(Calendar.HOUR_OF_DAY));
        System.out.println("MINUTE: " + calendar.get(Calendar.MINUTE));
        System.out.println("SECOND: " + calendar.get(Calendar.SECOND));
        System.out.println("MILLISECOND: " + calendar.get(Calendar.MILLISECOND));
        System.out.println("ZONE_OFFSET: "
                           + (calendar.get(Calendar.ZONE_OFFSET)/(60*60*1000)));
        System.out.println("DST_OFFSET: "
                           + (calendar.get(Calendar.DST_OFFSET)/(60*60*1000)));

        System.out.println("Current Time, with hour reset to 3");
        calendar.clear(Calendar.HOUR_OF_DAY); // so doesn't override
        calendar.set(Calendar.HOUR, 3);
        System.out.println("ERA: " + calendar.get(Calendar.ERA));
        System.out.println("YEAR: " + calendar.get(Calendar.YEAR));
        System.out.println("MONTH: " + calendar.get(Calendar.MONTH));
        System.out.println("WEEK_OF_YEAR: " + calendar.get(Calendar.WEEK_OF_YEAR));
        System.out.println("WEEK_OF_MONTH: " + calendar.get(Calendar.WEEK_OF_MONTH));
        System.out.println("DATE: " + calendar.get(Calendar.DATE));
        System.out.println("DAY_OF_MONTH: " + calendar.get(Calendar.DAY_OF_MONTH));
        System.out.println("DAY_OF_YEAR: " + calendar.get(Calendar.DAY_OF_YEAR));
        System.out.println("DAY_OF_WEEK: " + calendar.get(Calendar.DAY_OF_WEEK));
        System.out.println("DAY_OF_WEEK_IN_MONTH: "
                           + calendar.get(Calendar.DAY_OF_WEEK_IN_MONTH));
        System.out.println("AM_PM: " + calendar.get(Calendar.AM_PM));
        System.out.println("HOUR: " + calendar.get(Calendar.HOUR));
        System.out.println("HOUR_OF_DAY: " + calendar.get(Calendar.HOUR_OF_DAY));
        System.out.println("MINUTE: " + calendar.get(Calendar.MINUTE));
        System.out.println("SECOND: " + calendar.get(Calendar.SECOND));
        System.out.println("MILLISECOND: " + calendar.get(Calendar.MILLISECOND));
        System.out.println("ZONE_OFFSET: "
               + (calendar.get(Calendar.ZONE_OFFSET)/(60*60*1000))); // in hours
        System.out.println("DST_OFFSET: "
               + (calendar.get(Calendar.DST_OFFSET)/(60*60*1000))); // in hours
```

Since:

JDK1.1

See Also:

TimeZone, Serialized Form

Nested Class Summary

Nested classes/interfaces inherited from class java.util.Calendar

Calendar.Builder

Field Summary

Fields

Modifier and Type	Field	Description
static int	**AD**	Value of the ERA field indicating the common era (Anno Domini), also known as CE.
static int	**BC**	Value of the ERA field indicating the period before the common era (before Christ), also known as BCE.

Fields inherited from class java.util.Calendar

ALL_STYLES, AM, AM_PM, APRIL, areFieldsSet, AUGUST, DATE, DAY_OF_MONTH, DAY_OF_WEEK, DAY_OF_WEEK_IN_MONTH, DAY_OF_YEAR, DECEMBER, DST_OFFSET, ERA, FEBRUARY, FIELD_COUNT, fields, FRIDAY, HOUR, HOUR_OF_DAY, isSet, isTimeSet, JANUARY, JULY, JUNE, LONG, LONG_FORMAT, LONG_STANDALONE, MARCH, MAY, MILLISECOND, MINUTE, MONDAY, MONTH, NARROW_FORMAT, NARROW_STANDALONE, NOVEMBER, OCTOBER, PM, SATURDAY, SECOND, SEPTEMBER, SHORT, SHORT_FORMAT, SHORT_STANDALONE, SUNDAY, THURSDAY, time, TUESDAY, UNDECIMBER, WEDNESDAY, WEEK_OF_MONTH, WEEK_OF_YEAR, YEAR, ZONE_OFFSET

Constructor Summary

Constructors

Constructor

```
GregorianCalendar()
```

```
GregorianCalendar(int year, int month, int dayOfMonth)
```

```
GregorianCalendar(int year, int month, int dayOfMonth, int hourOfDay, int minute
```

```
GregorianCalendar(int year, int month, int dayOfMonth, int hourOfDay, int minute,
```

```
GregorianCalendar(Locale aLocale)
```

```
GregorianCalendar(TimeZone zone)
```

```
GregorianCalendar(TimeZone zone, Locale aLocale)
```

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	**add**(int field, int amount)	Adds the specified (signed) amount of time to the given calendar field, based on the calendar's rules.
Object	**clone**()	Creates and returns a copy o this object.
protected void	**computeFields**()	Converts the time value (millisecond offset from the **Epoch**) to calendar field values.
protected void	**computeTime**()	Converts calendar field values to the time value (millisecond offset from the **Epoch**).
boolean	**equals**(**Object** obj)	Compares this `GregorianCalendar` to the specified `Object`.
static **GregorianCalendar**	**from**(**ZonedDateTime** zdt)	Obtains an instance of `GregorianCalendar` with the default locale from a `ZonedDateTime` object.
int	**getActualMaximum**(int field)	Returns the maximum value that this calendar field could have, taking into consideration the given time value and the current values of the **getFirstDayOfWeek**, **getMinimalDaysInFirstWee**

		getGregorianChange and **getTimeZone** methods.
int	**getActualMinimum**(int field)	Returns the minimum value that this calendar field could have, taking into consideration the given time value and the current values of the **getFirstDayOfWeek**, **getMinimalDaysInFirstWee** **getGregorianChange** and **getTimeZone** methods.
String	**getCalendarType**()	Returns "gregory" as the calendar type.
int	**getGreatestMinimum**(int field)	Returns the highest minimum value for the given calendar field of this GregorianCalendar instance
Date	**getGregorianChange**()	Gets the Gregorian Calendar change date.
int	**getLeastMaximum**(int field)	Returns the lowest maximum value for the given calendar field of this GregorianCalendar instance
int	**getMaximum**(int field)	Returns the maximum value for the given calendar field o this GregorianCalendar instance.
int	**getMinimum**(int field)	Returns the minimum value for the given calendar field o this GregorianCalendar instance.
TimeZone	**getTimeZone**()	Gets the time zone.
int	**getWeeksInWeekYear**()	Returns the number of weeks in the **week year** represente by this GregorianCalendar.
int	**getWeekYear**()	Returns the **week year** represented by this GregorianCalendar.
int	**hashCode**()	

		Generates the hash code for this GregorianCalendar object.
boolean	**isLeapYear**(int year)	Determines if the given year is a leap year.
boolean	**isWeekDateSupported**()	Returns true indicating this GregorianCalendar supports week dates.
void	**roll**(int field, boolean up)	Adds or subtracts (up/down) single unit of time on the given time field without changing larger fields.
void	**roll**(int field, int amount)	Adds a signed amount to the specified calendar field without changing larger fields.
void	**setGregorianChange**(**Date** date)	Sets the GregorianCalendar change date.
void	**setTimeZone**(**TimeZone** zone)	Sets the time zone with the given time zone value.
void	**setWeekDate**(int weekYear, int weekOfYear, int dayOfWeek)	Sets this GregorianCalendar to the date given by the date specifiers - **weekYear**, weekOfYear, and dayOfWeek.
ZonedDateTime	**toZonedDateTime**()	Converts this object to a ZonedDateTime that represents the same point on the time-line as this GregorianCalendar.

Methods inherited from class java.util.Calendar

after, before, clear, clear, compareTo, complete, get, getAvailableCalendarTypes, getAvailableLocales, getDisplayName, getDisplayNames, getFirstDayOfWeek, getInstance, getInstance, getInstance, getInstance, getMinimalDaysInFirstWeek, getTime, getTimeInMillis, internalGet, isLenient, isSet, set, set, set, set, setFirstDayOfWeek, setLenient, setMinimalDaysInFirstWeek, setTime, setTimeInMillis, toInstant, toString

Methods inherited from class java.lang.Object

finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

BC

```
public static final int BC
```

Value of the ERA field indicating the period before the common era (before Christ), also known as BCE. The sequence of years at the transition from BC to AD is ..., 2 BC, 1 BC, 1 AD, 2 AD,...

See Also:

Calendar.ERA, Constant Field Values

AD

```
public static final int AD
```

Value of the ERA field indicating the common era (Anno Domini), also known as CE. The sequence of years at the transition from BC to AD is ..., 2 BC, 1 BC, 1 AD, 2 AD,...

See Also:

Calendar.ERA, Constant Field Values

Constructor Detail

GregorianCalendar

```
public GregorianCalendar()
```

Constructs a default GregorianCalendar using the current time in the default time zone with the default FORMAT locale.

GregorianCalendar

```
public GregorianCalendar(TimeZone zone)
```

Constructs a GregorianCalendar based on the current time in the given time zone with the default FORMAT locale.

Parameters:

zone - the given time zone.

GregorianCalendar

```
public GregorianCalendar(Locale aLocale)
```

Constructs a GregorianCalendar based on the current time in the default time zone with the given locale.

Parameters:

aLocale - the given locale.

GregorianCalendar

```
public GregorianCalendar(TimeZone zone,
                         Locale aLocale)
```

Constructs a GregorianCalendar based on the current time in the given time zone with the given locale.

Parameters:

zone - the given time zone.

aLocale - the given locale.

GregorianCalendar

```
public GregorianCalendar(int year,
                         int month,
                         int dayOfMonth)
```

Constructs a GregorianCalendar with the given date set in the default time zone with the default locale.

Parameters:

year - the value used to set the YEAR calendar field in the calendar.

month - the value used to set the MONTH calendar field in the calendar. Month value is 0-based. e.g., 0 for January.

dayOfMonth - the value used to set the DAY_OF_MONTH calendar field in the calendar.

GregorianCalendar

```
public GregorianCalendar(int year,
                         int month,
                         int dayOfMonth,
                         int hourOfDay,
                         int minute)
```

Constructs a `GregorianCalendar` with the given date and time set for the default time zone with the default locale.

Parameters:

`year` - the value used to set the YEAR calendar field in the calendar.

`month` - the value used to set the MONTH calendar field in the calendar. Month value is 0-based. e.g., 0 for January.

`dayOfMonth` - the value used to set the DAY_OF_MONTH calendar field in the calendar.

`hourOfDay` - the value used to set the HOUR_OF_DAY calendar field in the calendar.

`minute` - the value used to set the MINUTE calendar field in the calendar.

GregorianCalendar

```
public GregorianCalendar(int year,
                         int month,
                         int dayOfMonth,
                         int hourOfDay,
                         int minute,
                         int second)
```

Constructs a GregorianCalendar with the given date and time set for the default time zone with the default locale.

Parameters:

`year` - the value used to set the YEAR calendar field in the calendar.

`month` - the value used to set the MONTH calendar field in the calendar. Month value is 0-based. e.g., 0 for January.

`dayOfMonth` - the value used to set the DAY_OF_MONTH calendar field in the calendar.

`hourOfDay` - the value used to set the HOUR_OF_DAY calendar field in the calendar.

minute - the value used to set the MINUTE calendar field in the calendar.

second - the value used to set the SECOND calendar field in the calendar.

Method Detail

setGregorianChange

```
public void setGregorianChange(Date date)
```

Sets the GregorianCalendar change date. This is the point when the switch from Julian dates to Gregorian dates occurred. Default is October 15, 1582 (Gregorian). Previous to this, dates will be in the Julian calendar.

To obtain a pure Julian calendar, set the change date to Date(Long.MAX_VALUE). To obtain a pure Gregorian calendar, set the change date to Date(Long.MIN_VALUE).

Parameters:

date - the given Gregorian cutover date.

getGregorianChange

```
public final Date getGregorianChange()
```

Gets the Gregorian Calendar change date. This is the point when the switch from Julian dates to Gregorian dates occurred. Default is October 15, 1582 (Gregorian). Previous to this, dates will be in the Julian calendar.

Returns:

the Gregorian cutover date for this GregorianCalendar object.

isLeapYear

```
public boolean isLeapYear(int year)
```

Determines if the given year is a leap year. Returns true if the given year is a leap year. To specify BC year numbers, 1 - year number must be given. For example, year BC 4 is specified as -3.

Parameters:

year - the given year.

Returns:

true if the given year is a leap year; false otherwise.

getCalendarType

```
public String getCalendarType()
```

Returns "gregory" as the calendar type.

Overrides:

getCalendarType in class Calendar

Returns:

"gregory"

Since:

1.8

See Also:

Locale extensions, Locale.Builder.setLocale(Locale), Locale.Builder.setUnicodeLocaleKeyword(String, String)

equals

```
public boolean equals(Object obj)
```

Compares this GregorianCalendar to the specified Object. The result is true if and only if the argument is a GregorianCalendar object that represents the same time value (millisecond offset from the Epoch) under the same Calendar parameters and Gregorian change date as this object.

Overrides:

equals in class Calendar

Parameters:

obj - the object to compare with.

Returns:

true if this object is equal to obj; false otherwise.

See Also:

Calendar.compareTo(Calendar)

hashCode

```
public int hashCode()
```

Generates the hash code for this GregorianCalendar object.

Overrides:

hashCode in class Calendar

Returns:

a hash code value for this object.

See Also:

Object.equals(java.lang.Object), System.identityHashCode(java.lang.Object)

add

```
public void add(int field,
                int amount)
```

Adds the specified (signed) amount of time to the given calendar field, based on the calendar's rules.

Add rule 1. The value of `field` after the call minus the value of `field` before the call is `amount`, modulo any overflow that has occurred in `field`. Overflow occurs when a field value exceeds its range and, as a result, the next larger field is incremented or decremented and the field value is adjusted back into its range.

Add rule 2. If a smaller field is expected to be invariant, but it is impossible for it to be equal to its prior value because of changes in its minimum or maximum after `field` is changed, then its value is adjusted to be as close as possible to its expected value. A smaller field represents a smaller unit of time. `HOUR` is a smaller field than `DAY_OF_MONTH`. No adjustment is made to smaller fields that are not expected to be invariant. The calendar system determines what fields are expected to be invariant.

Specified by:

add in class Calendar

Parameters:

field - the calendar field.

amount - the amount of date or time to be added to the field.

Throws:

IllegalArgumentException - if field is ZONE_OFFSET, DST_OFFSET, or unknown, or if any calendar fields have out-of-range values in non-lenient mode.

See Also:

Calendar.roll(int,int), Calendar.set(int,int)

roll

```
public void roll(int field,
                 boolean up)
```

Adds or subtracts (up/down) a single unit of time on the given time field without changing larger fields.

Example: Consider a `GregorianCalendar` originally set to December 31, 1999. Calling `roll(Calendar.MONTH, true)` sets the calendar to January 31, 1999. The `YEAR` field is unchanged because it is a larger field than `MONTH`.

Specified by:

`roll` in class `Calendar`

Parameters:

`up - indicates if the value of the specified calendar field is to be rolled up or rolled down. Use true if rolling up, false otherwise.`

`field - the time field.`

Throws:

`IllegalArgumentException - if field is ZONE_OFFSET, DST_OFFSET, or unknown, or if any calendar fields have out-of-range values in non-lenient mode.`

See Also:

`add(int,int)`, `Calendar.set(int,int)`

roll

```
public void roll(int field,
                 int amount)
```

Adds a signed amount to the specified calendar field without changing larger fields. A negative roll amount means to subtract from field without changing larger fields. If the specified amount is 0, this method performs nothing.

This method calls `Calendar.complete()` before adding the amount so that all the calendar fields are normalized. If there is any calendar field having an out-of-range value in non-lenient mode, then an `IllegalArgumentException` is thrown.

Example: Consider a `GregorianCalendar` originally set to August 31, 1999. Calling `roll(Calendar.MONTH, 8)` sets the calendar to April 30, **1999**. Using a `GregorianCalendar`, the `DAY_OF_MONTH` field cannot be 31 in the month April. `DAY_OF_MONTH` is set to the closest possible value, 30. The `YEAR` field maintains the value of 1999 because it is a larger field than `MONTH`.

Example: Consider a GregorianCalendar originally set to Sunday June 6, 1999. Calling roll(Calendar.WEEK_OF_MONTH, -1) sets the calendar to Tuesday June 1, 1999, whereas calling add(Calendar.WEEK_OF_MONTH, -1) sets the calendar to Sunday May 30, 1999. This is because the roll rule imposes an additional constraint: The MONTH must not change when the WEEK_OF_MONTH is rolled. Taken together with add rule 1, the resultant date must be between Tuesday June 1 and Saturday June 5. According to add rule 2, the DAY_OF_WEEK, an invariant when changing the WEEK_OF_MONTH, is set to Tuesday, the closest possible value to Sunday (where Sunday is the first day of the week).

Overrides:

roll in class Calendar

Parameters:

field - the calendar field.

amount - the signed amount to add to field.

Throws:

IllegalArgumentException - if field is ZONE_OFFSET, DST_OFFSET, or unknown, or if any calendar fields have out-of-range values in non-lenient mode.

Since:

1.2

See Also:

roll(int,boolean), add(int,int), Calendar.set(int,int)

getMinimum

```
public int getMinimum(int field)
```

Returns the minimum value for the given calendar field of this GregorianCalendar instance. The minimum value is defined as the smallest value returned by the get method for any possible time value, taking into consideration the current values of the getFirstDayOfWeek, getMinimalDaysInFirstWeek, getGregorianChange and getTimeZone methods.

Specified by:

getMinimum in class Calendar

Parameters:

field - the calendar field.

Returns:

the minimum value for the given calendar field.

See Also:

getMaximum(int), getGreatestMinimum(int), getLeastMaximum(int), getActualMinimum(int), getActualMaximum(int)

getMaximum

public int getMaximum(int field)

Returns the maximum value for the given calendar field of this GregorianCalendar instance. The maximum value is defined as the largest value returned by the get method for any possible time value, taking into consideration the current values of the getFirstDayOfWeek, getMinimalDaysInFirstWeek, getGregorianChange and getTimeZone methods.

Specified by:

getMaximum in class Calendar

Parameters:

field - the calendar field.

Returns:

the maximum value for the given calendar field.

See Also:

getMinimum(int), getGreatestMinimum(int), getLeastMaximum(int), getActualMinimum(int), getActualMaximum(int)

getGreatestMinimum

```
public int getGreatestMinimum(int field)
```

Returns the highest minimum value for the given calendar field of this `GregorianCalendar` instance. The highest minimum value is defined as the largest value returned by `getActualMinimum(int)` for any possible time value, taking into consideration the current values of the `getFirstDayOfWeek`, `getMinimalDaysInFirstWeek`, `getGregorianChange` and `getTimeZone` methods.

Specified by:

`getGreatestMinimum` in class `Calendar`

Parameters:

`field` - the calendar field.

Returns:

the highest minimum value for the given calendar field.

See Also:

`getMinimum(int)`, `getMaximum(int)`, `getLeastMaximum(int)`, `getActualMinimum(int)`, `getActualMaximum(int)`

getLeastMaximum

```
public int getLeastMaximum(int field)
```

Returns the lowest maximum value for the given calendar field of this `GregorianCalendar` instance. The lowest maximum value is defined as the smallest value returned by `getActualMaximum(int)` for any possible time value, taking into consideration the current values of the `getFirstDayOfWeek`, `getMinimalDaysInFirstWeek`, `getGregorianChange` and `getTimeZone` methods.

Specified by:

`getLeastMaximum` in class `Calendar`

Parameters:

`field` - the calendar field

Returns:

the lowest maximum value for the given calendar field.

See Also:

`getMinimum(int)`, `getMaximum(int)`, `getGreatestMinimum(int)`, `getActualMinimum(int)`, `getActualMaximum(int)`

getActualMinimum

```
public int getActualMinimum(int field)
```

Returns the minimum value that this calendar field could have, taking into consideration the given time value and the current values of the `getFirstDayOfWeek`, `getMinimalDaysInFirstWeek`, `getGregorianChange` and `getTimeZone` methods.

For example, if the Gregorian change date is January 10, 1970 and the date of this `GregorianCalendar` is January 20, 1970, the actual minimum value of the `DAY_OF_MONTH` field is 10 because the previous date of January 10, 1970 is December 27, 1996 (in the Julian calendar). Therefore, December 28, 1969 to January 9, 1970 don't exist.

Overrides:

`getActualMinimum` in class `Calendar`

Parameters:

`field - the calendar field`

Returns:

`the minimum of the given field for the time value of this GregorianCalendar`

Since:

`1.2`

See Also:

`getMinimum(int)`, `getMaximum(int)`, `getGreatestMinimum(int)`, `getLeastMaximum(int)`, `getActualMaximum(int)`

getActualMaximum

```
public int getActualMaximum(int field)
```

Returns the maximum value that this calendar field could have, taking into consideration the given time value and the current values of the `getFirstDayOfWeek`, `getMinimalDaysInFirstWeek`, `getGregorianChange` and `getTimeZone` methods. For example, if the date of this instance is February 1, 2004, the actual maximum value of the `DAY_OF_MONTH` field is 29 because 2004 is a leap year, and if the date of this instance is February 1, 2005, it's 28.

This method calculates the maximum value of `WEEK_OF_YEAR` based on the `YEAR` (calendar year) value, not the week year. Call `getWeeksInWeekYear()` to get the maximum value of `WEEK_OF_YEAR` in the week year of this `GregorianCalendar`.

Overrides:

getActualMaximum in class Calendar

Parameters:

field - the calendar field

Returns:

the maximum of the given field for the time value of this GregorianCalendar

Since:

1.2

See Also:

getMinimum(int), getMaximum(int), getGreatestMinimum(int), getLeastMaximum(int), getActualMinimum(int)

clone

public Object clone()

Description copied from class: Calendar

Creates and returns a copy of this object.

Overrides:

clone in class Calendar

Returns:

a copy of this object.

See Also:

Cloneable

getTimeZone

public TimeZone getTimeZone()

Description copied from class: Calendar

Gets the time zone.

Overrides:

getTimeZone in class Calendar

Returns:

the time zone object associated with this calendar.

setTimeZone

public void setTimeZone(TimeZone zone)

Description copied from class: Calendar

Sets the time zone with the given time zone value.

Overrides:

setTimeZone in class Calendar

Parameters:

zone - the given time zone.

isWeekDateSupported

```
public final boolean isWeekDateSupported()
```

Returns true indicating this GregorianCalendar supports week dates.

Overrides:

isWeekDateSupported in class Calendar

Returns:

true (always)

Since:

1.7

See Also:

getWeekYear(), setWeekDate(int,int,int), getWeeksInWeekYear()

getWeekYear

```
public int getWeekYear()
```

Returns the week year represented by this GregorianCalendar. The dates in the weeks between 1 and the maximum week number of the week year have the same week year value that may be one year before or after the YEAR (calendar year) value.

This method calls Calendar.complete() before calculating the week year.

Overrides:

getWeekYear in class Calendar

Returns:

the week year represented by this GregorianCalendar. If the ERA value is BC, the year is represented by 0 or a negative number: BC 1 is 0, BC 2 is -1, BC 3 is -2, and so on.

Throws:

IllegalArgumentException - if any of the calendar fields is invalid in non-lenient mode.

Since:

1.7

See Also:

isWeekDateSupported(), getWeeksInWeekYear(), Calendar.getFirstDayOfWeek(), Calendar.getMinimalDaysInFirstWeek()

setWeekDate

```
public void setWeekDate(int weekYear,
                        int weekOfYear,
                        int dayOfWeek)
```

Sets this GregorianCalendar to the date given by the date specifiers - weekYear, weekOfYear, and dayOfWeek. weekOfYear follows the WEEK_OF_YEAR numbering. The dayOfWeek value must be one of the DAY_OF_WEEK values: SUNDAY to SATURDAY.

Note that the numeric day-of-week representation differs from the ISO 8601 standard, and that the weekOfYear numbering is compatible with the standard when getFirstDayOfWeek() is MONDAY and getMinimalDaysInFirstWeek() is 4.

Unlike the set method, all of the calendar fields and the instant of time value are calculated upon return.

If weekOfYear is out of the valid week-of-year range in weekYear, the weekYear and weekOfYear values are adjusted in lenient mode, or an IllegalArgumentException is thrown in non-lenient mode.

Overrides:

setWeekDate in class Calendar

Parameters:

weekYear - the week year

weekOfYear - the week number based on weekYear

dayOfWeek - the day of week value: one of the constants for the DAY_OF_WEEK field: SUNDAY, ..., SATURDAY.

Throws:

IllegalArgumentException - if any of the given date specifiers is invalid, or if any of the calendar fields are inconsistent with the given date specifiers in non-lenient mode

Since:

1.7

See Also:

isWeekDateSupported(), Calendar.getFirstDayOfWeek(), Calendar.getMinimalDaysInFirstWeek()

getWeeksInWeekYear

```
public int getWeeksInWeekYear()
```

Returns the number of weeks in the week year represented by this `GregorianCalendar`.

For example, if this `GregorianCalendar`'s date is December 31, 2008 with the ISO 8601 compatible setting, this method will return 53 for the period: December 29, 2008 to January 3, 2010 while `getActualMaximum(WEEK_OF_YEAR)` will return 52 for the period: December 31, 2007 to December 28, 2008.

Overrides:

`getWeeksInWeekYear` in class `Calendar`

Returns:

the number of weeks in the week year.

Since:

1.7

See Also:

`Calendar.WEEK_OF_YEAR`, `getWeekYear()`, `getActualMaximum(int)`

computeFields

```
protected void computeFields()
```

Converts the time value (millisecond offset from the Epoch) to calendar field values. The time is *not* recomputed first; to recompute the time, then the fields, call the `complete` method.

Specified by:

`computeFields` in class `Calendar`

See Also:

`Calendar.complete()`

computeTime

```
protected void computeTime()
```

Converts calendar field values to the time value (millisecond offset from the Epoch).

Specified by:

`computeTime` in class `Calendar`

Throws:

`IllegalArgumentException` - if any calendar fields are invalid.

See Also:

`Calendar.complete()`, `Calendar.computeFields()`

toZonedDateTime

```
public ZonedDateTime toZonedDateTime()
```

Converts this object to a `ZonedDateTime` that represents the same point on the time-line as this `GregorianCalendar`.

Since this object supports a Julian-Gregorian cutover date and `ZonedDateTime` does not, it is possible that the resulting year, month and day will have different values. The result will represent the correct date in the ISO calendar system, which will also be the same value for Modified Julian Days.

Returns:

a zoned date-time representing the same point on the time-line as this gregorian calendar

Since:

1.8

from

```
public static GregorianCalendar from(ZonedDateTime zdt)
```

Obtains an instance of `GregorianCalendar` with the default locale from a `ZonedDateTime` object.

Since `ZonedDateTime` does not support a Julian-Gregorian cutover date and uses ISO calendar system, the return GregorianCalendar is a pure Gregorian calendar and uses ISO 8601 standard for week definitions, which has `MONDAY` as the `FirstDayOfWeek` and 4 as the value of the `MinimalDaysInFirstWeek`.

`ZoneDateTime` can store points on the time-line further in the future and further in the past than `GregorianCalendar`. In this scenario, this method will throw an `IllegalArgumentException` exception.

Parameters:

zdt - the zoned date-time object to convert

Returns:

the gregorian calendar representing the same point on the time-line as the zoned date-time provided

Throws:

`NullPointerException` - if zdt is null

`IllegalArgumentException` - if the zoned date-time is too large to represent as a GregorianCalendar

Since:

1.8

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.