JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface UnaryOperator<T>

Type Parameters:

T - the type of the operand and result of the operator

All Superinterfaces:

Function<T,T>

Functional Interface:

This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.

```
@FunctionalInterface
public interface UnaryOperator<T>
extends Function<T,T>
```

Represents an operation on a single operand that produces a result of the same type as its operand. This is a specialization of `Function` for the case where the operand and result are of the same type.

This is a functional interface whose functional method is `Function.apply(Object)`.

Since:

1.8

See Also:

Function

Method Summary

Static Methods

Modifier and Type	Method	Description
static <T> UnaryOperator <T>	**identity**()	Returns a unary operator that always returns its input argument.

Methods declared in interface Function

`andThen`, `apply`, `compose`

Method Details

identity

```
static <T> UnaryOperator<T> identity()
```

Returns a unary operator that always returns its input argument.

Type Parameters:

T - the type of the input and output of the operator

Returns:

a unary operator that always returns its input argument

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.