JavaScript is disabled on your browser.

Class LongSummaryStatistics

java.lang.Object
    java.util.LongSummaryStatistics

All Implemented Interfaces:

IntConsumer, LongConsumer

```
public class LongSummaryStatistics
extends Object
implements LongConsumer, IntConsumer
```

A state object for collecting statistics such as count, min, max, sum, and average.

This class is designed to work with (though does not require) streams. For example, you can compute summary statistics on a stream of longs with:

```
LongSummaryStatistics stats = longStream.collect(LongSummaryStatistics::new,
                                                 LongSummaryStatistics::accept,
                                                 LongSummaryStatistics::combine);
```

LongSummaryStatistics can be used as a Stream.collect(Collector) reduction} target for a stream. For example:

```
LongSummaryStatistics stats = people.stream()
                                    .collect(Collectors.summarizingLong(Person::ge
```

This computes, in a single pass, the count of people, as well as the minimum, maximum, sum, and average of their ages.

Implementation Note:

This implementation is not thread safe. However, it is safe to use `Collectors.toLongStatistics()` on a parallel stream, because the parallel implementation of `Stream.collect()` provides the necessary partitioning, isolation, and merging of results for safe and efficient parallel execution.

This implementation does not check for overflow of the sum.

Since:

1.8

Constructor Summary

Constructors

Constructor	Description
`LongSummaryStatistics()`	Construct an empty instance with zero count, zero sum, `Long.MAX_VALUE` min, `Long.MIN_VALUE` max and zero average.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	`accept(int value)`	Records a new `int` value into the summary information.
void	`accept(long value)`	Records a new `long` value into the summary information.
void	`combine(LongSummaryStatistics other)`	Combines the state of another `LongSummaryStatistics` into this one.
double	`getAverage()`	Returns the arithmetic mean of values recorded, or zero if no values have been recorded.

long	**getCount**()	Returns the count of values recorded.
long	**getMax**()	Returns the maximum value recorded, or `Long.MIN_VALUE` if no values have been recorded
long	**getMin**()	Returns the minimum value recorded, or `Long.MAX_VALUE` if no values have been recorded.
long	**getSum**()	Returns the sum of values recorded, or zero if no values have been recorded.
String	**toString**()	Returns a string representation of the object.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Methods inherited from interface java.util.function.LongConsumer

andThen

Methods inherited from interface java.util.function.IntConsumer

andThen

Constructor Detail

LongSummaryStatistics

```
public LongSummaryStatistics()
```

Construct an empty instance with zero count, zero sum, `Long.MAX_VALUE` min, `Long.MIN_VALUE` max and zero average.

Method Detail

accept

```
public void accept(int value)
```

Records a new `int` value into the summary information.

Specified by:

`accept` in interface `IntConsumer`

Parameters:

`value` - the input value

accept

```
public void accept(long value)
```

Records a new `long` value into the summary information.

Specified by:

`accept` in interface `LongConsumer`

Parameters:

`value` - the input value

combine

```
public void combine(LongSummaryStatistics other)
```

Combines the state of another `LongSummaryStatistics` into this one.

Parameters:

`other` - another `LongSummaryStatistics`

Throws:

`NullPointerException` - if other is null

getCount

```
public final long getCount()
```

Returns the count of values recorded.

Returns:

`the count of values`

getSum

```
public final long getSum()
```

Returns the sum of values recorded, or zero if no values have been recorded.

Returns:

`the sum of values, or zero if none`

getMin

```
public final long getMin()
```

Returns the minimum value recorded, or `Long.MAX_VALUE` if no values have been recorded.

Returns:

`the minimum value, or Long.MAX_VALUE if none`

getMax

```
public final long getMax()
```

Returns the maximum value recorded, or `Long.MIN_VALUE` if no values have been recorded

Returns:

`the maximum value, or Long.MIN_VALUE if none`

getAverage

```
public final double getAverage()
```

Returns the arithmetic mean of values recorded, or zero if no values have been recorded.

Returns:

`The arithmetic mean of values, or zero if none`

toString

```
public String toString()
```

Description copied from class: Object

Returns a string representation of the object. In general, the `toString` method returns a string that "textually represents" this object. The result should be a concise but informative representation that is easy for a person to read. It is recommended that all subclasses override this method.

The `toString` method for class `Object` returns a string consisting of the name of the class of which the object is an instance, the at-sign character `@', and the unsigned hexadecimal representation of the hash code of the object. In other words, this method returns a string equal to the value of:

```
getClass().getName() + '@' + Integer.toHexString(hashCode())
```

Overrides:

`toString` in class `Object`

Returns:

a string representation of the object.

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.