JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.function

Interface Predicate<T>

Type Parameters:

`T - the type of the input to the predicate`

Functional Interface:

`This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.`

```
@FunctionalInterface
public interface Predicate<T>
```

Represents a predicate (boolean-valued function) of one argument.

This is a functional interface whose functional method is `test(Object)`.

Since:

1.8

Method Summary

Abstract Methods | **Default Methods**

Modifier and Type	Method	Description
`default Predicate<T>`	`and(Predicate<? super T> other)`	Returns a composed predicate that represents a short-circuiting logical AND of this predicate and another.

static <T> **Predicate**<T>	**isEqual**(**Object** targetRef)	Returns a predicate that tests if two arguments are equal according to **Objects.equals(Object, Object)**.
default **Predicate**<**T**>	**negate**()	Returns a predicate that represents the logical negation of this predicate.
default **Predicate**<**T**>	**or**(**Predicate**<? super **T**> other)	Returns a composed predicate that represents a short-circuiting logical OR of this predicate and another.
boolean	**test**(**T** t)	Evaluates this predicate on the given argument.

Method Detail

test

`boolean test(T t)`

Evaluates this predicate on the given argument.

Parameters:

`t - the input argument`

Returns:

`true if the input argument matches the predicate, otherwise false`

and

`default Predicate<T> and(Predicate<? super T> other)`

Returns a composed predicate that represents a short-circuiting logical AND of this predicate and another. When evaluating the composed predicate, if this predicate is `false`, then the `other` predicate is not evaluated.

Any exceptions thrown during evaluation of either predicate are relayed to the caller; if evaluation of this predicate throws an exception, the `other` predicate will not be evaluated.

Parameters:

other - a predicate that will be logically-ANDed with this predicate

Returns:

a composed predicate that represents the short-circuiting logical AND of this predicate and the other predicate

Throws:

NullPointerException - if other is null

negate

```
default Predicate<T> negate()
```

Returns a predicate that represents the logical negation of this predicate.

Returns:

a predicate that represents the logical negation of this predicate

or

```
default Predicate<T> or(Predicate<? super T> other)
```

Returns a composed predicate that represents a short-circuiting logical OR of this predicate and another. When evaluating the composed predicate, if this predicate is `true`, then the `other` predicate is not evaluated.

Any exceptions thrown during evaluation of either predicate are relayed to the caller; if evaluation of this predicate throws an exception, the `other` predicate will not be evaluated.

Parameters:

other - a predicate that will be logically-ORed with this predicate

Returns:

a composed predicate that represents the short-circuiting logical OR of this predicate and the other predicate

Throws:

NullPointerException - if other is null

isEqual

```
static <T> Predicate<T> isEqual(Object targetRef)
```

Returns a predicate that tests if two arguments are equal according to Objects.equals(Object, Object).

Type Parameters:

`T - the type of arguments to the predicate`

Parameters:

`targetRef - the object reference with which to compare for equality, which may be null`

Returns:

`a predicate that tests if two arguments are equal according to Objects.equals(Object, Object)`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.