JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.function

Interface UnaryOperator<T>

Type Parameters:

`T - the type of the operand and result of the operator`

All Superinterfaces:

`Function<T,T>`

Functional Interface:

`This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.`

```
@FunctionalInterface
public interface UnaryOperator<T>
extends Function<T,T>
```

Represents an operation on a single operand that produces a result of the same type as its operand. This is a specialization of `Function` for the case where the operand and result are of the same type.

This is a functional interface whose functional method is `Function.apply(Object)`.

Since:

1.8

See Also:

`Function`

Method Summary

Default Methods

Modifier and Type	Method	Description
static <T> UnaryOperator<T>	identity()	Returns a unary operator that always returns its input argument.

Methods inherited from interface java.util.function.Function

andThen, apply, compose

Method Detail

identity

```
static <T> UnaryOperator<T> identity()
```

Returns a unary operator that always returns its input argument.

Specified by:

identity in interface Function<T,T>

Type Parameters:

T - the type of the input and output of the operator

Returns:

a unary operator that always returns its input argument

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.