JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class IOError

java.lang.Object
    java.lang.Throwable
        java.lang.Error
            java.io.IOError

All Implemented Interfaces:

Serializable

```
public class IOError
extends Error
```

Thrown when a serious I/O error has occurred.

Since:

1.6

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IOError(Throwable cause)`	Constructs a new instance of IOError with the specified cause.

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

IOError

```
public IOError(Throwable cause)
```

Constructs a new instance of IOError with the specified cause. The IOError is created with the detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of cause).

Parameters:

`cause` - The cause of this error, or `null` if the cause is not known

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.