JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface ObjectInput

All Superinterfaces:

AutoCloseable, DataInput

All Known Implementing Classes:

ObjectInputStream

```
public interface ObjectInput
extends DataInput, AutoCloseable
```

ObjectInput extends the DataInput interface to include the reading of objects. DataInput includes methods for the input of primitive types, ObjectInput extends that interface to include objects, arrays, and Strings.

Since:

1.1

See Also:

InputStream, ObjectOutputStream, ObjectInputStream

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
int	**available**()	Returns the number of bytes that can be read without blocking.
void	**close**()	Closes the input stream.
int	**read**()	Reads a byte of data.
int	**read**(byte[] b)	Reads into an array of bytes.
int	**read**(byte[] b, int off, int len)	Reads into an array of bytes.
Object	**readObject**()	Read and return an object.
long	**skip**(long n)	Skips n bytes of input.

Methods declared in interface DataInput

readBoolean, readByte, readChar, readDouble, readFloat, readFully, readFully, readInt, readLine, readLong, readShort, readUnsignedByte, readUnsignedShort, readUTF, skipBytes

Method Details

readObject

```
Object readObject()
           throws ClassNotFoundException,
                  IOException
```

Read and return an object. The class that implements this interface defines where the object is "read" from.

Returns:

the object read from the stream

Throws:

ClassNotFoundException - If the class of a serialized object cannot be found.

IOException - If any of the usual Input/Output related exceptions occur.

read

```
int read()
  throws IOException
```

Reads a byte of data. This method will block if no input is available.

Returns:

the byte read, or -1 if the end of the stream is reached.

Throws:

IOException - If an I/O error has occurred.

read

```
int read(byte[] b)
  throws IOException
```

Reads into an array of bytes. This method will block until some input is available.

Parameters:

b - the buffer into which the data is read

Returns:

the total number of bytes read into the buffer, or `-1` if there is no more data because the end of the stream has been reached.

Throws:

`IOException` - If an I/O error has occurred.

read

```
int read(byte[] b,
         int off,
         int len)
  throws IOException
```

Reads into an array of bytes. This method will block until some input is available.

Parameters:

`b` - the buffer into which the data is read

`off` - the start offset of the data

`len` - the maximum number of bytes read

Returns:

the total number of bytes read into the buffer, or `-1` if there is no more data because the end of the stream has been reached.

Throws:

`IOException` - If an I/O error has occurred.

`IndexOutOfBoundsException` - If `off` is negative, `len` is negative, or `len` is greater than `b.length - off`

skip

```
long skip(long n)
   throws IOException
```

Skips n bytes of input.

Parameters:

`n` - the number of bytes to be skipped

Returns:

the actual number of bytes skipped.

Throws:

`IOException` - If an I/O error has occurred.

available

```
int available()
       throws IOException
```

Returns the number of bytes that can be read without blocking.

Returns:

the number of available bytes.

Throws:

`IOException` - If an I/O error has occurred.

close

```
void close()
    throws IOException
```

Closes the input stream. Must be called to release any resources associated with the stream.

Specified by:

`close` in interface `AutoCloseable`

Throws:

`IOException` - If an I/O error has occurred.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.