JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class ObjectOutputStream.PutField

java.lang.Object
    java.io.ObjectOutputStream.PutField

Enclosing class:

ObjectOutputStream

```
public abstract static class ObjectOutputStream.PutField
extends Object
```

Provide programmatic access to the persistent fields to be written to ObjectOutput.

Since:

1.2

Constructor Summary

Constructors

Constructor	Description
PutField()	Constructor for subclasses to call.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
abstract void	**put**(String name, boolean val)	Put the value of the named boolean field into the persistent field.
abstract void	**put**(String name, byte val)	Put the value of the named byte field into the persistent field.
abstract void	**put**(String name, char val)	Put the value of the named char field into the persistent field.
abstract void	**put**(String name, double val)	Put the value of the named double field into the persistent field.
abstract void		

	put(String name, float val)	Put the value of the named float field into the persistent field.
abstract void	**put**(String name, int val)	Put the value of the named int field into the persistent field.
abstract void	**put**(String name, long val)	Put the value of the named long field into the persistent field.
abstract void	**put**(String name, short val)	Put the value of the named short field into the persistent field.
abstract void	**put**(String name, Object val)	Put the value of the named Object field into the persistent field.
abstract void	**write**(ObjectOutput out)	**Deprecated, for removal: This API element is subject to removal in a future version.** This method does not write the values contained by this PutField object in a proper format, and may result in corruption of the serialization stream.

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

PutField

```
public PutField()
```

Constructor for subclasses to call.

Method Details

put

```
public abstract void put(String name,
                         boolean val)
```

Put the value of the named boolean field into the persistent field.

Parameters:

`name` - the name of the serializable field

`val` - the value to assign to the field

Throws:

`IllegalArgumentException` - if `name` does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not `boolean`

put

```
public abstract void put(String name,
                         byte val)
```

Put the value of the named byte field into the persistent field.

Parameters:

`name` - the name of the serializable field

`val` - the value to assign to the field

Throws:

`IllegalArgumentException` - if `name` does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not `byte`

put

```
public abstract void put(String name,
                         char val)
```

Put the value of the named char field into the persistent field.

Parameters:

`name` - the name of the serializable field

`val` - the value to assign to the field

Throws:

IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not char

put

```
public abstract void put(String name,
                         short val)
```

Put the value of the named short field into the persistent field.

Parameters:

name - the name of the serializable field

val - the value to assign to the field

Throws:

IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not short

put

```
public abstract void put(String name,
                         int val)
```

Put the value of the named int field into the persistent field.

Parameters:

name - the name of the serializable field

val - the value to assign to the field

Throws:

IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not int

put

```
public abstract void put(String name,
                         long val)
```

Put the value of the named long field into the persistent field.

Parameters:

name - the name of the serializable field

val - the value to assign to the field

Throws:

IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not long

put

```
public abstract void put(String name,
                         float val)
```

Put the value of the named float field into the persistent field.

Parameters:

name - the name of the serializable field

val - the value to assign to the field

Throws:

IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not float

put

```
public abstract void put(String name,
                         double val)
```

Put the value of the named double field into the persistent field.

Parameters:

name - the name of the serializable field

val - the value to assign to the field

Throws:

IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not double

put

```
public abstract void put(String name,
                         Object val)
```

Put the value of the named Object field into the persistent field.

Parameters:

name - the name of the serializable field

val - the value to assign to the field (which may be null)

Throws:

IllegalArgumentException - if name does not match the name of a serializable field for the class whose fields are being written, or if the type of the named field is not a reference type

write

```
@Deprecated(forRemoval=true,
            since="1.4")
public abstract void write(ObjectOutput out)
                    throws IOException
```

Deprecated, for removal: This API element is subject to removal in a future version.
This method does not write the values contained by this `PutField` object in a proper format, and may result in corruption of the serialization stream. The correct way to write `PutField` data is by calling the `ObjectOutputStream.writeFields()` method.

Write the data and fields to the specified ObjectOutput stream, which must be the same stream that produced this `PutField` object.

Parameters:

`out` - the stream to write the data and fields to

Throws:

`IOException` - if I/O errors occur while writing to the underlying stream

`IllegalArgumentException` - if the specified stream is not the same stream that produced this `PutField` object

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.