JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class PipedWriter

java.lang.Object
    java.io.Writer
        java.io.PipedWriter

All Implemented Interfaces:

Closeable, Flushable, Appendable, AutoCloseable

```
public class PipedWriter
extends Writer
```

Piped character-output streams.

Since:

1.1

Field Summary

Fields declared in class Writer
lock

Constructor Summary

Constructors

Constructor	Description
PipedWriter()	Creates a piped writer that is not yet connected to a piped reader.
PipedWriter(PipedReader snk)	Creates a piped writer connected to the specified piped reader.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
void	close()	Closes this piped output stream and releases any system resources associated with this stream.

void	**connect**(PipedReader snk)	Connects this piped writer to a receiver.
void	**flush**()	Flushes this output stream and forces any buffered output characters to be written out.
void	**write**(char[] cbuf, int off, int len)	Writes len characters from the specified character array starting at offset off to this piped output stream.
void	**write**(int c)	Writes the specified char to the piped output stream.

Methods declared in class Writer

append, append, append, nullWriter, write, write, write

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Details

PipedWriter

```
public PipedWriter(PipedReader snk)
            throws IOException
```

Creates a piped writer connected to the specified piped reader. Data characters written to this stream will then be available as input from snk.

Parameters:

snk - The piped reader to connect to.

Throws:

IOException - if an I/O error occurs.

PipedWriter

```
public PipedWriter()
```

Creates a piped writer that is not yet connected to a piped reader. It must be connected to a piped reader, either by the receiver or the sender, before being used.

See Also:

`PipedReader.connect(java.io.PipedWriter)`, `connect(java.io.PipedReader)`

Method Details

connect

```
public void connect(PipedReader snk)
             throws IOException
```

Connects this piped writer to a receiver. If this object is already connected to some other piped reader, an `IOException` is thrown.

If `snk` is an unconnected piped reader and `src` is an unconnected piped writer, they may be connected by either the call:

```
    src.connect(snk)
```

or the call:

```
    snk.connect(src)
```

The two calls have the same effect.

Parameters:

`snk` - the piped reader to connect to.

Throws:

`IOException` - if an I/O error occurs.

write

```
public void write(int c)
           throws IOException
```

Writes the specified `char` to the piped output stream. If a thread was reading data characters from the connected piped input stream, but the thread is no longer alive, then an `IOException` is thrown.

Implements the `write` method of `Writer`.

Overrides:

`write` in class `Writer`

Parameters:

`c` - the `char` to be written.

Throws:

`IOException` - if the pipe is `broken`, `unconnected`, closed or an I/O error occurs.

write

```
public void write(char[] cbuf,
                  int off,
                  int len)
           throws IOException
```

Writes `len` characters from the specified character array starting at offset `off` to this piped output stream. This method blocks until all the characters are written to the output stream. If a thread was reading data characters from the connected piped input stream, but the thread is no longer alive, then an `IOException` is thrown.

Specified by:

`write` in class `Writer`

Parameters:

`cbuf` - the data.

`off` - the start offset in the data.

`len` - the number of characters to write.

Throws:

`IndexOutOfBoundsException` - If `off` is negative, or `len` is negative, or `off + len` is negative or greater than the length of the given array

`IOException` - if the pipe is `broken`, `unconnected`, closed or an I/O error occurs.

flush

```
public void flush()
           throws IOException
```

Flushes this output stream and forces any buffered output characters to be written out. This will notify any readers that characters are waiting in the pipe.

Specified by:

`flush` in interface `Flushable`

Specified by:

`flush` in class `Writer`

Throws:

`IOException` - if the pipe is closed, or an I/O error occurs.

close

```
public void close()
           throws IOException
```

Closes this piped output stream and releases any system resources associated with this stream. This stream may no longer be used for writing characters.

Specified by:

`close` in interface `AutoCloseable`

Specified by:

`close` in interface `Closeable`

Specified by:

`close` in class `Writer`

Throws:

`IOException` - if an I/O error occurs.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.