JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class StringBufferInputStream

java.lang.Object
    java.io.InputStream
        java.io.StringBufferInputStream

All Implemented Interfaces:

Closeable, AutoCloseable

```
@Deprecated
public class StringBufferInputStream
extends InputStream
```

Deprecated.
This class does not properly convert characters into bytes. As of JDK 1.1, the preferred way to create a stream from a string is via the `StringReader` class.

This class allows an application to create an input stream in which the bytes read are supplied by the contents of a string. Applications can also read bytes from a byte array by using a `ByteArrayInputStream`.

Only the low eight bits of each character in the string are used by this class.

Since:

1.0

See Also:

ByteArrayInputStream, StringReader

Field Summary

Fields

Modifier and Type	Field	Description
protected String	buffer	**Deprecated.** The string from which bytes are read.
protected int	count	**Deprecated.** The number of valid characters in the input stream buffer.
protected int	pos	**Deprecated.**

	The index of the next character to read from the input stream buffer.

Constructor Summary

Constructors

Constructor	Description
`StringBufferInputStream(String s)`	**Deprecated.** Creates a string input stream to read data from the specified string.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`int`	`available()`	**Deprecated.** Returns the number of bytes that can be read from the input stream without blocking.
`int`	`read()`	**Deprecated.** Reads the next byte of data from this input stream.
`int`	`read(byte[] b, int off, int len)`	**Deprecated.** Reads up to `len` bytes of data from this input stream into an array of bytes.
`void`	`reset()`	**Deprecated.** Resets the input stream to begin reading from the first character of this input stream's underlying buffer.

long	skip(long n)	**Deprecated.** Skips n bytes of input from this input stream.

Methods declared in class InputStream

close, mark, markSupported, nullInputStream, read, readAllBytes, readNBytes, readNBytes, skipNBytes, transferTo

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Details

buffer

```
protected String buffer
```

Deprecated.

The string from which bytes are read.

pos

```
protected int pos
```

Deprecated.

The index of the next character to read from the input stream buffer.

See Also:

buffer

count

```
protected int count
```

Deprecated.

The number of valid characters in the input stream buffer.

See Also:

`buffer`

Constructor Details

StringBufferInputStream

```
public StringBufferInputStream(String s)
```

Deprecated.

Creates a string input stream to read data from the specified string.

Parameters:

`s` - the underlying input buffer.

Method Details

read

```
public int read()
```

Deprecated.

Reads the next byte of data from this input stream. The value byte is returned as an `int` in the range `0` to `255`. If no byte is available because the end of the stream has been reached, the value `-1` is returned.

Specified by:

`read` in class `InputStream`

Implementation Requirements:

The `read` method of `StringBufferInputStream` cannot block. It returns the low eight bits of the next character in this input stream's buffer.

Returns:

the next byte of data, or `-1` if the end of the stream is reached.

read

```
public int read(byte[] b,
                int off,
                int len)
```

Deprecated.

Reads up to `len` bytes of data from this input stream into an array of bytes.

Overrides:

`read` in class `InputStream`

Implementation Requirements:

The `read` method of `StringBufferInputStream` cannot block. It copies the low eight bits from the characters in this input stream's buffer into the byte array argument.

Parameters:

`b` - the buffer into which the data is read.

`off` - the start offset in array `b` at which the data is written.

`len` - the maximum number of bytes to read.

Returns:

the total number of bytes read into the buffer, or `-1` if there is no more data because the end of the stream has been reached.

See Also:

`InputStream.read()`

skip

```
public long skip(long n)
```

Deprecated.

Skips `n` bytes of input from this input stream. Fewer bytes might be skipped if the end of the input stream is reached.

Overrides:

`skip` in class `InputStream`

Parameters:

`n` - the number of bytes to be skipped.

Returns:

the actual number of bytes skipped.

See Also:

`InputStream.skipNBytes(long)`

available

```
public int available()
```

Deprecated.

Returns the number of bytes that can be read from the input stream without blocking.

Overrides:

`available` in class `InputStream`

Returns:

the value of `count - pos`, which is the number of bytes remaining to be read from the input buffer.

reset

```
public void reset()
```

Deprecated.

Resets the input stream to begin reading from the first character of this input stream's underlying buffer.

Overrides:

`reset` in class `InputStream`

See Also:

`InputStream.mark(int)`, `IOException`

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.