JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class WriteAbortedException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.io.IOException
        java.io.ObjectStreamException
          java.io.WriteAbortedException

All Implemented Interfaces:

Serializable

```
public class WriteAbortedException
extends ObjectStreamException
```

Signals that one of the ObjectStreamExceptions was thrown during a write operation. Thrown during a read operation when one of the ObjectStreamExceptions was thrown during a write operation. The exception that terminated the write can be found in the detail field. The stream is reset to its initial state and all references to objects already deserialized are discarded.

Since:

1.1

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
Exception	**detail**	**Deprecated.** This field predates the general-purpose exception chaining facility.

Constructor Summary

Constructors

Constructor	Description
WriteAbortedException(String s, Exception ex)	Constructs a WriteAbortedException with a string describing the

exception and the exception causing the abort.

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
Throwable	**getCause**()	Returns the exception that terminated the operation (the *cause*).
String	**getMessage**()	Produce the message and include the message from the nested exception, if there is one.

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getLocalizedMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Field Details

detail

```
@Deprecated(since="17")
public Exception detail
```

Deprecated.
This field predates the general-purpose exception chaining facility. The `Throwable.getCause()` method is now the preferred means of obtaining this information.

Exception that was caught while writing the ObjectStream.

Constructor Details

WriteAbortedException

```
public WriteAbortedException(String s,
                             Exception ex)
```

Constructs a WriteAbortedException with a string describing the exception and the exception causing the abort.

Parameters:

`s` - String describing the exception.

`ex` - Exception causing the abort.

Method Details

getMessage

```
public String getMessage()
```

Produce the message and include the message from the nested exception, if there is one.

Overrides:

`getMessage` in class `Throwable`

Returns:

the detail message string of this `Throwable` instance (which may be `null`).

getCause

```
public Throwable getCause()
```

Returns the exception that terminated the operation (the *cause*).

Overrides:

`getCause` in class `Throwable`

Returns:

the exception that terminated the operation (the *cause*), which may be null.

Since:

1.4

---

contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.

Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.

Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.

All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.