JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Character.Subset

java.lang.Object
    java.lang.Character.Subset

Direct Known Subclasses:

Character.UnicodeBlock, InputSubset

Enclosing class:

Character

```
public static class Character.Subset
extends Object
```

Instances of this class represent particular subsets of the Unicode character set. The only family of subsets defined in the `Character` class is `Character.UnicodeBlock`. Other portions of the Java API may define other subsets for their own purposes.

Since:

1.2

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**Subset**(String name)	Constructs a new Subset instance.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
final boolean	**equals**(Object obj)	Compares two Subset objects for equality.
final int	**hashCode**()	Returns the standard hash code as defined by the Object.hashCode() method.
final String	**toString**()	Returns the name of this subset.

Methods declared in class Object

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

Subset

```
protected Subset(String name)
```

Constructs a new `Subset` instance.

Parameters:

`name` - The name of this subset

Throws:

`NullPointerException` - if name is `null`

Method Details

equals

```
public final boolean equals(Object obj)
```

Compares two `Subset` objects for equality. This method returns `true` if and only if `this` and the argument refer to the same object; since this method is `final`, this guarantee holds for all subclasses.

Overrides:

`equals` in class `Object`

Parameters:

`obj` - the reference object with which to compare.

Returns:

`true` if this object is the same as the obj argument; `false` otherwise.

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public final int hashCode()
```

Returns the standard hash code as defined by the `Object.hashCode()` method. This method is `final` in order to ensure that the `equals` and `hashCode` methods will be consistent in all subclasses.

Overrides:

hashCode in class Object

Returns:

a hash code value for this object

See Also:

Object.equals(java.lang.Object),
System.identityHashCode(Object)

toString

```
public final String toString()
```

Returns the name of this subset.

Overrides:

toString in class Object

Returns:

a string representation of the object

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.