JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class InternalError

java.lang.Object
  java.lang.Throwable
    java.lang.Error
      java.lang.VirtualMachineError
        java.lang.InternalError

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

ZipError

```
public class InternalError
extends VirtualMachineError
```

Thrown to indicate some unexpected internal error has occurred in the Java Virtual Machine.

Since:

1.0

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`InternalError()`	Constructs an `InternalError` with no detail message.
`InternalError(String message)`	Constructs an `InternalError` with the specified detail message.
`InternalError(String message, Throwable cause)`	Constructs an `InternalError` with the specified detail message and cause.
`InternalError(Throwable cause)`	Constructs an `InternalError` with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

InternalError

```
public InternalError()
```

Constructs an `InternalError` with no detail message.

InternalError

```
public InternalError(String message)
```

Constructs an `InternalError` with the specified detail message.

Parameters:

`message` - the detail message.

InternalError

```
public InternalError(String message,
                     Throwable cause)
```

Constructs an `InternalError` with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this error's detail message.

Parameters:

`message` - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).

cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.8

InternalError

`public InternalError(Throwable cause)`

Constructs an `InternalError` with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Parameters:

cause - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.8

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.