JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class RuntimePermission

java.lang.Object
    java.security.Permission
        java.security.BasicPermission
            java.lang.RuntimePermission

All Implemented Interfaces:

Serializable, Guard

```
@Deprecated(since="25",
            forRemoval=true)
public final class RuntimePermission
extends BasicPermission
```

Deprecated, for removal: This API element is subject to removal in a future version.
This permission cannot be used for controlling access to resources as the Security Manager is no longer supported.

This class is for runtime permissions. A `RuntimePermission` contains a name (also referred to as a "target name") but no actions list; you either have the named permission or you don't.

The target name is the name of the runtime permission. The naming convention follows the hierarchical property naming convention, typically the reverse domain name notation, to avoid name clashes. An asterisk may appear at the end of the name, following a ".", or by itself, to signify a wildcard match. For example: "loadLibrary.*" and "*" signify a wildcard match, while "*loadLibrary" and "a*b" do not.

Since:

1.2

See Also:

BasicPermission, Permission, Permissions, PermissionCollection, SecurityManager, Serialized Form

Constructor Summary

Constructors

Constructor	Description
`RuntimePermission(String name)`	**Deprecated, for removal: This API element is subject to removal in a future version.**

	Creates a new RuntimePermission with the specified name.
`RuntimePermission(String name, String actions)`	**Deprecated, for removal: This API element is subject to removal in a future version.** Creates a new RuntimePermission object with the specified name.

Method Summary

Methods declared in class BasicPermission

`equals`, `getActions`, `hashCode`, `implies`, `newPermissionCollection`

Methods declared in class Permission

`checkGuard`, `getName`, `toString`

Methods declared in class Object

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

RuntimePermission

```
public RuntimePermission(String name)
```

Deprecated, for removal: This API element is subject to removal in a future version.

Creates a new RuntimePermission with the specified name. The name is the symbolic name of the RuntimePermission, such as "exit", "setFactory", etc. An asterisk may appear at the end of the name, following a ".", or by itself, to signify a wildcard match.

Parameters:

`name` - the name of the RuntimePermission.

Throws:

NullPointerException - if name is null.

IllegalArgumentException - if name is empty.

RuntimePermission

```
public RuntimePermission(String name,
                         String actions)
```

Deprecated, for removal: This API element is subject to removal in a future version.

Creates a new RuntimePermission object with the specified name. The name is the symbolic name of the RuntimePermission, and the actions String is currently unused and should be null.

Parameters:

name - the name of the RuntimePermission.

actions - should be null.

Throws:

NullPointerException - if name is null.

IllegalArgumentException - if name is empty.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.