JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Annotation Interface Repeatable

```
@Documented
@Retention(RUNTIME)
@Target(ANNOTATION_TYPE)
public @interface Repeatable
```

The annotation interface `java.lang.annotation.Repeatable` is used to indicate that the annotation interface whose declaration it (meta-)annotates is *repeatable*. The value of `@Repeatable` indicates the *containing annotation interface* for the repeatable annotation interface.

See *Java Language Specification*:

9.6.3 Repeatable Annotation Interfaces
9.7.5 Multiple Annotations of the Same Interface

Since:

1.8

Required Element Summary

Required Elements

Modifier and Type	Required Element	Description
`Class<? extends Annotation>`	**`value`**	Indicates the *containing annotation interface* for the repeatable annotation interface.

Element Details

value

`Class<? extends Annotation> value`

Indicates the *containing annotation interface* for the repeatable annotation interface.

Returns:

the containing annotation interface

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other

countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.