JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface CompilationMXBean

All Superinterfaces:

`PlatformManagedObject`

```
public interface CompilationMXBean
extends PlatformManagedObject
```

The management interface for the compilation system of the Java virtual machine.

A Java virtual machine has a single instance of the implementation class of this interface. This instance implementing this interface is an MXBean that can be obtained by calling the `ManagementFactory.getCompilationMXBean()` method or from the `platform MBeanServer` method.

The `ObjectName` for uniquely identifying the MXBean for the compilation system within an MBeanServer is:

```
java.lang:type=Compilation
```

It can be obtained by calling the `PlatformManagedObject.getObjectName()` method.

Since:

1.5

See Also:

`ManagementFactory.getPlatformMXBeans(Class)`,
JMX Specification.,
Ways to Access MXBeans

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
`String`	**`getName`**`()`	Returns the name of the Just-in-time (JIT) compiler.
`long`	**`getTotalCompilationTime`**`(`	Returns the approximate accumulated elapsed time (in milliseconds) spent in compilation.
`boolean`	**`isCompilationTimeMonitor`**	

	Tests if the Java virtual machine supports the monitoring of compilation time.

Methods declared in interface PlatformManagedObject

`getObjectName`

Method Details

getName

`String getName()`

Returns the name of the Just-in-time (JIT) compiler.

Returns:

the name of the JIT compiler.

isCompilationTimeMonitoringSupported

`boolean isCompilationTimeMonitoringSupported()`

Tests if the Java virtual machine supports the monitoring of compilation time.

Returns:

`true` if the monitoring of compilation time is supported; `false` otherwise.

getTotalCompilationTime

`long getTotalCompilationTime()`

Returns the approximate accumulated elapsed time (in milliseconds) spent in compilation. If multiple threads are used for compilation, this value is summation of the approximate time that each thread spent in compilation.

This method is optionally supported by the platform. A Java virtual machine implementation may not support the compilation time monitoring. The `isCompilationTimeMonitoringSupported()` method can be used to determine if the Java virtual machine supports this operation.

This value does not indicate the level of performance of the Java virtual machine and is not intended for performance comparisons of different virtual machine implementations. The implementations may have different definitions and different measurements of the compilation time.

Returns:

Compilation time in milliseconds

Throws:

`UnsupportedOperationException` - if the Java virtual machine does not support this operation.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.