JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class LockInfo

java.lang.Object
    java.lang.management.LockInfo

Direct Known Subclasses:

MonitorInfo

```
public class LockInfo
extends Object
```

Information about a *lock*. A lock can be a built-in object monitor, an *ownable synchronizer,* or the Condition object associated with synchronizers.

An ownable synchronizer is a synchronizer that may be exclusively owned by a thread and uses AbstractOwnableSynchronizer (or its subclass) to implement its synchronization property. ReentrantLock and the write-lock (but not the read-lock) of ReentrantReadWriteLock are two examples of ownable synchronizers provided by the platform.

MXBean Mapping

LockInfo is mapped to a CompositeData as specified in the from method.

Since:

1.6

See Also:

AbstractOwnableSynchronizer, Condition

Constructor Summary

Constructors

Constructor	Description
LockInfo(String className, int identityHashCode)	Constructs a LockInfo object.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
static LockInfo	**from**(CompositeData cd)	Returns a LockInfo object represented by

		the given `CompositeData`.
`String`	**`getClassName`**`()`	Returns the fully qualified name of the class of the lock object.
`int`	**`getIdentityHashCode`**`()`	Returns the identity hash code of the lock object returned from the `System.identityHashCode(Object)` method.
`String`	**`toString`**`()`	Returns a string representation of a lock.

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

LockInfo

```
public LockInfo(String className,
                int identityHashCode)
```

Constructs a `LockInfo` object.

Parameters:

`className` - the fully qualified name of the class of the lock object.

`identityHashCode` - the `identity hash code` of the lock object.

Method Details

getClassName

```
public String getClassName()
```

Returns the fully qualified name of the class of the lock object.

Returns:

the fully qualified name of the class of the lock object.

getIdentityHashCode

```
public int getIdentityHashCode()
```

Returns the identity hash code of the lock object returned from the `System.identityHashCode(Object)` method.

Returns:

the identity hash code of the lock object.

from

```
public static LockInfo from(CompositeData cd)
```

Returns a `LockInfo` object represented by the given `CompositeData`.
The given `CompositeData` must contain the following attributes:

Attribute Name	Type
className	`java.lang.String`
identityHashCode	`java.lang.Integer`

Parameters:

`cd` - `CompositeData` representing a `LockInfo`

Returns:

a `LockInfo` object represented by `cd` if `cd` is not `null`; `null` otherwise.

Throws:

`IllegalArgumentException` - if `cd` does not represent a `LockInfo` with the attributes described above.

Since:

1.8

toString

```
public String toString()
```

Returns a string representation of a lock. The returned string representation consists of the name of the class of the lock object, the at-sign character `@', and the unsigned hexadecimal representation of the *identity* hash code of the object. This method returns a string equals to the value of:

```
lock.getClass().getName() + '@' + Integer.toHexString(System.identityHashCo
```

where `lock` is the lock object.

Overrides:

`toString` in class `Object`

Returns:

the string representation of a lock.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.