JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class MonitorInfo

java.lang.Object
    java.lang.management.LockInfo
        java.lang.management.MonitorInfo

```
public class MonitorInfo
extends LockInfo
```

Information about an object monitor lock. An object monitor is locked when entering a synchronization block or method on that object.

MXBean Mapping

`MonitorInfo` is mapped to a `CompositeData` with attributes as specified in the `from` method.

Since:

1.6

Constructor Summary

Constructors

Constructor	Description
`MonitorInfo(String className, int identityHashCode, int stackDepth, StackTraceElement stackFrame)`	Construct a `MonitorInfo` object.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
`static MonitorInfo`	`from(CompositeData cd)`	Returns a `MonitorInfo` object represented by the given `CompositeData`.
`int`	`getLockedStackDepth()`	Returns the depth in the stack trace where the object monitor was locked.
`StackTraceElement`	`getLockedStackFrame()`	

	Returns the stack frame that locked the object monitor.

Methods declared in class LockInfo

`getClassName`, `getIdentityHashCode`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

MonitorInfo

```
public MonitorInfo(String className,
                   int identityHashCode,
                   int stackDepth,
                   StackTraceElement stackFrame)
```

Construct a `MonitorInfo` object.

Parameters:

`className` - the fully qualified name of the class of the lock object.

`identityHashCode` - the `identity hash code` of the lock object.

`stackDepth` - the depth in the stack trace where the object monitor was locked.

`stackFrame` - the stack frame that locked the object monitor.

Throws:

`IllegalArgumentException` - if `stackDepth` ≥ 0 but `stackFrame` is `null`, or `stackDepth` < 0 but `stackFrame` is not `null`.

Method Details

getLockedStackDepth

```
public int getLockedStackDepth()
```

Returns the depth in the stack trace where the object monitor was locked. The depth is the index to the `StackTraceElement` array returned in the `ThreadInfo.getStackTrace()` method.

Returns:

the depth in the stack trace where the object monitor was locked, or a negative number if not available.

getLockedStackFrame

`public StackTraceElement getLockedStackFrame()`

Returns the stack frame that locked the object monitor.

Returns:

`StackTraceElement` that locked the object monitor, or `null` if not available.

from

`public static MonitorInfo from(CompositeData cd)`

Returns a `MonitorInfo` object represented by the given `CompositeData`. The given `CompositeData` must contain the following attributes as well as the attributes specified in the mapped type for the `LockInfo` class:

Attribute Name	Type
lockedStackFrame	`CompositeData` for `StackTraceElement` as specified in `ThreadInfo.from(CompositeData)` method.
lockedStackDepth	`java.lang.Integer`

Parameters:

`cd` - `CompositeData` representing a `MonitorInfo`

Returns:

a `MonitorInfo` object represented by `cd` if `cd` is not `null`; `null` otherwise.

Throws:

`IllegalArgumentException` - if `cd` does not represent a `MonitorInfo` with the attributes described above.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.