JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface AnnotatedWildcardType

All Superinterfaces:

AnnotatedElement, AnnotatedType

---

public interface **AnnotatedWildcardType**
extends AnnotatedType

AnnotatedWildcardType represents the potentially annotated use of a wildcard type argument, whose upper or lower bounds may themselves represent annotated uses of types.

See *Java Language Specification*:

4.5.1 Type Arguments of Parameterized Types

Since:

1.8

Method Summary

All Methods | Instance Methods

Modifier and Type	Method	Description
AnnotatedType[]	**getAnnotatedLowerBounds**()	Returns the potentially annotated lower bounds of this wildcard type.
AnnotatedType	**getAnnotatedOwnerType**()	Returns the potentially annotated type that this type is a member of, if this type represents a nested type.
AnnotatedType[]	**getAnnotatedUpperBounds**()	Returns the potentially annotated upper bounds of this wildcard type.

Methods declared in interface AnnotatedElement

getAnnotationsByType, getDeclaredAnnotation, getDeclaredAnnotationsByType, isAnnotationPresent

Methods declared in interface AnnotatedType

`getAnnotation`, `getAnnotations`, `getDeclaredAnnotations`, `getType`

Method Details

getAnnotatedLowerBounds

`AnnotatedType[] getAnnotatedLowerBounds()`

Returns the potentially annotated lower bounds of this wildcard type. If no lower bound is explicitly declared, the lower bound is the type of null. In this case, a zero length array is returned.

API Note:

While to date a wildcard may have at most one lower bound, callers of this method should be written to accommodate multiple bounds.

Returns:

the potentially annotated lower bounds of this wildcard type or an empty array if no lower bound is explicitly declared.

See Also:

`WildcardType.getLowerBounds()`

getAnnotatedUpperBounds

`AnnotatedType[] getAnnotatedUpperBounds()`

Returns the potentially annotated upper bounds of this wildcard type. If no upper bound is explicitly declared, the upper bound is unannotated `Object`

API Note:

While to date a wildcard may have at most one upper bound, callers of this method should be written to accommodate multiple bounds.

Returns:

the potentially annotated upper bounds of this wildcard type

See Also:

`WildcardType.getUpperBounds()`

getAnnotatedOwnerType

`AnnotatedType getAnnotatedOwnerType()`

Returns the potentially annotated type that this type is a member of, if this type represents a nested type. For example, if this type is `@TA O<T>.I<S>`, return a representation of `@TA O<T>`.

Returns `null` for an `AnnotatedType` that is an instance of `AnnotatedWildcardType`.

Specified by:

`getAnnotatedOwnerType` in interface `AnnotatedType`

Returns:

`null`

Since:

9

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.