JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface Member

All Known Implementing Classes:

Constructor, Executable, Field, Method

`public interface Member`

Member is an interface that reflects identifying information about a single member (a field or a method) or a constructor.

Since:

1.1

See Also:

Class, Field, Method, Constructor

Field Summary

Fields

Modifier and Type	Field	Description
`static final int`	**DECLARED**	Identifies the set of declared members of a class or interface.
`static final int`	**PUBLIC**	Identifies the set of all public members of a class or interface, including inherited members.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
`default Set<AccessFlag>`	**accessFlags**()	Returns an unmodifiable set of the access flags for this member, possibly empty.
`Class<?>`	**getDeclaringClass**()	Returns the Class object representing the class or interface that declares the member or

		constructor represented by this Member.
int	**getModifiers**()	Returns the Java language modifiers for the member or constructor represented by this Member, as an integer.
String	**getName**()	Returns the simple name of the underlying member or constructor represented by this Member.
boolean	**isSynthetic**()	Returns `true` if this member was introduced by the compiler; returns `false` otherwise.

Field Details

PUBLIC

`static final int PUBLIC`

Identifies the set of all public members of a class or interface, including inherited members.

See Also:

Constant Field Values

DECLARED

`static final int DECLARED`

Identifies the set of declared members of a class or interface. Inherited members are not included.

See Also:

Constant Field Values

Method Details

getDeclaringClass

`Class<?> getDeclaringClass()`

Returns the Class object representing the class or interface that declares the member or constructor represented by this Member.

Returns:

an object representing the declaring class of the underlying member

getName

`String getName()`

Returns the simple name of the underlying member or constructor represented by this Member.

Returns:

the simple name of the underlying member

getModifiers

`int getModifiers()`

Returns the Java language modifiers for the member or constructor represented by this Member, as an integer. The Modifier class should be used to decode the modifiers in the integer.

Returns:

the Java language modifiers for the underlying member

See Also:

`Modifier`, `accessFlags()`

accessFlags

`default Set<AccessFlag> accessFlags()`

Returns an unmodifiable set of the access flags for this member, possibly empty.

Implementation Requirements:

The default implementation throws `UnsupportedOperationException`.

Returns:

an unmodifiable set of the access flags for this member, possibly empty

Since:

20

See Also:

`getModifiers()`

isSynthetic

`boolean isSynthetic()`

Returns `true` if this member was introduced by the compiler; returns `false` otherwise.

Returns:

true if and only if this member was introduced by the compiler.

See *Java Language Specification*:

13.1 The Form of a Binary

Since:

1.5

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.