JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Interface ParameterizedType

All Superinterfaces:

Type

```
public interface ParameterizedType
extends Type
```

ParameterizedType represents a parameterized type such as `Collection<String>`.

A parameterized type is created the first time it is needed by a reflective method, as specified in this package. When a parameterized type p is created, the generic class or interface declaration that p instantiates is resolved, and all type arguments of p are created recursively. See `TypeVariable` for details on the creation process for type variables. Repeated creation of a parameterized type has no effect.

Instances of classes that implement this interface must implement an equals() method that equates any two instances that share the same generic class or interface declaration and have equal type parameters.

See *Java Language Specification*:

4.5 Parameterized Types

Since:

1.5

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
Type[]	**getActualTypeArguments**()	Returns an array of Type objects representing the actual type arguments to this type.
Type	**getOwnerType**()	Returns a Type object representing the type that this type is a member of.
Type	**getRawType**()	Returns the Type object representing the class or

	interface that declared this type.

Methods declared in interface Type

`getTypeName`

Method Details

getActualTypeArguments

`Type[] getActualTypeArguments()`

Returns an array of `Type` objects representing the actual type arguments to this type.

Note that in some cases, the returned array be empty. This can occur if this type represents a non-parameterized type nested within a parameterized type.

Returns:

an array of `Type` objects representing the actual type arguments to this type

Throws:

`TypeNotPresentException` - if any of the actual type arguments refers to a non-existent class or interface declaration

`MalformedParameterizedTypeException` - if any of the actual type parameters refer to a parameterized type that cannot be instantiated for any reason

Since:

1.5

getRawType

`Type getRawType()`

Returns the `Type` object representing the class or interface that declared this type.

API Note:

All `ParameterizedType` objects from core reflection return a `Class`. The static `Type` return type allows other implementations to represent classes and interfaces not in the current runtime.

Returns:

the Type object representing the class or interface that declared this type

Since:

1.5

getOwnerType

`Type getOwnerType()`

Returns a Type object representing the type that this type is a member of. For example, if this type is `O<T>.I<S>`, return a representation of `O<T>`.

If this type is a top-level type, `null` is returned.

Returns:

a Type object representing the type that this type is a member of. If this type is a top-level type, `null` is returned

Throws:

`TypeNotPresentException` - if the owner type refers to a non-existent class or interface declaration

`MalformedParameterizedTypeException` - if the owner type refers to a parameterized type that cannot be instantiated for any reason

Since:

1.5

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.