JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class UndeclaredThrowableException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.reflect.UndeclaredThrowableException

All Implemented Interfaces:

Serializable

```
public class UndeclaredThrowableException
extends RuntimeException
```

Thrown by a method invocation on a proxy instance if its invocation handler's `invoke` method throws a checked exception (a `Throwable` that is not assignable to `RuntimeException` or `Error`) that is not assignable to any of the exception types declared in the `throws` clause of the method that was invoked on the proxy instance and dispatched to the invocation handler.

An `UndeclaredThrowableException` instance contains the undeclared checked exception that was thrown by the invocation handler, and it can be retrieved with the `getUndeclaredThrowable()` method. `UndeclaredThrowableException` extends `RuntimeException`, so it is an unchecked exception that wraps a checked exception.

Since:

1.3

See Also:

`InvocationHandler`, Serialized Form

Constructor Summary

Constructors

Constructor	Description
`UndeclaredThrowableException``(Throwable undeclaredThrowable)`	Constructs an `UndeclaredThrowableException` with the specified `Throwable`.
`UndeclaredThrowableException``(Throwable undeclaredThrowable, String s)`	Constructs an `UndeclaredThrowableException` with the specified `Throwable` and a detail message.

Method Summary

All Methods	Instance Methods	

Modifier and Type	Method	Description
Throwable	**getUndeclaredThrowable()**	Returns the Throwable instance wrapped in this UndeclaredThrowableException, which may be null.

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

UndeclaredThrowableException

```
public UndeclaredThrowableException(Throwable undeclaredThrowable)
```

Constructs an UndeclaredThrowableException with the specified Throwable.

Parameters:

undeclaredThrowable - the undeclared checked exception that was thrown, may be null

UndeclaredThrowableException

```
public UndeclaredThrowableException(Throwable undeclaredThrowable,
                                    String s)
```

Constructs an UndeclaredThrowableException with the specified Throwable and a detail message.

Parameters:

undeclaredThrowable - the undeclared checked exception that was thrown, may be null

s - the detail message, may be `null`

Method Details

getUndeclaredThrowable

```
public Throwable getUndeclaredThrowable()
```

Returns the `Throwable` instance wrapped in this `UndeclaredThrowableException`, which may be `null`.

API Note:

This method predates the general-purpose exception chaining facility. The `Throwable.getCause()` method is now the preferred means of obtaining this information.

Returns:

the undeclared checked exception that was thrown

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.