JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Enum Class ByteOrder

java.lang.Object
    java.lang.Enum<ByteOrder>
        java.nio.ByteOrder

All Implemented Interfaces:

Serializable, Comparable<ByteOrder>, Constable

```
public enum ByteOrder
extends Enum<ByteOrder>
```

A typesafe enumeration for byte orders.

Since:

1.4

Nested Class Summary

Nested classes/interfaces declared in class Enum
Enum.EnumDesc<E>

Enum Constant Summary

Enum Constants

Enum Constant	Description
BIG_ENDIAN	Constant denoting big-endian byte order.
LITTLE_ENDIAN	Constant denoting little-endian byte order.

Method Summary

All Methods | **Static Methods**

Modifier and Type	Method	Description
static ByteOrder	**nativeOrder**()	Retrieves the native byte order of the underlying platform.
static ByteOrder	**valueOf**(String name)	

	Returns the enum constant of this class with the specified name.
`static ByteOrder[] values()`	Returns an array containing the constants of this enum class, in the order they are declared.

Methods declared in class Enum

`clone`, `compareTo`, `describeConstable`, `equals`, `finalize`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods declared in class Object

`getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Enum Constant Details

LITTLE_ENDIAN

```
public static final ByteOrder LITTLE_ENDIAN
```

Constant denoting little-endian byte order. In this order, the bytes of a multibyte value are ordered from least significant to most significant.

BIG_ENDIAN

```
public static final ByteOrder BIG_ENDIAN
```

Constant denoting big-endian byte order. In this order, the bytes of a multibyte value are ordered from most significant to least significant.

Method Details

values

```
public static ByteOrder[] values()
```

Returns an array containing the constants of this enum class, in the order they are declared.

Returns:

an array containing the constants of this enum class, in the order they are declared

valueOf

```
public static ByteOrder valueOf(String name)
```

Returns the enum constant of this class with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this class. (Extraneous whitespace characters are not permitted.)

Parameters:

`name` - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`IllegalArgumentException` - if this enum class has no constant with the specified name

`NullPointerException` - if the argument is null

nativeOrder

```
public static ByteOrder nativeOrder()
```

Retrieves the native byte order of the underlying platform.

This method is defined so that performance-sensitive Java code can allocate direct buffers with the same byte order as the hardware. Native code libraries are often more efficient when such buffers are used.

Returns:

The native byte order of the hardware upon which this Java virtual machine is running

---

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.