JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class IllegalChannelGroupException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException
          java.nio.channels.IllegalChannelGroupException

All Implemented Interfaces:

Serializable

```
public class IllegalChannelGroupException
extends IllegalArgumentException
```

Unchecked exception thrown when an attempt is made to open a channel in a group that was not created by the same provider.

Since:

1.7

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IllegalChannelGroupException()`	Constructs an instance of this class.

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

IllegalChannelGroupException

```
public IllegalChannelGroupException()
```

Constructs an instance of this class.

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.