JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Pipe.SourceChannel

java.lang.Object
  java.nio.channels.spi.AbstractInterruptibleChannel
    java.nio.channels.SelectableChannel
      java.nio.channels.spi.AbstractSelectableChannel
        java.nio.channels.Pipe.SourceChannel

All Implemented Interfaces:

`Closeable`, `AutoCloseable`, `Channel`, `InterruptibleChannel`, `ReadableByteChannel`, `ScatteringByteChannel`

Enclosing class:

`Pipe`

```
public abstract static class Pipe.SourceChannel
extends AbstractSelectableChannel
implements ReadableByteChannel, ScatteringByteChannel
```

A channel representing the readable end of a `Pipe`.

Since:

1.4

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	`SourceChannel (SelectorProvider provid`	Constructs a new instance of this class.

Method Summary

All Methods | **Instance Methods**

Modifier and Type	Method	Description
final int	`validOps()`	Returns an operation set identifying this channel's supported operations.

Methods declared in class AbstractSelectableChannel

blockingLock, configureBlocking, implCloseChannel, implCloseSelectableChannel, implConfigureBlocking, isBlocking, isRegistered, keyFor, provider, register

Methods declared in class SelectableChannel

register

Methods declared in class AbstractInterruptibleChannel

begin, close, end, isOpen

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods declared in interface ReadableByteChannel

read

Methods declared in interface ScatteringByteChannel

read, read

Constructor Details

SourceChannel

```
protected SourceChannel(SelectorProvider provider)
```

Constructs a new instance of this class.

Parameters:

`provider` - The selector provider

Method Details

validOps

```
public final int validOps()
```

Returns an operation set identifying this channel's supported operations.

Pipe-source channels only support reading, so this method returns `SelectionKey.OP_READ`.

Specified by:

`validOps` in class `SelectableChannel`

Returns:

The valid-operation set

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.